


# DALI CABLING SYSTEM (3G2.5 mm<sup>2</sup> + DALI-Bus)

10

....



- decentralized installation, therefore a reduced cable quantity and thus minimum fire load
- DALI control and power supply on one flat cable for up to 64 DALI luminaires
- fast, flexible installation in site
- mounting safety through system coding

## woertz@

#### Woertz AG

Hofackerstrasse 47 Postfach 948 CH-4132 Muttenz info@woertz.ch www.woertz.ch



## Flat cable (3G2.5 mm<sup>2</sup> + DALI-Bus)


Woertz has developed a 1-phase bus flat cable with corresponding junction boxes.




#### technical data product Art. No. halogen free flat cable 48280/FRNC/OS cable type flat cable 3G2.5+2x1.5 mm<sup>2</sup> 49700D1 construction products regulation B2ca s1 d0 a1 junction box LNPE+Bus cable construction 3G2.5+2x1.5 mm<sup>2</sup>, LNPE+Bus junction box Bus 49702D1 sheath color pastel blue junction box LNPE+Bus C2 9715D1 polyolefin, flame retardant junction box Bus CW 49712D1 sheath and core insulation connectors C2 49345/.../C2 copper conductor fine wire tinned 600/1000 V AC device plug connections C2 49345/GA/.../C2 rated voltage 48510/05 fire load 1.79 kWh/m end piece

Power and bus conductors combined in a single cable 3G2.5+2x1.5 mm<sup>2</sup>. The bus conductors are dimensioned for 220-240 V.

### Applications for luminaire cabling





junction boxes

flat cable DALI 3G2.5+2x1.5 mm<sup>2</sup>





