




Product data sheet

51764 - Housing insert BAK4 aluminum



to BAK4, fixing to the ceiling formwork
consisting of:
Frame 304x304 of cast aluminum complete
and screwed collar, height 72mm
of sendzimir galvanized steel sheet 1.5mm

Characteristics	
Base Unit	Piece
availability	Delivery according to agreement
group	282000
Packaging unit	1
country of origin	CH
Customs tariff number	7308.9000
Weight (g)	1670 g



Product data sheet

51764 - Housing insert BAK4 aluminum

Product accessories



Product data sheet

51764 - Housing insert BAK4 aluminum

Product systems



Floor junction box BAK4 to slab formwork



Plenum box BAK4 for fastening to the slab formwork.

The installation of underfloor ducts requires a minimum height of the concrete cover (60mm). If this height is not available, special boxes can be obtained for concreting into the raw slab. After fastening to the formwork, they are connected to each other with underfloor trunking 200 x 40, covered with the temporary protective cover and poured into the concrete up to the top edge.

The installation kit is mounted on the levelable box insert; the opening between the box bottom and the installation plate allows the cable to pass through to the next box. After finished wiring, an aluminum cover with cable trough is attached.

Connection box consisting of:

- Enclosure with adjustable feet, with four side openings 202 x 42 mm and a bottom entry tube M50 with temporary one-way steel cover incl. 4 screws
 - Enclosure insert made of aluminum, with frame 304 x 304
 - Aluminum lid with edge height 4 mm
 - 2 cable trays made of polycarbonate crystal clear with transparent filler piece
-