



3430GR - Double level terminal DIN35 4mm<sup>2</sup> gray



Double deck clamp with stainless steel screws, countersunk for cross connections, 2x3-digit marking option on both sides

Characteristics	
Eldas number	158102237
Base Unit	Piece
availability	available from stock
EAN Code	7611718202568
group	165000
Packaging unit	50
country of origin	СН
Customs tariff number	8536.9080
Weight (g)	18 g
Color	gray
Technical data	
Dimensions length x width x height (mm)	64x6x49 mm
Dimensions length x width x height (inch)	2.52x0.24x1.93 inch
Cross section (mm <sup>2</sup> )	0,5 - 4 mm²
Nominal current (A)	32 A





### 3430GR - Double level terminal DIN35 4mm<sup>2</sup> gray

Rated voltage (V)	500 V
Connection type	Screw terminal
DIN rail type	DIN-35
Number of connection point	4
Number of floor	2
Number of potentials	2
Clamping screw M	МЗ
Insulating material	PA66
Nominal Cross-section (mm <sup>2</sup> )	4 mm²
Stripping length mm (mm)	10 mm
Head reception room width x height (mm)	3.2x5 mm
Rating data according to UL 1059	
Rated voltage US (V)	300 V
Nominal cross section (AWG)	12 AWG
Cross-section (AWG)	12 - 20 AWG
Stripping length (inch)	0,39 inch





3430GR - Double level terminal DIN35 4mm<sup>2</sup> gray

#### **Product accessories**

ŦŦ	81526/2 - Cross-connection 2pole to terminal 2.5mm2/4mm2 Cross connections complete with M3 screws. 11.1x17.8 mm
	81526/3 - Cross-connection 3-pole to terminals DIN15/32/35 2.5mm <sup>2</sup> /4mm <sup>2</sup> Insulated cross-connection 3-pole to terminals DIN15/32/35 2.5mm <sup>2</sup> /4mm <sup>2</sup> including screws M3. Dimension: 17.2x17.8 mm
	81526/4 - Cross-connection 4-pole to terminals DIN15/32/35 2.5mm <sup>2</sup> /4mm <sup>2</sup>
	Insulated cross-connection 4-pole to terminals DIN15/32/35 2.5mm <sup>2</sup> /4mm <sup>2</sup> including screws M3. Dimension: 23.3x17.8 mm
	81526/5 - Cross-connection 5-pole to terminals DIN15/32/35 2.5mm <sup>2</sup> /4mm <sup>2</sup>
	Insulated cross-connection 5-pole to terminals DIN15/32/35 2.5mm <sup>2</sup> /4mm <sup>2</sup> including screws M3. Dimension: 29.4x17.8 mm
	81526/10 - Cross-connection 10-pole to terminals DIN15/32/35 2.5mm <sup>2</sup> /4mm <sup>2</sup>
	Insulated cross-connection 10-pole to terminals DIN15/32/35 2.5mm <sup>2</sup> /4mm <sup>2</sup> including screws M3. Dimension: 59.9x17.8 mm
ų.	81526 - Cross connection bolt single M3, insulated (9.1 mm)
Ű	Cross connection bolt complete with spacer sleeve. 9.1 mm
	30441 - Link to cross-connections
	to terminals 4mm 2
	to terminals 4mm 2
	to terminals 4mm 2 80070R - Test plug Ø M3 red, socket 4mm
	to terminals 4mm 2 80070R - Test plug Ø M3 red, socket 4mm plug and adaptor in one piece
	to terminals 4mm 2 80070R - Test plug Ø M3 red, socket 4mm plug and adaptor in one piece 2737R - Test plug Ø 2.8mm red, socket 4mm
	to terminals 4mm 2 80070R - Test plug Ø M3 red, socket 4mm plug and adaptor in one piece 2737R - Test plug Ø 2.8mm red, socket 4mm connecting cable incl.
	to terminals 4mm 2 80070R - Test plug Ø M3 red, socket 4mm plug and adaptor in one piece 2737R - Test plug Ø 2.8mm red, socket 4mm connecting cable incl. 80222/6 - Test adaptor to terminal series 3450 2 spiral springs





3430GR - Double level terminal DIN35 4mm<sup>2</sup> gray

	Bezeichnungskarte_6x3mm - Designation card 6x3mm Various designation plates with different embossing.
	<b>3431 - End barrier DIN35 grey to 3430, 30860</b> End wall suitable for 3430, 30860
	<b>3432 - Partition DIN35 grey to 30860</b> Partition wall suitable for 30860
	80254 - Push-in barrier DIN35 to 30860, 3430 white
	<b>30199 - Stopper DIN35 height 50mm</b> Aluminum alloy locking piece
	<b>30791 - Cross-junction rack 10pole grey 6mm</b> to terminals with 6mm pin spacing
- D	<b>3894/4 - Cover for 4 terminals yellow</b> with black printing, to series 3430
- D	<b>3894/5 - Cover for 5 terminals yellow</b> with black printing, to series 3430
- D	<b>3894/6 - Cover for 6 terminals yellow</b> with black printing, to series 3430
- D	<b>3894/7 - Cover for 7 terminals yellow</b> with black printing, to series 3430
A Contraction of the second se	<b>3894/8 - Cover for 8 terminals yellow</b> with black printing, to series 3430
	81440 - Sealing eyelet Ø 3.2mm Sealing eyes





3430GR - Double level terminal DIN35 4mm<sup>2</sup> gray

ANE	<b>3512 - Sealing screw M3x25 of polyamide</b> Sealing screw spring-loaded test probes, several numbers of poles can be lined up
aunana	<b>30421 - Cover strip for double level and terminal blocks 9.5mm, length 280mm</b> Cover strip for double level and terminal blocks DIN32/35 9.5mm, length 280mm





3430GR - Double level terminal DIN35 4mm<sup>2</sup> gray

### **Product systems**



**Double deck clamps DIN 35** 

Various double-deck clamps.

