



3410BL - Double level terminal DIN35 6mm² blue



Double deck clamp with stainless steel screws, countersunk for cross connections, 2x3-digit marking option on both sides

Characteristics	
Eldas number	158102357
Base Unit	Piece
availability	Delivery according to agreement
EAN Code	7611718205491
group	165000
Packaging unit	25
country of origin	СН
Customs tariff number	8536.9080
Weight (g)	30 g
Color	blue
Technical data	
Dimensions length x width x height (mm)	78x7x64 mm
Dimensions length x width x height (inch)	3.07x0.28x2.52 inch
Cross section (mm ²)	0,5 - 6 mm²
Nominal current (A)	41 A





3410BL - Double level terminal DIN35 6mm² blue

Rated voltage (V)	500 V
Connection type	Screw terminal
DIN rail type	DIN-35
Number of connection point	4
Number of floor	2
Number of potentials	2
Clamping screw M	М3
Insulating material	PA66
Nominal Cross-section (mm ²)	6 mm²
Stripping length mm (mm)	9 mm
Head reception room width x height (mm)	3.8x5.7 mm
Rating data according to UL 1059	
Rated voltage US (V)	300 V
Nominal cross section (AWG)	10 AWG
Cross-section (AWG)	10 - 20 AWG
Stripping length (inch)	0,35 inch





3410BL - Double level terminal DIN35 6mm² blue

Product accessories

	80070R - Test plug Ø M3 red, socket 4mm
	plug and adaptor in one piece
	2737R - Test plug Ø 2.8mm red, socket 4mm
	connecting cable incl.
	Bezeichnungskarte_6x12mm - Designation cards 6x12mm
	Various designation labels 6x12mm with different embossing.
	Bezeichnungskarte_6x9mm - Designation card 6x9mm
	Various designation plates with different embossing.
	Bezeichnungskarte_6x3mm - Designation card 6x3mm
	Various designation plates with different embossing.
	3411 - End barrier DIN35 grey to 3410
	End wall suitable for 3410
	3412 - Partition DIN35 grey to 3410
	Partition wall suitable for 3410
· · · · · · · · · · · · · · · · · · ·	30199 - Stopper DIN35 height 50mm
	Aluminum alloy locking piece
Ħ	81507/2 - Cross-connection 2-pole to DIN32/35 6mm ² terminal blocks
	Insulated cross-connection 2-pole to terminal blocks DIN32/35 6mm ² including screws M2.5. dimension: 12.6x20.8 mm
TTT	81507/3 - Cross-connection 3-pole to terminals DIN32/35 6mm ²
	Insulated cross-connection 3-pole to terminals DIN32/35 6mm ² including screws M2. Dimension: 5.19.7x20.8 mm
	81507/4 - Cross-connection 4-pole to terminals DIN32/35 6mm ²
	Insulated cross-connection 4-pole to terminals DIN32/35 6mm ² including screws M2.5. dimension: 26.8x20.8 mm





3410BL - Double level terminal DIN35 6mm² blue

	81507/5 - Cross-connection 5-pole to terminals DIN32/35 6mm ² Insulated cross-connection 5-pole to terminals DIN32/35 6mm ² including screws M2.5. dimension: 33.9x20.8 mm
	81507/10 - Cross-connection 10-pole to terminals DIN32/35 6mm² Insulated cross-connection 10-pole to terminals DIN32/35 6mm ² including screws M2.5. dimension: 69.4x20.8 mm
Ĩ	81506 - Cross connection bolt single M3 insulated (10.6 mm) Cross-connection bolt complete with spacer sleeve. Standard version. Dimension: 10.6 mm
\bullet \bullet	30441 - Link to cross-connections to terminals 4mm 2
\bullet \bullet	81452L - Link to cross-connections to terminals 6mm 2
	3826/4 - Cover for 4 terminals yellow with black printing,to series 3452/6 and 3410
- D	3826/5 - Cover for 5 terminals yellow with black printing, to series 34526 and 3410
	3826/6 - Cover for 6 terminals yellow with black printing, to series 34526 and 3410
	3826/7 - Cover for 7 terminals yellow with black printing, to series 34526 and 3410
- D	3826/8 - Cover for 8 terminals yellow with black printing, to series 34526 and 3410
Ļ	81440 - Sealing eyelet Ø 3.2mm Sealing eyes
JAN B	3512 - Sealing screw M3x25 of polyamide Sealing screw spring-loaded test probes, several numbers of poles can be lined up





3410BL - Double level terminal DIN35 6mm² blue

Product systems



Double deck clamps DIN 35

Various double-deck clamps.

