




Floor channel BOK 8880 400x80mm integrated leveling device




Floor channel BOK 8880 400x80mm with integrated leveling device.

## Components



## 52345 - Installation kit Scs 3FLF horizontal empty BOK



Dimension: 400x95x41.4mm Color: RAL 7032 pebble gray





### 55032 - Installation kit Sts 4FLF horizontal empty BOK

made of galvanized sheet steel 1.5mm with knurled screw for lateral fixing in the trunking shell. Dimension: 376x47(53)x40mm Color: RAL 7032 pebble gray

Equipped: 1 pcs. blind hole clamp 8x2.5mm <sup>2</sup> 10146





### 52483N - Cross connection BOK 8880/400x80 iN

Cross joint BOK 8880/400x80 with integrated leveling made of sendzimirgalvanized sheet steel 1.5mm pressed on both sides in special aluminum profile Woertz with temporary protective edge inserted in groove and impact sound trapezoidal rubber as cover support

Leveling hexagonal bolts M10x60 polyamide Including connecting material

High 80mm / cover nominal width 400mm

Length: 1000mm





### 52481N - Angle connection BOK 8880/400x80 iN

with integrated levelingmade of sendzimir-galvanized sheet steel 1.5mmpressed into special aluminum profile Woertz on both sides with temporary protective edge inserted in groove and impact sound trapezoidal rubber as cover supportleveling hexagonal bolts M10x60 polyamideincluding connecting materialheight 80mm / nominal cover width 400mm







Floor channel BOK 8880 400x80mm integrated leveling device

	r toor charmer 2011 edge rechection integrated to rouning devices	
	52482N - T-joint BOK 8880/400x80 iN	
la de la companya de	with integrated levelingmade of sendzimir-galvanized sheet steel 1.5mmpressed into special aluminum profile Woertz on both sides with temporary protective edge inserted in groove and impact sound trapezoidal rubber as cover supportleveling hexagonal bolts M10x60 polyamideincluding connecting materialheight 80mm / nominal cover width 400mm length: 1000mm	
	52484 - End wall BOK 8880/400x80 SK	
	made of sendzimir-galvanized steel sheet 1.5mm pressed into special aluminum profile Woertz with temporary protective edge inserted in groove and impact sound trapezoidal rubber as cover supportincluding connecting material height 80mm / cover nominal width 400mm	
_	52484/0 - End wall BOK 8880/400x80 SK 0	
	made of sendzimir-galvanized steel sheet 1.5mm including connecting material height 80mm / lid nominal width 406mm	
	52477 - Temporary wooden cover BOK 8880/400	
	to be inserted as a placeholder and protection for the floor channel Dimension: 1000x401x12mm	
Ė	52410/22 - Al protective edge 22 BOK 8880	
** **	made of aluminumDimension: 2000x37x3mm	
±.	52410/3 - Al protective edge 3 BOK 8880	回公共 (基本) 正理(1000年)
51 + 28	made of aluminumDimension: 2000x18x3mm	
3	52410/12 - Al protective edge 12 BOK 8880	
***	made of aluminumDimension: 2000x27x3mm	
	52480N - Floor duct BOK 8880/400x80 iN	
	with integrated leveling made of sendzimir galvanized steel sheet 1.5mm pressed into special aluminum profile Woertz on both sides with temporary protective	



## 52469 - St lid BOK 8880/400 SK

80mm / nominal cover width 400mm length: 2000mm

made of sendzimir galvanized steel sheet 4mm dimension: 500x400mm

edge inserted into groove and impact sound trapezoidal rubber as cover support leveling hexagonal bolts M10x60 polyamide including connecting material height







Floor channel BOK 8880 400x80mm integrated leveling device

	52466 - St lid BOK 8880/400 SK KD made of sendzimir-galvanized steel sheet 4mm dimension: 500x400mm cable gland enclosed loose	
	52468 - St lid BOK 8880/400 SK KMn	
Tipe .	made of sendzimir-galvanized steel sheet 4mm dimension: 500x400mm cable tray enclosed loose	
	52467 - St lid BOK 8880/400 SK BL	
	made of sendzimir-galvanized steel sheet 4mm dimension: 500x400mm with brush strips as cable outlet, for 3mm finished floor height	
	52473/3 - 0	
	made of aluminum 2mm toxtured with galvanized steel sheet insert 2mm. Dimension: 500x399x7mm edge height inside occupiable: 3mm	
	52472/3 - 0	
	made of aluminum 2mm with galvanized steel sheet insert 2mm getoxt.dimension: 1000x399x7mm edge height inside occupiable: 3mm	
	52472/12 - 0	回答: 200 - 254 回 536   355 - 255 536   356 - 255 536   356 - 255
	for 12mm edge, to BOK 8880/400,Length: 1000mm	
	52473/22 - 0	
	made of aluminum 3mm dimension: 500x399x19mm edge height inside 22mm	
	52472/22 - 0	
	made of aluminum 3mm dimension: 1000x399x16mm edge height inside 22mm	
	52474/3 - 0	
	of aluminiumdim 500x400edge 3mm cable trough separately enclosed	
Ė	52412/3 - Cr protective edge 3 BOK 8880	
22.	made of chrome steel V2Adimension: 2000x18x3mm	
-3 -	52412/12 - Cr protective edge 12 BOK 8880	
11.8	made of chrome steel V2Adimension: 2000x27x3mm	





Floor channel BOK 8880 400x80mm integrated leveling device

-3 -3	52412/22 - Cr protective edge 22 BOK 8880	
<b>8</b>	made of chrome steel V2Adimension: 2000x37x3mm	
	52473/12 - 0	
	made of aluminum 3mm dimension: 500x399x16mm edge height inside 13mm	
	55026 - Installation kit 2FLF 6/5 empty BOK 8880/x80	
	made of galvanized steel sheet 1.5mm with knurled screw for lateral fixing in the channel shell. Color: RAL 7032 pebble gray	
	51880 - Cable bushing with filler piece BOK	
	made of polycarbonate crystal clearwith transparent fillerDimension: 86x60x9.5mm	
	52091 - Mounting bracket 1 FLF 3/5 empty BOK	
	made of galvanized sheet steel color: RAL 7032 pebble gray	
*	52404 - End piece to leveling bar BOK8880/400	
	Dimensions 360x50x4mm Leveling bar additionally used in caseof non-existent brace	
	52348 - Insert set empty 4-8LM vertical BOK	
	to BOK 8880/ from 60mm height for modules type Legrand Mosaic 45x45 made of galvanized sheet steel color RAL 7032 pebble gray	
	52465/0 - St lid BOK 8880/400 SK 0	
	made of sendzimir galvanized steel sheet 4mm dimension: 1000x406	
	52465 - St lid BOK 8880/400 SK	
	made of sendzimir galvanized steel sheet 4mm dimension: 1000x400mm	
	52469/0 - St lid BOK 8880/400 SK 0	
	made of sendzimir galvanized steel sheet 4mm dimension: 500x406mm	
	51996 - Installation kit Scs 2FLF horizontal empty BOK	国 <b>党</b> 为各。是4国 第200章 第200章 第
	Low current versionmade of galvanized steel sheet 1.5mm with strain relief stampings and knurled screw for lateral fixing in the trunking shell. Color: RAL 7032 pebble gray	





Floor channel BOK 8880 400x80mm integrated leveling device



#### 55039 - Installation kit socket outlet T13 3FLF horizontal SB BOK

Installation kit socket T13 3FLF horizontal SB BOK made of galvanized sheet steel 1.5mm with knurled screw for lateral fixing in the trunking shell. Dimension: 302x47(53)x40mm Color: RAL 7032 pebble gray Equipped, wired and tested: 1 pcs. blind terminal 7x2.5mm <sup>2</sup> 10127 3 pcs. socket T13 FLF white 55200 1x L1 / 1x L2 / 1x L3 1 pc. Td-cable 5x1.5mm <sup>2</sup> / 1000mm 1 pc. FK junction box technofil 49909 (10A)





#### 52467/0 - St lid BOK 8880/400 SK 0 BL

made of sendzimir-galvanized steel sheet 4mm dimension: 500x406mm with brush strips as cable outlet, for 3mm finished floor height





#### 52466/0 - St lid BOK 8880/400 SK 0 KD

made of sendzimir galvanized steel sheet 4mm dimension: 500x406mm with cable gland





#### 52467/0SB - St lid visible BOK 8880/400 SK 0 BL

made of sendzimir galvanized steel sheet 4mm dimension:500x406mm with brush strip as cable outlet, top flush for visible lid





#### 52468/0 - St lid BOK 8880/400 SK 0 KMn

made of sendzimir-galvanized steel sheet 4mm dimension 500x406mm with cable trough enclosed loose





#### 52479/0SB - Cr lid visible BOK 8880/400 SK 0 BL

made of chrome steel V2A 4mm, brushed Dimensions: 490x406mm With brush strip 54x30mm as a cable outlet top flush for visible cover





#### 52474/22 - Al lid with rim BOK 22 8880/400 KMn

made of aluminum 3mm dimension: 500x399x26mm edge height inside occupiable: 23mm cable trough loosely enclosed





## 52474/12 - Al lid with rim BOK 12 8880/400 KMn

made of aluminum 3mm dimension: 500x399x16mm edge height inside 13mm cable tray enclosed loose





### 52478/0SB - Cr lid visible BOK 8880/400 SK 0

made of chrome steel V2A 4mm, brushed dimension: 990x406mm







Floor channel BOK 8880 400x80mm integrated leveling device

1186	55019 - Installation kit bticino 2x2-3gang empty BOK	
A fallow	made of galvanized sheet steel color: RAL 7032 pebble gray	
4	52403 - Mounting bracket 80 BOK 8880/80	
	made of sheet steel 2.5mm for floor trunking BOK 8880 height 80mm	
	55041 - Installation kit socket T23 3FLF horizontal SB BOK	
1010	Installation kit socket T23 3FLF horizontal SB BOK made of galvanized sheet steel 1.5mm with knurled screw for lateral fixing in the trunking shell. Dimension: 302x47(53)x40mm Color: RAL 7032 pebble gray Equipped, wired and tested: 1 pcs. blind terminal 7x2.5mm <sup>2</sup> 10127 3 pcs. socket T23 FLF white 55210 1x L1 / 1x L2 / 1x L3 1 pc. Td-cable 5x2.5mm <sup>2</sup> / 1000mm 1 pc. FK socket SK ecobus power 5x2.5 <sup>2</sup> Pow 5P 49701P (16A)	
<u>*</u> .	52404/100 - Leveling bar connection BOK 8880/400	
	made of sendzimir galvanized steel sheet 4mm dimensions: 360x100mm with 3 leveling hexagonal screws M10x60 polyamide with blind rivets for fastening to channel shell for additional mounting in case of missing connection.	
	52344 - Insert Sts 3FLF horizontal SB BOK	
10 0 0 m	made of galvanized sheet steel 1.5mm with knurled screw for lateral fixing in the trunking shell Dimensions: 302x47(53)x40mm Color: RAL 7032 pebble gray equipped, wired and tested: 1 pcs. blind hole terminal 7x2.5mm² 10127 3 pcs. socket T13 FLF white 55200 1x L1 / 1x L2 / 1x L3 1 pcs. Td cable 5x1.5mm² / 1000mm. 1 pc. FK socket SK ecobus power 5x2.5² Pow 5P 49701P (16A)	
	55031 - Installation kit Sts 3FLF horizontal empty BOK	
	made of galvanized sheet steel 1.5mm with knurled screw for lateral fixing in the trunking shell. Dimension: 302x47(53)x40mm Color: RAL 7032 pebble gray Equipped: 1 pcs. blind hole clamp 7x2.5mm <sup>2</sup> 10127	
	55033 - Installation kit Sts 6FLF horizontal empty BOK	
	made of galvanized sheet steel 1.5mm with knurled screw for lateral fixing in the trunking shell. Dimension: 525x47(53)x40mm Color: RAL 7032 pebble gray Equipped: 1 pcs. blind hole clamp 10x2.5mm <sup>2</sup> 10128	
	51049 - Adjustable cable trough BOK 8880 fDsb	
	made of polycarbonate crystal clear for cover visible for mounting with threaded bolt	





Floor channel BOK 8880 400x80mm integrated leveling device

	<b>52407 - Connecting link straight BOK 8880</b> made of sheet steel dimension: 130x10x2.5mm with 4 pieces hexagonal screws M4x8 for connecting the channel shells	
	52408 - Angle connecting link 90° BOK 8880  made of sheet steel dimension: 67.5/67.5xx10x2.5mm with 4 pcs hexagonal bolts M4x8 for connecting the channel shells	
	52415 - U-clamp profile reinforced 1-3mm as edge protection profile for sheet thickness up to 3mm	
	51069 - Cable trough levelable BOK SK 0-21mm  made of polycarbonate crystal clear for cover visible for mounting with threaded bolt	
-	<b>52420 - Brush strip cpl. BOK 8880 s=6</b> made of plastic, black dimension: 54x35mm bristles length: 25mm	
•	<b>52421 - Brush strip cpl. BOK 8880 s=4 visible</b> made of plastic, black dimension: 54x37mm bristles length: 30mm	
-	·	