




35330/4GR - Tension clamp terminal DIN35 4mm² 88.5x6x35mm grey



Tension clamp DIN35 4mm² 88.5x6x35mm grey with 3 connections marking possibility on the side and in the middle with stripes, recessed for cross connection

Characteristics	
Eldas number	158440237
Base Unit	Piece
availability	available from stock
EAN Code	7611718247460
group	165000
Packaging unit	25
country of origin	СН
Customs tariff number	8536.9080
Weight (g)	14 g
Color	gray
Technical data	
Dimensions length x width x height (mm)	88.5x6x35 mm
Dimensions length x width x height (inch)	3.48x0.24x1.38 inch
Cross section (mm²)	0,5 - 4 mm²
Nominal current (A)	30 A





35330/4GR - Tension clamp terminal DIN35 $4mm^2$ 88.5x6x35mm grey

Rated voltage (V)	600 V
Connection type	Spring clamp
DIN rail type	DIN-35
Number of connection point	3
Number of floor	1
Number of potentials	1
Insulating material	PA66
Nominal Cross-section (mm²)	4 mm²
Stripping length mm (mm)	12 mm
Rating data according to UL 1059	
Rated voltage US (V)	300 V
Nominal cross section (AWG)	12 AWG
Cross-section (AWG)	12 - 20 AWG
Stripping length (inch)	0,47 inch





35330/4GR - Tension clamp terminal DIN35 4mm² 88.5x6x35mm grey

Product accessories

	80247 - Test plug Ø 2.3mm red, socket 4mm connecting cable incl.
	80248 - Test plug Ø 2.3mm black, socket 4mm connecting cable incl.
	Bezeichnungskarte_6x12mm - Designation cards 6x12mm Various designation labels 6x12mm with different embossing.
	Bezeichnungskarte_6x9mm - Designation card 6x9mm Various designation plates with different embossing.
	35455/09BS - Marking strip 9x240mm with 25strips per box
	35455/69T - Marking adaptor for label 6x9mm to spring clamp terminals
	35341/4 - Partition and end barrier 109.5x39mm grey, to spring clamp terminals with 3 and 4 clamps
	35445 - End retainer for Spring clamp terminal DIN35 of polyamide 66, greydimensions: 8x45.2x23.5mm to spring clamp terminals 1.5 to 16mm 2
• world e 3542506 •	35425/06 - Cross-junction rack 10pole black Cross-connection rake insulated, black, to tension spring terminals 6mm
	35425/06BR - Bridge to cross-junction rack black Bridge insulated, suitable for 3542506 and 3542508 to connect 2 connecting rakes. 33.2x6x10.4 mm
1111111111	35435/415 - Cable entrance to 1.5mm2 conductors funnel-shaped, to spring clamp terminals 4mm 2Stripes of 10 pieces, separable





35330/4GR - Tension clamp terminal DIN35 4mm² 88.5x6x35mm grey

Product systems



Tension clamp terminals with three connections DIN 35

Various tension spring terminals with three connections.

