




Floor channel BOK 8880 400x50mm on leveling device




Floor channel BOK 8880 400x50mm on leveling device.

Components



52450 - Floor duct BOK 8880/400x50 SK







52453 - Angle connection BOK 8880/400x50 SK

made of sendzimir-galvanized sheet steel 1.5mm pressed into special aluminum profile Woertz on both sides with temporary protective edge inserted into groove and impact sound trapezoidal rubber as cover supportincluding fastening straps and connecting material height 80mm / nominal cover width 400mm





52454 - T-joint BOK 8880/400x50 SK

made of sendzimir-galvanized sheet steel 1.5mm pressed into special aluminum profile Woertz on both sides with temporary protective edge inserted into groove and impact sound trapezoidal rubber as cover supportincluding fastening straps and connecting material height 50mm / nominal cover width 400mm length: 1000mm





52455 - Cross connection BOK 8880/400x50 SK

made of sendzimir-galvanized sheet steel 1.5mm pressed into special aluminum profile Woertz on both sides with temporary protective edge inserted into groove and impact sound trapezoidal rubber as cover supportincluding fastening straps and connecting material height 50mm / nominal cover width 400mm length: 1000mm





52407 - Connecting link straight BOK 8880

made of sheet steel dimension: 130x10x2.5mm with 4 pieces hexagonal screws M4x8

for connecting the channel shells







-		
	52408 - Angle connecting link 90° BOK 8880	
	made of sheet steel dimension: 67.5/67.5xx10x2.5mm with 4 pcs hexagonal bolts M4x8	
	for connecting the channel shells	
	52415 - U-clamp profile reinforced 1-3mm	
	as edge protection profile for sheet thickness up to 3mm	
	52400 - Leveling bar straight BOK 8880/400	
	made of steel dimension: 530x50x5mm	
	52504 - Leveling plate BOK 8880/400	
	made of sendzimir galvanized sheet steel dimension: 530x530x4mm	
	to angle- cross- and T-connection	
	52515 - Leveling foot M10 cpl H=53mm BOK 8880	
	for finished floor heights:	
	Channel height 50mm, 70-90mm	回花為此時期
	Channel height 60mm, 80-100mm	
	Channel height 80mm, 100-140mm	
1	52516 - Leveling foot M10 cpl H=103mm BOK 8880	
	for finished floor heights:	
	Channel height 50mm, 80-140mm	宣传等级
	Channel height 60mm, 90-150mm	
	Channel height 80mm, 110-170mm	
4	52517 - Leveling foot M10 cpl H=153mm BOK 8880	
	for finished floor heights:	
_	Channel height 50mm, 80-190mm	
	Channel height 60mm, 90-200mm	
	Channel height 80mm, 110-220mm	
	52518 - Leveling foot M10 cpl H=203mm BOK 8880	
	for finished floor heights:	
	Channel height 50mm, 180-240mm	
	Channel height 60mm, 190-250mm	
	Channel height 80mm, 210-270mm	
	5	





52519 - Leveling foot M10 cpl H=253mm BOK 8880 for finished floor heights: Channel height 50mm, 230-290mm Channel height 60mm, 240-300mm Channel height 80mm, 260-320mm	
52456 - End wall BOK 8880/400x50 SK made of sendzimir-galvanized steel sheet 1.5mm pressed into special aluminum profile Woertz with temporary protective edge inserted in groove and impact sound trapezoidal rubber as cover supportincluding connecting material height 50mm / cover nominal width 400mm	
52456/0 - End wall BOK 8880/400x50 SK 0 made of sendzimir-galvanized steel sheet 1.5mm including connecting material height 50mm / lid nominal width 406mm	
52477 - Temporary wooden cover BOK 8880/400 to be inserted as a placeholder and protection for the floor channel Dimension: 1000x401x12mm	
52465 - St lid BOK 8880/400 SK made of sendzimir galvanized steel sheet 4mm dimension: 1000x400mm	
52469 - St lid BOK 8880/400 SK made of sendzimir galvanized steel sheet 4mm dimension: 500x400mm	
52466 - St lid BOK 8880/400 SK KD made of sendzimir-galvanized steel sheet 4mm dimension: 500x400mm cable gland enclosed loose	
52467 - St lid BOK 8880/400 SK BL made of sendzimir-galvanized steel sheet 4mm dimension: 500x400mm with brush strips as cable outlet, for 3mm finished floor height	
52468 - St lid BOK 8880/400 SK KMn made of sendzimir-galvanized steel sheet 4mm dimension: 500x400mm cable tray enclosed loose	
52465/0 - St lid BOK 8880/400 SK 0 made of sendzimir galvanized steel sheet 4mm dimension: 1000x406	





52469/0 - St lid BOK 8880/400 SK 0 made of sendzimir galvanized steel sheet 4mm dimension: 500x406mm	
52466/0 - St lid BOK 8880/400 SK 0 KD made of sendzimir galvanized steel sheet 4mm dimension: 500x406mm with cable gland	
52467/0 - St lid BOK 8880/400 SK 0 BL made of sendzimir-galvanized steel sheet 4mm dimension: 500x406mm with brush strips as cable outlet, for 3mm finished floor height	
52467/0SB - St lid visible BOK 8880/400 SK 0 BL made of sendzimir galvanized steel sheet 4mm dimension:500x406mm with brush strip as cable outlet, top flush for visible lid	
52468/0 - St lid BOK 8880/400 SK 0 KMn made of sendzimir-galvanized steel sheet 4mm dimension 500x406mm with cable trough enclosed loose	
52472/3 - 0 made of aluminum 2mm with galvanized steel sheet insert 2mm getoxt.dimension: 1000x399x7mm edge height inside occupiable: 3mm	
52472/12 - 0 for 12mm edge, to BOK 8880/400,Length: 1000mm	
52472/22 - 0 made of aluminum 3mm dimension: 1000x399x16mm edge height inside 22mm	
52473/3 - 0 made of aluminum 2mm toxtured with galvanized steel sheet insert 2mm. Dimension: 500x399x7mm edge height inside occupiable: 3mm	
52473/12 - 0 made of aluminum 3mm dimension: 500x399x16mm edge height inside 13mm	
52473/22 - 0 made of aluminum 3mm dimension: 500x399x19mm edge height inside 22mm	





	52474/3 - 0 of aluminiumdim 500x400edge 3mm cable trough separately enclosed	
	52474/12 - Al lid with rim BOK 12 8880/400 KMn made of aluminum 3mm dimension: 500x399x16mm edge height inside 13mm	
	cable tray enclosed loose	
	52474/22 - Al lid with rim BOK 22 8880/400 KMn	
	made of aluminum 3mm dimension: 500x399x26mm edge height inside occupiable: 23mm cable trough loosely enclosed	
	52478/0SB - Cr lid visible BOK 8880/400 SK 0	
	made of chrome steel V2A 4mm, brushed dimension: 990x406mm	
	52479/0SB - Cr lid visible BOK 8880/400 SK 0 BL	
	made of chrome steel V2A 4mm, brushed Dimensions: 490x406mm With brush strip 54x30mm as a cable outlet top flush for visible cover	
	51880 - Cable bushing with filler piece BOK	
	made of polycarbonate crystal clearwith transparent fillerDimension: 86x60x9.5mm	
	51049 - Adjustable cable trough BOK 8880 fDsb	
	made of polycarbonate crystal clear for cover visible for mounting with threaded bolt	
	51069 - Cable trough levelable BOK SK 0-21mm	
	made of polycarbonate crystal clear for cover visible for mounting with threaded bolt	
-	52420 - Brush strip cpl. BOK 8880 s=6	回表现得多4回 第二十二章
	made of plastic, black dimension: 54x35mm bristles length: 25mm	
	52410/3 - Al protective edge 3 BOK 8880	国公司 (2010) 第2013年 2014 2014 2014 2014 2014 2014 2014 2014
*** ***	made of aluminumDimension: 2000x18x3mm	
	52410/12 - Al protective edge 12 BOK 8880	
120 120 130 130 130 130 130 130 130 130 130 13	made of aluminumDimension: 2000x27x3mm	





Floor channel BOK 8880 400x50mm on leveling device

<u> </u>	52410/22 - Al protective edge 22 BOK 8880	回标第一条 回 7 章 1 章 2 章 2 章 2 章 2 章 2 章 2 章 2 章 2 章 2
**************************************	made of aluminumDimension: 2000x37x3mm	
)	52412/3 - Cr protective edge 3 BOK 8880	
× × × × × × × × × × × × × × × × × × ×	made of chrome steel V2Adimension: 2000x18x3mm	
 	52412/12 - Cr protective edge 12 BOK 8880	
**************************************	made of chrome steel V2Adimension: 2000x27x3mm	
- T	52412/22 - Cr protective edge 22 BOK 8880	
20 · 30 · 30 · 30 · 30 · 30 · 30 · 30 ·	made of chrome steel V2Adimension: 2000x37x3mm	
	52344 - Insert Sts 3FLF horizontal SB BOK	
1900	made of galvanized sheet steel 1.5mm with knurled screw for lateral fixing in the trunking shell Dimensions: 302x47(53)x40mm Color: RAL 7032 pebble gray	
	equipped, wired and tested: 1 pcs. blind hole terminal 7x2.5mm² 10127 3 pcs. socket T13 FLF white 55200 1x L1 / 1x L2 / 1x L3 1 pcs. Td cable	
	5x1.5mm ² / 1000mm. 1 pc. FK socket SK ecobus power 5x2.5 ² Pow 5P 49701P (16A)	
	51996 - Installation kit Scs 2FLF horizontal empty BOK	
	Low current versionmade of galvanized steel sheet 1.5mm with strain relief stampings and knurled screw for lateral fixing in the trunking shell. Color: RAL 7032 pebble gray	
	52345 - Installation kit Scs 3FLF horizontal empty BOK	
	Low current version made of sendzimir galvanized sheet steel 1.5mm with strain relief stampings and knurled screw for lateral fixing in the trunking shell	
	Dimension: 400x95x41.4mm Color: RAL 7032 pebble gray	
0.00	55039 - Installation kit socket outlet T13 3FLF horizontal SB BOK	
	Installation kit socket T13 3FLF horizontal SB BOK made of galvanized sheet steel 1.5mm with knurled screw for lateral fixing in the trunking shell. Dimension: 302x47(53)x40mm Color: RAL 7032 pebble gray Equipped, wired and tested: 1	

pcs. blind terminal 7x2.5mm ² 10127 3 pcs. socket T13 FLF white 55200 1x L1 / 1x L2 / 1x L3 1 pc. Td-cable 5x1.5mm² / 1000mm 1 pc. FK junction box technofil

49909 (10A)







1000	55041 - Installation kit socket T23 3FLF horizontal SB BOK Installation kit socket T23 3FLF horizontal SB BOK made of galvanized sheet steel 1.5mm with knurled screw for lateral fixing in the trunking shell. Dimension: 302x47(53)x40mm Color: RAL 7032 pebble gray Equipped, wired and tested: 1 pcs. blind terminal 7x2.5mm ² 10127 3 pcs. socket T23 FLF white 55210 1x L1 / 1x L2 / 1x L3 1 pc. Td-cable 5x2.5mm ² / 1000mm 1 pc. FK socket SK ecobus power 5x2.5² Pow 5P 49701P (16A)	
	55031 - Installation kit Sts 3FLF horizontal empty BOK made of galvanized sheet steel 1.5mm with knurled screw for lateral fixing in the trunking shell. Dimension: 302x47(53)x40mm Color: RAL 7032 pebble gray Equipped: 1 pcs. blind hole clamp 7x2.5mm ² 10127	
	55032 - Installation kit Sts 4FLF horizontal empty BOK made of galvanized sheet steel 1.5mm with knurled screw for lateral fixing in the trunking shell. Dimension: 376x47(53)x40mm Color: RAL 7032 pebble gray Equipped: 1 pcs. blind hole clamp 8x2.5mm ² 10146	
	55033 - Installation kit Sts 6FLF horizontal empty BOK made of galvanized sheet steel 1.5mm with knurled screw for lateral fixing in the trunking shell. Dimension: 525x47(53)x40mm Color: RAL 7032 pebble gray Equipped: 1 pcs. blind hole clamp 10x2.5mm ² 10128	
\(\)	52091 - Mounting bracket 1 FLF 3/5 empty BOK made of galvanized sheet steel color: RAL 7032 pebble gray	
•	52421 - Brush strip cpl. BOK 8880 s=4 visible made of plastic, black dimension: 54x37mm bristles length: 30mm	
THE SEC	55019 - Installation kit bticino 2x2-3gang empty BOK made of galvanized sheet steel color: RAL 7032 pebble gray	