



Product data sheet

3880GR - Two-step terminal DIN32 4mm2 grey



Characteristics	
Eldas number	158202237
Base Unit	Piece
availability	Delivery in 4 weeks
EAN Code	7611718201400
group	165000
Packaging unit	50
country of origin	CH
Customs tariff number	8536.9080
Weight (g)	16,7 g
Color	gray
Technical data	
Dimensions length x width x height (mm)	62x6x48 mm
Dimensions length x width x height (inch)	2.44x0.24x1.89 inch
Cross section (mm²)	0,5 - 4 mm²
Nominal current (A)	20 A



Product data sheet

3880GR - Two-step terminal DIN32 4mm2 grey

Rated voltage (V)	500 V
Connection type	Screw terminal
DIN rail type	DIN-32
Number of connection point	4
Number of floor	2
Number of potentials	2
Clamping screw M	M3
Insulating material	PA66
Nominal Cross-section (mm²)	4 mm²
Stripping length mm (mm)	10 mm
Head reception room width x height (mm)	3.2x5 mm
Rating data according to UL 1059	
Rated voltage US (V)	300 V
Nominal cross section (AWG)	12 AWG
Cross-section (AWG)	12 - 20 AWG
Stripping length (inch)	0,39 inch



Product data sheet


3880GR - Two-step terminal DIN32 4mm² grey

Product accessories




80222/6 - Test adaptor to terminal series 3450 2 spiral springs

with hole for strands up to 0.75mm²



Bezeichnungskarte_6x9mm - Designation card 6x9mm

Various designation plates with different embossing.



Bezeichnungskarte_6x3mm - Designation card 6x3mm

Various designation plates with different embossing.



81526/2 - Cross-connection 2pole to terminal 2.5mm²/4mm²

Cross connections complete with M3 screws. 11.1x17.8 mm



81526/3 - Cross-connection 3-pole to terminals DIN15/32/35 2.5mm²/4mm²

Insulated cross-connection 3-pole to terminals DIN15/32/35 2.5mm²/4mm² including screws M3. Dimension: 17.2x17.8 mm



81526/4 - Cross-connection 4-pole to terminals DIN15/32/35 2.5mm²/4mm²

Insulated cross-connection 4-pole to terminals DIN15/32/35 2.5mm²/4mm² including screws M3. Dimension: 23.3x17.8 mm



81526/5 - Cross-connection 5-pole to terminals DIN15/32/35 2.5mm²/4mm²

Insulated cross-connection 5-pole to terminals DIN15/32/35 2.5mm²/4mm² including screws M3. Dimension: 29.4x17.8 mm




81526/10 - Cross-connection 10-pole to terminals DIN15/32/35 2.5mm²/4mm²

Insulated cross-connection 10-pole to terminals DIN15/32/35 2.5mm²/4mm² including screws M3. Dimension: 59.9x17.8 mm



81526 - Cross connection bolt single M3, insulated (9.1 mm)

Cross connection bolt complete with spacer sleeve. 9.1 mm



30441 - Link to cross-connections

to terminals 4mm²



3894/4 - Cover for 4 terminals yellow

with black printing, to series 3430



Product data sheet

3880GR - Two-step terminal DIN32 4mm² grey



3894/5 - Cover for 5 terminals yellow

with black printing, to series 3430



3894/6 - Cover for 6 terminals yellow

with black printing, to series 3430



3894/7 - Cover for 7 terminals yellow

with black printing, to series 3430



3894/8 - Cover for 8 terminals yellow

with black printing, to series 3430



81440 - Sealing eyelet Ø 3.2mm

Sealing eyes



3512 - Sealing screw M3x25 of polyamide

Sealing screw spring-loaded test probes, several numbers of poles can be lined up



30421 - Cover strip for double level and terminal blocks 9.5mm, length 280mm

Cover strip for double level and terminal blocks DIN32/35 9.5mm , length 280mm



Product data sheet

3880GR - Two-step terminal DIN32 4mm² grey

Product systems

Double deck clamps DIN32

Various double deck clamps DIN32.

