




Floor channel BOK 8880 200x50mm integrated leveling device



Floor channel BOK 8880 200x50mm with integrated leveling device

#### Components

	52345 - Installation kit Scs 3FLF horizontal empty BOK	
	Low current version made of sendzimir galvanized sheet steel 1.5mm with strain relief stampings and knurled screw for lateral fixing in the trunking shell	
	Dimension: 400x95x41.4mm Color: RAL 7032 pebble gray	
	55032 - Installation kit Sts 4FLF horizontal empty BOK	
	made of galvanized sheet steel 1.5mm with knurled screw for lateral fixing in the trunking shell. Dimension: 376x47(53)x40mm Color: RAL 7032 pebble gray Equipped: 1 pcs. blind hole clamp 8x2.5mm <sup>2</sup> 10146	
~	52256 - End wall BOK 8880/200x50 with temporary protective edge	
	made of sendzimir-galvanized steel sheet 1.5mm with temporary protective edge pressed into special aluminum profile Woertz with temporary protective edge inserted into groove and impact sound trapezoidal rubber as cover supportincluding connecting material height 50mm / nominal cover width 200mm	
	52253N - Angle connection BOK 8880/200x50 iN	
	with integrated levelingmade of sendzimir-galvanized sheet steel 1.5mmpressed into special aluminum profile Woertz on both sides with temporary protective edge inserted in groove and impact sound trapezoidal rubber as cover supportleveling hexagonal screws M10x60 polyamideincluding connecting materialheight 50mm / nominal cover width 200mm	
	52254N - T-joint BOK 8880/200x50 iN	
	with integrated levelingmade of sendzimir-galvanized sheet steel 1.5mmpressed into special aluminum profile Woertz on both sides with temporary protective edge inserted into groove and impact sound trapezoidal rubber as cover supportleveling hexagonal bolts M10x60 polyamideincluding connecting materialheight 50mm / nominal cover width 200mm length: 1000mm	





	<b>52255N</b> - <b>Cross connection BOK 8880/200x50 iN</b> with integrated levelingmade of sendzimir-galvanized sheet steel 1.5mmpressed into special aluminum profile Woertz on both sides with temporary protective edge inserted into groove and impact sound trapezoidal rubber as cover supportleveling hexagonal bolts M10x60 polyamideincluding connecting materialheight 50mm / nominal cover width 200mm length: 1000mm	
	<b>52204 - End piece to leveling bar BOK8880/200</b> Dimensions 160x50x4mm Leveling bar additionally used in caseof non-existent brace	
	<b>51431 - St lid BOK 8880/200 SK</b> made of steel sheet 4mm dimension: 500x200mm with opening for connection attachment	
	<b>52267 - St lid BOK 8880/200 SK BL</b> made of sendzimir-galvanized steel sheet 4mm dimension: 500x200mm with brush strips as cable outlet, for 3mm finished floor height	
	<b>52265 - St lid BOK 8880/200 SK</b> made of sendzimir galvanized steel sheet 4mm dimension:1000x200mm	
	<b>52266 - St lid BOK 8880/200 SK KD</b> made of sendzimir-galvanized steel sheet 4mm dimension: 500x200mm cable gland loosely enclosed	
WK .	<b>52268 - St lid BOK 8880/200 SK KMn</b> made of sendzimir-galvanized steel sheet 4mm dimension: 500x200mm cable tray enclosed loose	
	<b>52272/3 - 0</b> aluminium 2mm galvanised sheet steel reinforced 3mm getoxt. Dimensions: 1000x199x7mm Edge height in 3mm	
	<b>52272/12 - 0</b> for 12mm edge, to BOK 8880/200,Length: 1000mm	
	<b>52272/22 - 0</b> for 22mm edge, to BOK 8880/200,Length: 1000mm	





	<b>52273/22 - 0</b> for 22mm edge, to BOK 8880/200,Length: 500mm	
	<b>52274/12 - 0</b> of aluminiumdim 500x200edge 12mm cable trough separately enclosed	
3 11 12	<b>52410/22 - Al protective edge 22 BOK 8880</b> made of aluminumDimension: 2000x37x3mm	
	<b>52273/12 - 0</b> for 12mm edge, to BOK 8880/200,Length: 500mm	
-1- 	<b>52410/3 - Al protective edge 3 BOK 8880</b> made of aluminumDimension: 2000x18x3mm	
- <sup>3</sup>	<b>52410/12 - Al protective edge 12 BOK 8880</b> made of aluminumDimension: 2000x27x3mm	
-3 	<b>52412/3 - Cr protective edge 3 BOK 8880</b> made of chrome steel V2Adimension: 2000x18x3mm	
- <sup>3</sup>	52412/12 - Cr protective edge 12 BOK 8880 made of chrome steel V2Adimension: 2000x27x3mm	
- C- 	52412/22 - Cr protective edge 22 BOK 8880 made of chrome steel V2Adimension: 2000x37x3mm	
	<b>52277 - Temporary wooden cover BOK8880/200</b> for insertion as a placeholder and protection for the floor channel Dimension: 1000x201x12mm	
	<b>51880 - Cable bushing with filler piece BOK</b> made of polycarbonate crystal clearwith transparent fillerDimension: 86x60x9.5mm	
	52250N - Floor duct BOK 8880/200x50 iN null	





	52091 - Mounting bracket 1 FLF 3/5 empty BOK	
	made of galvanized sheet steel color: RAL 7032 pebble gray	
	52265/0 - St lid BOK 8880/200 SK 0	
	made of sendzimir galvanized steel sheet 4mm dimension: 1000x206mm	
	52273/3 - 0	
$\checkmark$	made of aluminum 2mm toxtured with galvanized steel sheet insert 3mm. Dimension: 500x199x7mm edge height inside occupiable: 3mm	
$\land$	52274/3 - 0	
	aluminium 2mm galvanised sheet steel reinforced 3 mm getoxtDimensions: 500x200x7mm Edge height in 3 mm Loose cable trough	
	51996 - Installation kit Scs 2FLF horizontal empty BOK	
V and Str	Low current versionmade of galvanized steel sheet 1.5mm with strain relief stampings and knurled screw for lateral fixing in the trunking shell. Color: RAL 7032 pebble gray	
	52256/0 - End panel BOK 8880/200x50 SK with protective edge height 0	
	made of sendzimir-galvanized steel sheet 1.5mm with protective edge height 0 in special aluminum profile Woertz pressed in groove and impact sound trapezoidal rubber as cover supportincluding connecting material height 50mm / nominal cover width 200mm	
0.0	55039 - Installation kit socket outlet T13 3FLF horizontal SB BOK	
A Colorador	Installation kit socket T13 3FLF horizontal SB BOK made of galvanized sheet steel 1.5mm with knurled screw for lateral fixing in the trunking shell. Dimension: 302x47(53)x40mm Color: RAL 7032 pebble gray Equipped, wired and tested: 1 pcs. blind terminal 7x2.5mm <sup>2</sup> 10127 3 pcs. socket T13 FLF white 55200 1x L1 / 1x L2 / 1x L3 1 pc. Td-cable 5x1.5mm <sup>2</sup> / 1000mm 1 pc. FK junction box technofil 49909 (10A)	
	51432 - Connection attachment 2x5FLF vertical BOK	
ATT IN	Top 200x219x80 for 10 FLF sockets standing Color: at choice	
	52268/0 - St lid BOK 8880/200 SK 0 KMn	
The second second	made of sendzimir-galvanized steel sheet 4mm dimension: 500x206mm with cable trough enclosed loose	





	52267/0 - St lid BOK 8880/200 SK 0 BL	
	made of sendzimir-galvanized steel sheet 4mm dimension: 500x206mm with brush strips as cable outlet, for 3mm finished floor height	
	52269/0 - St lid BOK 8880/200 SK 0	
	made of sendzimir galvanized steel sheet 4mm dimension: 500x206mm	
	52267/0SB - St lid visible BOK 8880/200 SK 0 BL	
	made of sendzimir galvanized sheet steel 4mm dimension:500x206mm with brush strip as cable outlet, top flush with lid for visible lid	
	52274/22 - 0	
	of aluminiumdim 500x200edge 22mm cable trough separately enclosed	
	52266/0 - St lid BOK 8880/200 SK 0 KD	
	made of sendzimir galvanized steel sheet 4mm dimension: 500x206mm with cable gland	
	52279/0SB - Cr lid visible BOK 8880/200 SK 0 BL	
	made of chrome steel V2A 4mm, brushed Dimensions: 490x206mm With brush strip 54x30mm as a cable outlet Top flush for visible cover	
	52278/0SB - Cr lid visible BOK 8880/200 SK 0	
	made of chrome steel V2A 4mm, brushed dimension: 990x206mm	
	55019 - Installation kit bticino 2x2-3gang empty BOK	
A Link Stor	made of galvanized sheet steel color: RAL 7032 pebble gray	
10 m	55041 - Installation kit socket T23 3FLF horizontal SB BOK	
AF 19/9/2	Installation kit socket T23 3FLF horizontal SB BOK made of galvanized sheet steel 1.5mm with knurled screw for lateral fixing in the trunking shell. Dimension: 302x47(53)x40mm Color: RAL 7032 pebble gray Equipped, wired and tested: 1 pcs. blind terminal 7x2.5mm <sup>2</sup> 10127 3 pcs. socket T23 FLF white 55210 1x L1 / 1x L2 / 1x L3 1 pc. Td-cable 5x2.5mm <sup>2</sup> / 1000mm 1 pc. FK socket SK ecobus power 5x2.5 <sup>2</sup> Pow 5P 49701P (16A)	
	55028 - Adapter plate BOK 8880/200x50/60	
	made of sendzimir-galvanized sheet steel 1.5mm for mounting the installation kits in the floor ductincluding fastening material	





C 19/9/9	52344 - Insert Sts 3FLF horizontal SB BOK	
	made of galvanized sheet steel 1.5mm with knurled screw for lateral fixing in the trunking shell Dimensions: 302x47(53)x40mm Color: RAL 7032 pebble gray	
	equipped, wired and tested: 1 pcs. blind hole terminal 7x2.5mm <sup>2</sup> 10127	
	3 pcs. socket T13 FLF white 55200 1x L1 / 1x L2 / 1x L3 1 pcs. Td cable 5x1.5mm <sup>2</sup> / 1000mm. 1 pc. FK socket SK ecobus power 5x2.5 <sup>2</sup> Pow 5P 49701P	
	(16A)	
	55031 - Installation kit Sts 3FLF horizontal empty BOK	
A LL	made of galvanized sheet steel 1.5mm with knurled screw for lateral fixing in the trunking shell. Dimension: 302x47(53)x40mm Color: RAL 7032 pebble gray Equipped: 1 pcs. blind hole clamp 7x2.5mm <sup>2</sup> 10127	
123	55033 - Installation kit Sts 6FLF horizontal empty BOK	
A COLOR	made of galvanized sheet steel 1.5mm with knurled screw for lateral fixing in the trunking shell. Dimension: 525x47(53)x40mm Color: RAL 7032 pebble gray Equipped: 1 pcs. blind hole clamp 10x2.5mm <sup>2</sup> 10128	
á na	51049 - Adjustable cable trough BOK 8880 fDsb	
	made of polycarbonate crystal clear for cover visible for mounting with threaded bolt	
	52401 - Mounting bracket 50 BOK 8880/50	
	made of sheet steel 2.5mm for floor trunking BOK 8880 height 50mm	
	52407 - Connecting link straight BOK 8880	
	made of sheet steel dimension: 130x10x2.5mm with 4 pieces hexagonal screws M4x8	
	for connecting the channel shells	
	52408 - Angle connecting link 90° BOK 8880	
	made of sheet steel dimension: 67.5/67.5xx10x2.5mm with 4 pcs hexagonal bolts	
	M4x8 for connecting the channel shells	Enercesa
	52415 - U-clamp profile reinforced 1-3mm	
	as edge protection profile for sheet thickness up to 3mm	
No. of the second secon	52204/100 - Leveling bar connection BOK8880/200	
	made of sendzimir galvanized steel sheet 4mm dimensions: 160x100mm with 3 leveling hexagonal screws M10x60 polyamide with blind rivets for fastening to channel shell for additional mounting in case of missing connection.	





	<b>52269 - St lid BOK 8880/200 SK</b> made of sendzimir galvanized steel sheet 4mm dimension: 500x200mm	
*	<b>51069 - Cable trough levelable BOK SK 0-21mm</b> made of polycarbonate crystal clear for cover visible for mounting with threaded bolt	
-	<b>52420 - Brush strip cpl. BOK 8880 s=6</b> made of plastic, black dimension: 54x35mm bristles length: 25mm	
•	<b>52421 - Brush strip cpl. BOK 8880 s=4 visible</b> made of plastic, black dimension: 54x37mm bristles length: 30mm	