




## System overview

Floor channel BOK 8880 400x50mm integrated leveling device



Floor channel BOK 8880 400x50mm with integrated leveling device.

## Components




### 52345 - Installation kit Scs 3FLF horizontal empty BOK

Low current version made of sendzimir galvanized sheet steel 1.5mm with strain relief stampings and knurled screw for lateral fixing in the trunking shell

Dimension: 400x95x41.4mm


Color: RAL 7032 pebble gray



### 55032 - Installation kit Sts 4FLF horizontal empty BOK


made of galvanized sheet steel 1.5mm with knurled screw for lateral fixing in the trunking shell. Dimension: 376x47(53)x40mm Color: RAL 7032 pebble gray

Equipped: 1 pcs. blind hole clamp 8x2.5mm <sup>2</sup> 10146




### 52453N - Angle connection BOK 8880/400x50 iN

with integrated levelingmade of sendzimir-galvanized sheet steel 1.5mmpressed into special aluminum profile Woertz on both sides with temporary protective edge inserted in groove and impact sound trapezoidal rubber as cover supportleveling hexagonal bolts M10x60 polyamideincluding connecting materialheight 50mm / nominal cover width 400mm



### 52454N - T-joint BOK 8880/400x50 iN

with integrated levelingmade of sendzimir-galvanized sheet steel 1.5mmpressed into special aluminum profile Woertz on both sides with temporary protective edge inserted in groove and impact sound trapezoidal rubber as cover supportleveling hexagonal bolts M10x60 polyamideincluding connecting materialheight 50mm / nominal cover width 400mm length: 1000mm



### 52455N - Cross connection BOK 8880/400x50 iN





















with integrated levelingmade of sendzimir-galvanized sheet steel 1.5mmpressed into special aluminum profile Woertz on both sides with temporary protective edge inserted in groove and impact sound trapezoidal rubber as cover supportleveling hexagonal bolts M10x60 polyamideincluding connecting materialheight 50mm / nominal cover width 400mm length: 1000mm





## System overview

























### Floor channel BOK 8880 400x50mm integrated leveling device

	<b>52404 - End piece to leveling bar BOK8880/400</b> Dimensions 360x50x4mm Leveling bar additionally used in case of non-existent brace	
	<b>52456/0 - End wall BOK 8880/400x50 SK 0</b> made of sendzimir-galvanized steel sheet 1.5mm including connecting material height 50mm / lid nominal width 406mm	
	<b>52456 - End wall BOK 8880/400x50 SK</b> made of sendzimir-galvanized steel sheet 1.5mm pressed into special aluminum profile Woertz with temporary protective edge inserted in groove and impact sound trapezoidal rubber as cover support including connecting material height 50mm / cover nominal width 400mm	
	<b>52467 - St lid BOK 8880/400 SK BL</b> made of sendzimir-galvanized steel sheet 4mm dimension: 500x400mm with brush strips as cable outlet, for 3mm finished floor height	
	<b>52465 - St lid BOK 8880/400 SK</b> made of sendzimir galvanized steel sheet 4mm dimension: 1000x400mm	
	<b>52469 - St lid BOK 8880/400 SK</b> made of sendzimir galvanized steel sheet 4mm dimension: 500x400mm	
	<b>52466 - St lid BOK 8880/400 SK KD</b> made of sendzimir-galvanized steel sheet 4mm dimension: 500x400mm cable gland enclosed loose	
	<b>52468 - St lid BOK 8880/400 SK KMn</b> made of sendzimir-galvanized steel sheet 4mm dimension: 500x400mm cable tray enclosed loose	
	<b>52472/12 - 0</b> for 12mm edge, to BOK 8880/400, Length: 1000mm	
	<b>52473/3 - 0</b> made of aluminum 2mm textured with galvanized steel sheet insert 2mm. Dimension: 500x399x7mm edge height inside occupiable: 3mm	



## System overview

















### Floor channel BOK 8880 400x50mm integrated leveling device

	<b>52472/3 - 0</b> made of aluminum 2mm with galvanized steel sheet insert 2mm getext.dimension: 1000x399x7mm edge height inside occupiable: 3mm	
	<b>52477 - Temporary wooden cover BOK 8880/400</b> to be inserted as a placeholder and protection for the floor channel Dimension: 1000x401x12mm	
	<b>52472/22 - 0</b> made of aluminum 3mm dimension: 1000x399x16mm edge height inside 22mm	
	<b>52410/22 - Al protective edge 22 BOK 8880</b> made of aluminumDimension: 2000x37x3mm	
	<b>52410/3 - Al protective edge 3 BOK 8880</b> made of aluminumDimension: 2000x18x3mm	
	<b>52410/12 - Al protective edge 12 BOK 8880</b> made of aluminumDimension: 2000x27x3mm	
	<b>52412/3 - Cr protective edge 3 BOK 8880</b> made of chrome steel V2Adimension: 2000x18x3mm	
	<b>52412/12 - Cr protective edge 12 BOK 8880</b> made of chrome steel V2Adimension: 2000x27x3mm	
	<b>52412/22 - Cr protective edge 22 BOK 8880</b> made of chrome steel V2Adimension: 2000x37x3mm	
	<b>52473/12 - 0</b> made of aluminum 3mm dimension: 500x399x16mm edge height inside 13mm	
	<b>52473/22 - 0</b> made of aluminum 3mm dimension: 500x399x19mm edge height inside 22mm	
	<b>52474/3 - 0</b> of aluminiumdim 500x400edge 3mm cable trough separately enclosed	



## System overview





















### Floor channel BOK 8880 400x50mm integrated leveling device

	<p><b>52450N - Floor duct BOK 8880/400x50 iN</b></p> <p>with integrated leveling made of sendzimir galvanized steel sheet 1.5mm pressed into special aluminum profile Woertz on both sides with temporary protective edge inserted into groove and impact sound trapezoidal rubber as cover support leveling hexagonal bolts M10x60 polyamide including connecting material height 50mm / nominal cover width 400mm length: 2000mm</p>	
	<p><b>52091 - Mounting bracket 1 FLF 3/5 empty BOK</b></p> <p>made of galvanized sheet steel color: RAL 7032 pebble gray</p>	
	<p><b>51996 - Installation kit Scs 2FLF horizontal empty BOK</b></p> <p>Low current version made of galvanized steel sheet 1.5mm with strain relief stampings and knurled screw for lateral fixing in the trunking shell. Color: RAL 7032 pebble gray</p>	
	<p><b>55039 - Installation kit socket outlet T13 3FLF horizontal SB BOK</b></p> <p>Installation kit socket T13 3FLF horizontal SB BOK made of galvanized sheet steel 1.5mm with knurled screw for lateral fixing in the trunking shell. Dimension: 302x47(53)x40mm Color: RAL 7032 pebble gray Equipped, wired and tested: 1 pcs. blind terminal 7x2.5mm<sup>2</sup> 10127 3 pcs. socket T13 FLF white 55200 1x L1 / 1x L2 / 1x L3 1 pc. Td-cable 5x1.5mm<sup>2</sup> / 1000mm 1 pc. FK junction box technofil 49909 (10A)</p>	
	<p><b>55041 - Installation kit socket T23 3FLF horizontal SB BOK</b></p> <p>Installation kit socket T23 3FLF horizontal SB BOK made of galvanized sheet steel 1.5mm with knurled screw for lateral fixing in the trunking shell. Dimension: 302x47(53)x40mm Color: RAL 7032 pebble gray Equipped, wired and tested: 1 pcs. blind terminal 7x2.5mm<sup>2</sup> 10127 3 pcs. socket T23 FLF white 55210 1x L1 / 1x L2 / 1x L3 1 pc. Td-cable 5x2.5mm<sup>2</sup> / 1000mm 1 pc. FK socket SK ecobus power 5x2.5<sup>2</sup> Pow 5P 49701P (16A)</p>	
	<p><b>51880 - Cable bushing with filler piece BOK</b></p> <p>made of polycarbonate crystal clear with transparent filler Dimension: 86x60x9.5mm</p>	
	<p><b>52465/0 - St lid BOK 8880/400 SK 0</b></p> <p>made of sendzimir galvanized steel sheet 4mm dimension: 1000x406</p>	
	<p><b>52467/0 - St lid BOK 8880/400 SK 0 BL</b></p> <p>made of sendzimir-galvanized steel sheet 4mm dimension: 500x406mm with brush strips as cable outlet, for 3mm finished floor height</p>	



## System overview



















### Floor channel BOK 8880 400x50mm integrated leveling device

	<b>52466/0 - St lid BOK 8880/400 SK 0 KD</b> made of sendzimir galvanized steel sheet 4mm dimension: 500x406mm with cable gland	
	<b>52467/0SB - St lid visible BOK 8880/400 SK 0 BL</b> made of sendzimir galvanized steel sheet 4mm dimension: 500x406mm with brush strip as cable outlet, top flush for visible lid	
	<b>52468/0 - St lid BOK 8880/400 SK 0 KMn</b> made of sendzimir-galvanized steel sheet 4mm dimension 500x406mm with cable trough enclosed loose	
	<b>52479/0SB - Cr lid visible BOK 8880/400 SK 0 BL</b> made of chrome steel V2A 4mm, brushed Dimensions: 490x406mm With brush strip 54x30mm as a cable outlet top flush for visible cover	
	<b>52469/0 - St lid BOK 8880/400 SK 0</b> made of sendzimir galvanized steel sheet 4mm dimension: 500x406mm	
	<b>52474/22 - Al lid with rim BOK 22 8880/400 KMn</b> made of aluminum 3mm dimension: 500x399x26mm edge height inside occupiable: 23mm cable trough loosely enclosed	
	<b>52474/12 - Al lid with rim BOK 12 8880/400 KMn</b> made of aluminum 3mm dimension: 500x399x16mm edge height inside 13mm cable tray enclosed loose	
	<b>52478/0SB - Cr lid visible BOK 8880/400 SK 0</b> made of chrome steel V2A 4mm, brushed dimension: 990x406mm	
	<b>55019 - Installation kit bticino 2x2-3gang empty BOK</b> made of galvanized sheet steel color: RAL 7032 pebble gray	
	<b>52404/100 - Leveling bar connection BOK 8880/400</b> made of sendzimir galvanized steel sheet 4mm dimensions: 360x100mm with 3 leveling hexagonal screws M10x60 polyamide with blind rivets for fastening to channel shell for additional mounting in case of missing connection.	



## System overview




### Floor channel BOK 8880 400x50mm integrated leveling device

	<p><b>55031 - Installation kit Sts 3FLF horizontal empty BOK</b></p> <p>made of galvanized sheet steel 1.5mm with knurled screw for lateral fixing in the trunking shell. Dimension: 302x47(53)x40mm Color: RAL 7032 pebble gray Equipped: 1 pcs. blind hole clamp 7x2.5mm<sup>2</sup> 10127</p>	
	<p><b>52344 - Insert Sts 3FLF horizontal SB BOK</b></p> <p>made of galvanized sheet steel 1.5mm with knurled screw for lateral fixing in the trunking shell Dimensions: 302x47(53)x40mm Color: RAL 7032 pebble gray equipped, wired and tested: 1 pcs. blind hole terminal 7x2.5mm<sup>2</sup> 10127 3 pcs. socket T13 FLF white 55200 1x L1 / 1x L2 / 1x L3 1 pcs. Td cable 5x1.5mm<sup>2</sup> / 1000mm. 1 pc. FK socket SK ecobus power 5x2.5<sup>2</sup> Pow 5P 49701P (16A)</p>	
	<p><b>55033 - Installation kit Sts 6FLF horizontal empty BOK</b></p> <p>made of galvanized sheet steel 1.5mm with knurled screw for lateral fixing in the trunking shell. Dimension: 525x47(53)x40mm Color: RAL 7032 pebble gray Equipped: 1 pcs. blind hole clamp 10x2.5mm<sup>2</sup> 10128</p>	
	<p><b>51049 - Adjustable cable trough BOK 8880 fDsb</b></p> <p>made of polycarbonate crystal clear for cover visible for mounting with threaded bolt</p>	
	<p><b>51069 - Cable trough levelable BOK SK 0-21mm</b></p> <p>made of polycarbonate crystal clear for cover visible for mounting with threaded bolt</p>	
	<p><b>52401 - Mounting bracket 50 BOK 8880/50</b></p> <p>made of sheet steel 2.5mm for floor trunking BOK 8880 height 50mm</p>	
	<p><b>52407 - Connecting link straight BOK 8880</b></p> <p>made of sheet steel dimension: 130x10x2.5mm with 4 pieces hexagonal screws M4x8 for connecting the channel shells</p>	
	<p><b>52415 - U-clamp profile reinforced 1-3mm</b></p> <p>as edge protection profile for sheet thickness up to 3mm</p>	
	<p><b>52408 - Angle connecting link 90° BOK 8880</b></p> <p>made of sheet steel dimension: 67.5/67.5x10x2.5mm with 4 pcs hexagonal bolts M4x8 for connecting the channel shells</p>	



System overview

Floor channel BOK 8880 400x50mm integrated leveling device

	<b>52420 - Brush strip cpl. BOK 8880 s=6</b> made of plastic, black dimension: 54x35mm bristles length: 25mm	
	<b>52421 - Brush strip cpl. BOK 8880 s=4 visible</b> made of plastic, black dimension: 54x37mm bristles length: 30mm	