



Parapet trunking system BRK 4675 140x90



Parapet channel 4675 140x90 mm. Often used for the development of MVE 4675.

Components

| | 53353 - Terminal block 6mm² L/N/PE mountable on DIN-35 rail consisting of: 1 pcs. Branch terminal 6mm ² gray 30841GR 1 pcs. Branch terminal 6mm ² blue 30841BL 1 pc. Branch terminal 6mm ² green/yellow 30841E including cover and support bolt. | |
|----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
| | 53057 - Plug-in cover A150 elx BRK 4675/4775 | |
| | Made of aluminum profile 1.7mm , colorless anodized for EDIZIOdue socket spacing 150mm Length: 80mm | |
| | 53055 - Plug-in cover A150 ws BRK 4675/4775 | |
| | made of aluminum profile 1.7mm, for EDIZIOdue sockets distance 150mm Color: RAL 9010 Pure white Length: 80mm | |
| <u></u> | 53706 - End wall ws BRK 4675/140x90 | |
| | made of aluminum 1.5mm with 4 laterally recessed mounting screws with dowels Color: RAL 9010 Pure White | |
| <u> </u> | 53707 - End wall FnW BRK 4675/140x90 | |
| | made of aluminum 1.5mm with 4 sideways countersunk fixing screws with dowels Color: at choice | |
| | 53708 - 0 | |
| | made of aluminum 1.5mm, colorless anodized with 4 laterally countersunk fixing screws with dowels | |





| | 53701 - Channel shell FnW BRK 4675/140x90 | |
|---|-------------------------------------------------------------------------------------------------|---------------|
| 8 | made of aluminum profile 2.2mm with combination rail for mounting the | |
| | installation apparatus including connecting material and ground wire | |
| | Color: at choice | |
| | Length: 2000mm | |
| | 53702 - Channel shell elx BRK 4675/140x90 | |
| | made of aluminum profile 2.2mm, colorless anodized with combination rail for | |
| | mounting the installation apparatus including connecting material and ground wire | E161-9669/944 |
| | Length: 2000mm | |
| | 53700 - Channel shell ws BRK 4675/140x90 | |
| | made of aluminum profile 2.2mm with combination rail for mounting the | |
| | installation apparatus including connecting material and ground wire | |
| | Color: RAL 9010 pure white | |
| | Length: 2000mm | |
| • | 53535 - Connector BRK/MEK IG90° to AS | |
| | made of galvanized steel for inside miter 90° BRK/MEK 4670 / 4675 | |
| | 53511 - Connector straight BRK/MEK to AS | |
| | made of galvanized steel for straight connection BRK/MEK 4670 / 4675 | |
| | with hexagonal slotted screws made of galvanized steel M6x16, spring washers and sliding blocks | 国际外部的第4 |
| | for insertion in profile rail no. 4383, type C30 | |
| | 59014 - Distance compensation plate | |
| | pack of 100, assorted thicknesses 1, 2, 3, 5 and 10mm | |
| | 53071 - Connecting bolt set 90° / BRK 4675 | |
| ~ | made of steel galvanically nickel-plated for connecting the channel shells | |
| | 90° inside and outside miter Dimension: ø6x22x22mm Set of 4 pcs. | |
| | | |
| | | |
| | 53534 - Connecting piece BRK/MEK AG 90° to AS | |





| | 53570/130 - Cable tie plate STK to AS | |
|----|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
| | made of sheet steel 1.5mm dimension 130x60x19mm with slot nut and screw to mount on anchor rail 29x15x2mm Color: RAL 7032 pebble gray | |
| 1 | 53070 - Connecting bolt set straight / BRK 4675 | |
| | made of steel galvanically nickel-plated for connecting the channel shell profiles Dimension: Ø 6x60mm Set of 4 pcs. | |
| | 53714 - Connecting set straight BRK/MEK 4675 | |
| | consisting of: 1 pc. Connecting piece straight BRK/MEK to AS made of steel galvanized for straight connection 4 pcs. Connecting bolt straight / BRK/MEK 4675 made of steel galvanized nickel-plated for connecting the channel shell profiles. Dimension: ø 6x60mm | |
| • | 53715 - Connection kit IG90º BRK/MEK 4675 | |
| | for 90° inside miter consisting of: 1 pc. Connecting piece BRK/MEK IG90° to AS made of steel galvanized 4 pcs. Connecting bolt 90° / BRK/MEK 4675 made of steel galvanized nickel-plated for connecting the channel shell profiles with miter cut 45°. Dimension: ø6x22x22mm | |
| | 53716 - Connecting set AG90º BRK/MEK 4675 | |
| ~ | for 90° external miter consisting of: 1 pc. Connecting piece BRK/MEK AG90° to AS made of steel galvanized 4 pcs. Connecting bolt 90° / BRK/MEK 4675 made of steel galvanized nickel-plated for connecting the channel shell profiles with miter cut 45°. Dimension: ø6x22x22mm | |
| f. | 53009 - Connector 90° flat connection to anchor channel | |
| | made of steel galvanized for 90° flat connection BRK 4670 / 4675 | |
| 4 | 53017 - Plug-in cover elx A100 BRK 4675 | |
| | made of aluminum profile 1.7mm colorless anodized for EDIZIOdue socket spacing 100mm Color: RAL 9010 Pure white Length: 30mm | |
| | 52010 - Cable tray PVC BRK 4675 | |
| | made of plastic PVC to hang into the channel shell color: white width: 38mm / length: 1850mm | |
| | 53035 - Mounting plate AS with NIS box H69.5 | |
| | to BRK 4675/x90Fastening with anchoring studsHeight: 69.5mm | |





| | 53025 - Plug-in lid ws BRK A120 4675 | |
|---|------------------------------------------------------------------------------------------------------------------------------------|----------------|
| | made of aluminum profile 1.7mm color: RAL 9010 pure white | |
| | for EDIZIOdue socket spacing 120mm Color: RAL 9010 pure white | 12126044-0-744 |
| | Length: 50mm | |
| | 53015 - Plug-in lid ws BRK A100 4675 | |
| | made of aluminum profile 1.7mm color: RAL 9010 pure white for EDIZIOdue socket spacing 100mm | |
| | Color: RAL 9010 pure white | |
| | Length: 30mm | |
| | 53026 - Plug-in cover FnW BRK A120 4675 | |
| | made of aluminum profile 1.7mm color: RAL 9010 pure white | |
| | for EDIZIOdue socket spacing 120mm Color: at choice | |
| | Length: 50mm | |
| / | 53027 - Plug-in cover anodized A120 BRK 4675 | |
| | made of aluminum profile 1.7mm colorless anodized | |
| | for EDIZIOdue socket spacing 120mm Color: RAL 9010 Pure white | |
| | Length: 50mm | |
| | 53948 - Snap-on mounting plate with NIS box | |
| | for BRK 4671/x79 suitable for screw cap. and BRK 4675/x90 plug-in cap for JK apparatus Height: 63.5mm / installation depth: 68.5mm | |
| | | |
| | 53004 - Plug-type cover BRK 4675/4775 FnW | |
| | made of aluminum profile 1.7mm color: at choice Length: 2000mm | |
| | 53005 - Plug-type cover elx BRK 4675/4775 | |
| | made of aluminum profile 1.7mm , colorless anodized | |
| | Length: 2000mm | |
| | 53003 - Plug-type cover withe BRK 4675/4775 | |
| | made of aluminum profile 1.7mm color: RAL 9010 pure white Length: 2000mm | |
| | 59016 - Sound barrier Ø 30x300mm | |
| | Mineral fiber braids wrapped and compacted with crossed wire meshPacking | |
| | unit: 15 pcs. | |

woertz (2)



System overview

| 8 | 53053 - Plug-in cover CEE 16A 5p elx BRK 4675 | |
|--------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|
| A .O. | made of aluminum profile 1.7mm, colorless anodized for socket CEE 16A 5P | |
| | type 75 including extension bolt and fixing material | |
| | length 150mm | |
| / | 53056 - Plug-type cover BRK 4675/4775 FnW | 国治常常。54回 同時間にあった。 高麗教学家会力 |
| | made of aluminum profile 1.7mm, for EDIZIOdue socket spacing 150mm | |
| | Color: at choice Length: 80mm | LE18:0:0037.974 |
| 8.4 | 53052 - Plug-in cover CEE 16A 5p ws BRK 4675 | |
| R .O. | made of aluminum profile 1.7mm for socket CEE 16A 5P type 75 | |
| | including extension bolts and fastening material Color: RAL 9010 Pure white | 回議論就發展的 |
| | Length 150mm | |
| 4 | 53016 - Plug-in cover FnW A100 BRK 4675 | |
| | made of aluminum profile 1.7mm color: color: at choice | |
| | for EDIZIOdue socket spacing 100mm length: 30mm | 1216/12/03/1944 |
| 8 | 53050 - Plug-in cover CEE 16A 3p ws BRK 4675 | |
| ×.01 | made of aluminum profile 1.7mm for socket CEE 16A 3P type 63 | |
| | including extension bolts and fastening material Color: RAL 9010 Pure white | LIINTAKS |
| | Length 150mm | |
| | 53050/LED - Plug-in cover CEE 16A 3p LED ws BRK 4675 | |
| 7.0 | made of aluminum profile 1.7mm for socket CEE 16A 3P type 63 and punching | |
| | for LED voltage indicator, including extension bolt and fixing material. Color: RAL 9010 Pure white Length 150mm | |
| | 53710 - Connection kit FV90º BRK/MEK 4675 | |
| | for 90° flat connection consisting of: 1 pc. Connecting piece BRK/MEK FV90° to | |
| | AS made of steel galvanized 4 pcs. Connecting bolt 90° / BRK/MEK 4675 made of steel galvanized nickel-plated for connecting the channel shell profiles with | |
| | miter cut 45°. Dimension: ø6x22x22mm | |
| 3 | 53051 - Plug-in cover CEE 16A 3p elx BRK 4675 | |
| 3.0 | made of aluminum profile 1.7mm, colorless anodized for socket CEE 16A 3P | |
| | type 63 including extension bolt and fixing material | CUL:203:9H |
| | length 150mm | |





| | 53043 - Plug-in lid flush ws BRK 4675/4775 | |
|--|--------------------------------------------------------------------------|--|
| | made of aluminum profile 1.7mm color: RAL 9010 pure white Length: 2000mm | |
| | 53044 - Plug-in cover flush FnW BRK 4675/4775 | |
| | made of aluminum profile 1.7mm color: at choice Length: 2000mm | |
| | 53045 - Plug-in lid flush elx BRK 4675/4775 | |
| | made of aluminum profile 1.7mm , colorless anodized Length: 2000mm | |