



3410GR - Double level terminal DIN35 6mm² gray



Double deck clamp with stainless steel screws, countersunk for cross connections, 2x3-digit marking option on both sides

Characteristics	
Eldas number	158102337
Base Unit	Piece
availability	Delivery according to agreement
EAN Code	7611718205507
group	165000
Packaging unit	25
country of origin	СН
Customs tariff number	8536.9080
Weight (g)	30 g
Color	gray
Technical data	
Dimensions length x width x height (mm)	78x7x64 mm
Dimensions length x width x height (inch)	3.07x0.28x2.52 inch
Cross section (mm ²)	0,5 - 6 mm²
Nominal current (A)	41 A





3410GR - Double level terminal DIN35 6mm² gray

Rated voltage (V)	500 V
Connection type	Screw terminal
DIN rail type	DIN-35
Number of connection point	4
Number of floor	2
Number of potentials	2
Clamping screw M	МЗ
Insulating material	PA66
Nominal Cross-section (mm ²)	6 mm²
Stripping length mm (mm)	9 mm
Head reception room width x height (mm)	3.8x5.7 mm
Rating data according to UL 1059	
Rated voltage US (V)	300 V
Nominal cross section (AWG)	10 AWG
Cross-section (AWG)	10 - 20 AWG
Stripping length (inch)	0,35 inch





3410GR - Double level terminal DIN35 6mm² gray

Product accessories

	80070R - Test plug Ø M3 red, socket 4mm
	plug and adaptor in one piece
a company of the start of the start	2737R - Test plug Ø 2.8mm red, socket 4mm
	connecting cable incl.
	Bezeichnungskarte_6x12mm - Designation cards 6x12mm
	Various designation labels 6x12mm with different embossing.
	Bezeichnungskarte_6x9mm - Designation card 6x9mm
	Various designation plates with different embossing.
	Bezeichnungskarte_6x3mm - Designation card 6x3mm
	Various designation plates with different embossing.
	3411 - End barrier DIN35 grey to 3410
	End wall suitable for 3410
	3412 - Partition DIN35 grey to 3410
	Partition wall suitable for 3410
	30199 - Stopper DIN35 height 50mm
	Aluminum alloy locking piece
Ħ	81507/2 - Cross-connection 2-pole to DIN32/35 6mm ² terminal blocks
	Insulated cross-connection 2-pole to terminal blocks DIN32/35 6mm ² including screws M2.5. dimension: 12.6x20.8 mm
ŤŤŤ	81507/3 - Cross-connection 3-pole to terminals DIN32/35 6mm ²
	Insulated cross-connection 3-pole to terminals DIN32/35 6mm ² including screws M2. Dimension: 5.19.7x20.8 mm
iiii	81507/4 - Cross-connection 4-pole to terminals DIN32/35 6mm ²
	Insulated cross-connection 4-pole to terminals DIN32/35 6mm ² including screws M2.5. dimension: 26.8x20.8 mm





3410GR - Double level terminal DIN35 6mm² gray

	81507/5 - Cross-connection 5-pole to terminals DIN32/35 6mm ²
	Insulated cross-connection 5-pole to terminals DIN32/35 6mm ² including screws M2.5. dimension: 33.9x20.8 mm
	81507/10 - Cross-connection 10-pole to terminals DIN32/35 6mm ²
	Insulated cross-connection 10-pole to terminals DIN32/35 6mm ² including screws M2.5. dimension: 69.4x20.8 mm
Ī	81506 - Cross connection bolt single M3 insulated (10.6 mm)
	Cross-connection bolt complete with spacer sleeve. Standard version. Dimension: 10.6 mm
	30441 - Link to cross-connections
	to terminals 4mm 2
	81452L - Link to cross-connections
	to terminals 6mm 2
and a second	3826/4 - Cover for 4 terminals yellow
	with black printing,to series 3452/6 and 3410
wanted B	3826/5 - Cover for 5 terminals yellow
	with black printing, to series 34526 and 3410
wanted - D	3826/6 - Cover for 6 terminals yellow
	with black printing, to series 34526 and 3410
and the second s	3826/7 - Cover for 7 terminals yellow
	with black printing, to series 34526 and 3410
and a second and a second a se	3826/8 - Cover for 8 terminals yellow
	with black printing, to series 34526 and 3410
	81440 - Sealing eyelet Ø 3.2mm
	Sealing eyes
Ant	3512 - Sealing screw M3x25 of polyamide
	Sealing screw spring-loaded test probes, several numbers of poles can be lined up





3410GR - Double level terminal DIN35 6mm² gray

Product systems



Double deck clamps DIN 35

Various double-deck clamps.

