





Characteristics	
Eldas number	158210237
Base Unit	Piece
availability	available from stock
EAN Code	7611718202186
group	165000
Packaging unit	50
country of origin	СН
Customs tariff number	8536.9080
Weight (g)	12,8 g
Color	gray
Technical data	
Dimensions length x width x height (mm)	49x6x44 mm
Dimensions length x width x height (inch)	1.93x0.24x1.73 inch
Cross section (mm <sup>2</sup> )	0,5 - 4 mm²
Nominal current (A)	32 A





Rated voltage (V)	1000 V
Connection type	Screw terminal
DIN rail type	DIN-32
Number of connection point	2
Number of floor	1
Number of potentials	1
Clamping screw M	M3
Insulating material	PA66
Nominal Cross-section (mm <sup>2</sup> )	4 mm²
Stripping length mm (mm)	10 mm
Head reception room width x height (mm)	3.4x6 mm
Rating data according to UL 1059	
Rated voltage US (V)	600 V
Nominal cross section (AWG)	12 AWG
Cross-section (AWG)	12 - 20 AWG
Stripping length (inch)	0,39 inch





3301GR - Terminal DIN32 4mm2 grey

#### Product accessories

	80070R - Test plug Ø M3 red, socket 4mm plug and adaptor in one piece
	80070S - Test plug Ø M3 black, socket 4mm plug and adaptor in one piece
	2737R - Test plug Ø 2.8mm red, socket 4mm connecting cable incl.
	2737S - Test plug Ø 2.8mm black, socket 4mm connecting cable incl.
	<b>Bezeichnungskarte_6x12mm - Designation cards 6x12mm</b> Various designation labels 6x12mm with different embossing.
	Bezeichnungskarte_6x9mm - Designation card 6x9mm Various designation plates with different embossing.
3	Bezeichnungskarte_6x3mm - Designation card 6x3mm Various designation plates with different embossing.
	3661GR - End barrier DIN32 grey to 3301 null
	<b>3651GR - Partition DIN32 grey to 30111,3301,3302</b> for 30111,3301,3302
	<b>3758 - Stopper DIN32 height 30mm</b> from polyamide gray
	<b>3749 - Stopper DIN32 height 28mm</b> of anticorodal





Ħ	81506/2 - Cross-connection 2-pole to terminals DIN32/35 4mm <sup>2</sup>
	Insulated cross-connection 2-pole to terminals DIN32/35 4mm <sup>2</sup> including screws M3. Standard version. Dimension: 11.1x20.8 mm
	81506/3 - Cross-connection 3-pole to terminals DIN32/35 4mm <sup>2</sup>
	Insulated cross-connection 3-pole to terminals DIN32/35 4mm <sup>2</sup> including screws M3. Standard version. Dimension: 17.2x20.8 mm
	81506/4 - Cross-connection 4-pole to terminals DIN32/35 4mm <sup>2</sup>
	Insulated cross-connection 4-pole to terminals DIN32/35 4mm <sup>2</sup> including screws M3. Standard version. Dimension: 23.3x20.8 mm
	81506/5 - Cross-connection 5-pole to terminals DIN32/35 4mm <sup>2</sup>
	Insulated cross-connection 5-pole to terminals DIN32/35 4mm <sup>2</sup> including screws M3. Standard version. Dimension: 29.4x20.8 mm
	81506/10 - Cross-connection 10-pole to terminals DIN32/35 4mm <sup>2</sup>
	Insulated cross-connections 10-pole to terminals DIN32/35 4mm <sup>2</sup> including M3 screws. Standard version. Dimension: 59.9x20.8 mm
Ī	81506 - Cross connection bolt single M3 insulated (10.6 mm)
	Cross-connection bolt complete with spacer sleeve. Standard version. Dimension: 10.6 mm
	81410L - Link to cross-connections
	Connecting lug to terminals 4mm <sup>2</sup> . Dimension: 11.1x8 mm
<b>Г</b>	80049/4 - Warning plate for single terminal 4mm2
	to series 3450
Seeus	3886/4 - Cover for 4 terminals yellow
	with black printing, to series 3424,3450
	3886/5 - Cover for 5 terminals yellow
	with black printing, to series 3424,3450
- 1	3886/6 - Cover for 6 terminals yellow
	with black printing, to series 3424,3450





internet of the second se	<b>3886/7 - Cover for 7 terminals yellow</b> with black printing, to series 3424,3450
- D	<b>3886/8 - Cover for 8 terminals yellow</b> with black printing, to series 3424,3450
Ļ	81440 - Sealing eyelet Ø 3.2mm Sealing eyes
JAN 5	<b>3512 - Sealing screw M3x25 of polyamide</b> Sealing screw spring-loaded test probes, several numbers of poles can be lined up
automatic states	<b>30422 - Cover strip for terminal blocks 9.5mm, length 280mm</b> Cover strip for terminal blocks DIN32/35 9.5mm , length 280mm





3301GR - Terminal DIN32 4mm2 grey

### **Product systems**



Terminal blocks DIN32 2.5mm<sup>2</sup>-70mm<sup>2</sup>

Various terminal blocks DIN32 2.5mm<sup>2</sup>-70mm<sup>2</sup>.

