



Product data sheet

38300/4V - PE push-in spring terminal block 2-fold 4mm² yellow/green



Plug-in terminal block with 2 connection options and conductive to DIN rail.

Characteristics	
Eldas number	158436067
Base Unit	Piece
availability	available from stock
EAN Code	7611718250422
group	165000
Packaging unit	50
country of origin	CH
Customs tariff number	8536.9080
Weight (g)	6,63 g
Color	green/yellow
Technical data	
Dimensions length x width x height (mm)	47.8x6x32.1 mm
Dimensions length x width x height (inch)	1.88x0.24x1.26 inch
Cross section (mm ²)	0,5 - 4 mm ²
Nominal current (A)	32 A



Product data sheet

38300/4V - PE push-in spring terminal block 2-fold 4mm² yellow/green

Rated voltage (V)	800 V
Connection type	Plug-in spring terminal
DIN rail type	DIN-35
Number of connection point	2
Number of floor	1
Number of potentials	1
Insulating material	PA66
Nominal Cross-section (mm ²)	4 mm ²
Stripping length mm (mm)	12 mm
Head reception room width x height (mm)	3.7x3.6 mm
Rating data according to UL 1059	
Rated voltage US (V)	600 V
Nominal cross section (AWG)	12 AWG
Cross-section (AWG)	12 - 20 AWG
Stripping length (inch)	0,47 inch



Product data sheet


38300/4V - PE push-in spring terminal block 2-fold 4mm² yellow/green

Product accessories



Bezeichnungskarte_6x9mm - Designation card 6x9mm

Various designation plates with different embossing.



Bezeichnungskarte_6x3mm - Designation card 6x3mm

Various designation plates with different embossing.



38310 - Separation end wall to W-clamp 45°

null



3418 - Stopper DIN35 height 30mm

Makrolon locking piece



30370 - Stopper DIN35 height 23mm

Locking piece made of nickel-plated brass M3 screw



Product data sheet

38300/4V - PE push-in spring terminal block 2-fold 4mm² yellow/green

Product systems



Plug-in spring terminals with two connections DIN 35

Various plug-in spring terminals with two connections.

