



Product data sheet

3880/1P - Two-step terminal DIN32 4mm2 black



Characteristics	
Eldas number	158232237
Base Unit	Piece
availability	Delivery according to agreement
EAN Code	7611718206207
group	165000
Packaging unit	50
country of origin	CH
Customs tariff number	8536.9080
Weight (g)	17,5 g
Color	gray
Technical data	
Dimensions length x width x height (mm)	62x6x48 mm
Dimensions length x width x height (inch)	2.44x0.24x1.89 inch
Cross section (mm²)	0,5 - 4 mm²
Nominal current (A)	20 A



Product data sheet

3880/1P - Two-step terminal DIN32 4mm2 black

Rated voltage (V)	500 V
Connection type	Screw terminal
DIN rail type	DIN-32
Number of connection point	4
Number of floor	2
Number of potentials	1
Clamping screw M	M3
Insulating material	PA66
Nominal Cross-section (mm²)	4 mm²
Stripping length mm (mm)	10 mm
Head reception room width x height (mm)	3.2x5 mm
Rating data according to UL 1059	
Rated voltage US (V)	300 V
Nominal cross section (AWG)	12 AWG
Cross-section (AWG)	12 - 20 AWG
Stripping length (inch)	0,39 inch



Product data sheet

3880/1P - Two-step terminal DIN32 4mm² black

Product accessories




80222/6 - Test adaptor to terminal series 3450 2 spiral springs

with hole for strands up to 0.75mm²



Bezeichnungskarte_6x9mm - Designation card 6x9mm

Various designation plates with different embossing.



Bezeichnungskarte_6x3mm - Designation card 6x3mm

Various designation plates with different embossing.



81526/2 - Cross-connection 2pole to terminal 2.5mm²/4mm²

Cross connections complete with M3 screws. 11.1x17.8 mm



81526/3 - Cross-connection 3-pole to terminals DIN15/32/35 2.5mm²/4mm²

Insulated cross-connection 3-pole to terminals DIN15/32/35 2.5mm²/4mm² including screws M3. Dimension: 17.2x17.8 mm



81526/4 - Cross-connection 4-pole to terminals DIN15/32/35 2.5mm²/4mm²

Insulated cross-connection 4-pole to terminals DIN15/32/35 2.5mm²/4mm² including screws M3. Dimension: 23.3x17.8 mm



81526/5 - Cross-connection 5-pole to terminals DIN15/32/35 2.5mm²/4mm²

Insulated cross-connection 5-pole to terminals DIN15/32/35 2.5mm²/4mm² including screws M3. Dimension: 29.4x17.8 mm




81526/10 - Cross-connection 10-pole to terminals DIN15/32/35 2.5mm²/4mm²

Insulated cross-connection 10-pole to terminals DIN15/32/35 2.5mm²/4mm² including screws M3. Dimension: 59.9x17.8 mm



81526 - Cross connection bolt single M3, insulated (9.1 mm)

Cross connection bolt complete with spacer sleeve. 9.1 mm



30441 - Link to cross-connections

to terminals 4mm²



3894/4 - Cover for 4 terminals yellow

with black printing, to series 3430



Product data sheet

3880/1P - Two-step terminal DIN32 4mm2 black



3894/5 - Cover for 5 terminals yellow

with black printing, to series 3430



3894/6 - Cover for 6 terminals yellow

with black printing, to series 3430



3894/7 - Cover for 7 terminals yellow

with black printing, to series 3430



3894/8 - Cover for 8 terminals yellow

with black printing, to series 3430



81440 - Sealing eyelet Ø 3.2mm

Sealing eyes



3512 - Sealing screw M3x25 of polyamide

Sealing screw spring-loaded test probes, several numbers of poles can be lined up



30421 - Cover strip for double level and terminal blocks 9.5mm, length 280mm

Cover strip for double level and terminal blocks DIN32/35 9.5mm , length 280mm



Product data sheet

3880/1P - Two-step terminal DIN32 4mm² black

Product systems

Double level terminals 1-pole DIN32

Various double level terminals 1-pole DIN32

