



49345/10M25/C2 - Pre-wired Connecting C2-M 5G2.5 10m HF DALI



Pre-wired connector, plug 5-poles code 2, DALI, with 10 m cable 5G2.5 mm ² with free end, conductor compressed, 20 A, 250 V, halogen free, behaviour to fire classification Cca

157510227
Piece
Delivery according to agreement
7611718280368
170000
1
СН
8544.4229
1745 g
pastel blue
Connecting cable plug
Code 2
10000 x 52.3 x 13.7 mm
394 x 2.06 x 0.54 inch





49345/10M25/C2 - Pre-wired Connecting C2-M 5G2.5 10m HF DALI

Degree of protection	IP20, IP40 (Connected),IP68 (with sealing cover)
Number of poles	5 pole
Material	Polyamide
Construction (mm²)	5x2.5 mm ²
Rated current heavy current part (A)	20 A
Rated voltage heavy current part (V)	250 V
Cable length (m)	10 m
Halogen free	Yes
Cable type	Halogen free cables
International designation	N05Z1Z1-F
Reaction to fire classification	Cca s1 d0 a1
Cross section (mm²)	2.5 mm²
Copper conductor	Fine stranded KL5 EN60228
cores insulation	Flame retardant polyolefin
Cores colors	brown,blue,green/yellow,black,gray
Sheat insulation	Polyolefin flame retardant
Sheath color	Black
Minimum bending radius	6xD
Operating Temperature (°C)	-15 till 70 °C
Installation temperature min. (°C)	5 ℃
Test current heavy current part (kV)	4 kV





49345/10M25/C2 - Pre-wired Connecting C2-M 5G2.5 10m HF DALI

Halogen free acc. to	IEC/EN60754-1/2
Flame retardant according to	IEC/EN60332-1-2
Minimal smoke emision acc. to	IEC/EN 61034-2





49345/10M25/C2 - Pre-wired Connecting C2-M 5G2.5 10m HF DALI

Product accessories





49345/10M25/C2 - Pre-wired Connecting C2-M 5G2.5 10m HF DALI

Product systems

Plug connections code 2 for light control DALI, 5-pole (LNPE D1, D2) 5 pole connectors code 2 for light control DALI.	
Plug and connecting cable from C2 5P	
M M/F 5 pole Dali	