



Product data sheet

30432 - Three terminal block DIN35 4mm² PE-L gray



Three-pole installation terminal without protective conductor, with stainless steel screws, 4x3-digit designation option, for cross-connections recessed 2-pole

Characteristics	
Eldas number	158102037
Base Unit	Piece
availability	Delivery in 4 weeks
EAN Code	7611718204739
group	165000
Packaging unit	25
country of origin	CH
Customs tariff number	8536.9080
Weight (g)	19 g
Color	gray
Technical data	
Dimensions length x width x height (mm)	79.5x6x50 mm
Dimensions length x width x height (inch)	3.13x0.24x1.97 inch
Cross section (mm²)	0,5 - 4 mm²
Nominal current (A)	34 A



Product data sheet

30432 - Three terminal block DIN35 4mm² PE-L gray

Rated voltage (V)	400 V
Connection type	Screw terminal
DIN rail type	DIN-35
Number of connection point	5
Number of floor	3
Number of potentials	3
Clamping screw M	M3
Insulating material	PA66
Nominal Cross-section (mm²)	4 mm²
Stripping length mm (mm)	8,5 mm
Head reception room width x height (mm)	3.1x3.4 mm
Rating data according to UL 1059	
Rated voltage US (V)	300 V
Nominal cross section (AWG)	12 AWG
Cross-section (AWG)	12 - 20 AWG
Stripping length (inch)	0,34 inch



## Product data sheet

30432 - Three terminal block DIN35 4mm<sup>2</sup> PE-L gray

### Product accessories



#### 81536/2 - Cross-connection 2-pole to three-pole terminals DIN35 4mm<sup>2</sup>

Insulated cross-connection 2-pole to three-pole terminals DIN35 4mm<sup>2</sup> including screws M2.5. dimension: 11.1x11.4 mm



#### 81536/3 - Cross-connection 3-pole to three-pole terminals DIN35 4mm<sup>2</sup>

Insulated cross-connection 3-pole to three-pole terminals DIN35 4mm<sup>2</sup> including screws M2.5. dimension: 17.2x11.4 mm



#### 81536/4 - Cross-connection 4-pole to three-pin terminals DIN35 4mm<sup>2</sup>

Insulated cross-connection 4-pole to three-pole terminals DIN35 4mm<sup>2</sup> including screws M2.5. dimension: 23.3x11.4 mm



#### 81536/5 - Cross-connection 5-pole to three-pin terminals DIN35 4mm<sup>2</sup>

Insulated cross-connection 5-pole to three-pin terminals DIN35 4mm<sup>2</sup> including screws M2.5. Dimension: 29.4x11.4 mm



#### 81536/10 - Cross-connection 10-pole to three-pin terminals DIN35 4mm<sup>2</sup>

Insulated cross-connection 10-pole to three-pin terminals DIN35 4mm<sup>2</sup> including screws M2.5. dimension: 59.9x11.4 mm



#### 81535 - Cross connection bolt single M2.5 insulated (4.1 mm)

Cross connection bolt complete with spacer sleeve. 4.1 mm



#### 30441 - Link to cross-connections

to terminals 4mm 2



#### 80247 - Test plug Ø 2.3mm red, socket 4mm

connecting cable incl.



#### 80248 - Test plug Ø 2.3mm black, socket 4mm

connecting cable incl.



#### Bezeichnungskarte\_6x9mm - Designation card 6x9mm

Various designation plates with different embossing.



#### Bezeichnungskarte\_6x3mm - Designation card 6x3mm

Various designation plates with different embossing.



Product data sheet

30432 - Three terminal block DIN35 4mm<sup>2</sup> PE-L gray



**30438 - End barrier DIN35 grey to 30431, 30432**

End wall suitable for 30431, 30432



**3418 - Stopper DIN35 height 30mm**


Makrolon locking piece



## Product data sheet

30432 - Three terminal block DIN35 4mm<sup>2</sup> PE-L gray

## Product systems



### Three-stud installation clamps DIN 35

Various three-stud installation clamps.

