



Product data sheet

49345/5F25/C2 - Pre-wired Connecting C2-F 5G2.5 5m HF DALI



Pre-wired connector, socket 5-poles code 2, DALI, with 5 m cable 5G2.5 mm ² with free end, conductor compressed, 20 A, 250 V, halogen free, behaviour to fire classification Cca

| Characteristics | |
|---|---------------------------------|
| Eldas number | 157510127 |
| Base Unit | Piece |
| availability | Delivery according to agreement |
| EAN Code | 7611718274558 |
| group | 170000 |
| Packaging unit | 1 |
| country of origin | CH |
| Customs tariff number | 8544.4229 |
| Weight (g) | 900 g |
| Color | pastel blue |
| Connector type | Connection cable socket |
| Coding plug connection | Code 2 |
| Technical data | |
| Dimensions length x width x height (mm) | 5000 x 52.3 x 13.7 mm |
| Dimensions length x width x height (inch) | 197 x 2.06 x 0.54 inch |



Product data sheet

49345/5F25/C2 - Pre-wired Connecting C2-F 5G2.5 5m HF DALI

| | |
|--------------------------------------|--|
| Degree of protection | IP20, IP40 (Connected),IP68 (with sealing cover) |
| Number of poles | 5 pole |
| Material | Polyamide |
| Construction (mm²) | 5x2.5 mm² |
| Rated current heavy current part (A) | 20 A |
| Rated voltage heavy current part (V) | 250 V |
| Cable length (m) | 5 m |
| Halogen free | Yes |
| Cable type | Halogen free cables |
| International designation | N05Z1Z1-F |
| Reaction to fire classification | Cca s1 d0 a1 |
| Cross section (mm²) | 2.5 mm² |
| Copper conductor | Fine stranded KL5 EN60228 |
| cores insulation | Flame retardant polyolefin |
| Cores colors | brown,blue,green/yellow,black,gray |
| Sheat insulation | Polyolefin flame retardant |
| Sheath color | Black |
| Minimum bending radius | 6xD |
| Operating Temperature (°C) | -15 till 70 °C |
| Installation temperature min. (°C) | 5 °C |
| Test current heavy current part (kV) | 4 kV |



Product data sheet

49345/5F25/C2 - Pre-wired Connecting C2-F 5G2.5 5m HF DALI

| | |
|--------------------------------|-----------------|
| Halogen free acc. to | IEC/EN60754-1/2 |
| Flame retardant according to | IEC/EN60332-1-2 |
| Minimal smoke emission acc. to | IEC/EN 61034-2 |



Product data sheet

49345/5F25/C2 - Pre-wired Connecting C2-F 5G2.5 5m HF DALI

Product accessories



Product data sheet

49345/5F25/C2 - Pre-wired Connecting C2-F 5G2.5 5m HF DALI

Product systems



Plug connections code 2 for light control DALI, 5-pole (LNPE D1, D2)

5 pole connectors code 2 for light control DALI.

