



Product data sheet

49074G/L2 - Raptor switch actuator 3-fold - KNX - L2 - Code 1



Raptor switch actuator 3-fold - 16 A max. - 3 x 3-pole socket Code 1 - 1-phase powered, phase L2 - KNX bus coupler integrated - IP20

Characteristics

Eldas number	405441227
Base Unit	Piece
availability	available from stock
EAN Code	7611718272066
group	376000
Packaging unit	1
country of origin	CH
Customs tariff number	8536.5000
Weight (g)	585 g
Color	black
Coding plug connection	Code 1

Technical data

Peak inrush current	max. 500 A (2 ms)
Dimensions length x width x height (mm)	170x70x66 mm
Dimensions length x width x height (inch)	6.69x2.76x2.6 inch



Product data sheet

49074G/L2 - Raptor switch actuator 3-fold - KNX - L2 - Code 1

Degree of protection	IP20
Flat cable contacting type	Piercing contact (knife)
Material	PA 6.6
Configuration mode	S-mode
Type of connection	3-pole socket
Plug-in system	Code 1
Number of channels	3
Type of mounting	Flat cable Woertz combi 5G2.5 2x1.5 mm ²
Transmission media	KNX TP1
Operating Temperature (°C)	-5 - 45 °C
Installation temperature min. (°C)	10 °C
Rated current per channel (A)	16 A
Contact to flat cable	L2NPE KNX
Operating voltage	230 VAC ± 10 %
KNX bus voltage (type)	29 VDC SELV Typ
Switching voltage (VAC)	230 VAC



Product data sheet

49074G/L2 - Raptor switch actuator 3-fold - KNX - L2 - Code 1

Product accessories



Product data sheet

49074G/L2 - Raptor switch actuator 3-fold - KNX - L2 - Code 1

Product systems



KNX flat cable actuators for switching function

Various KNX flat cable actuators for switching function.



Flat cable system Combi 5G2.5 2x1.5 mm² (KNX)

This flexible system is the basis for decentralized building automation and combines power current and bus data line in a single cable application.

The areas of application are office and public buildings, industrial buildings, hotels or even modular buildings with a high degree of prefabrication for quick installation.

