



49908 - Junction box flat cable Technofil $3x \emptyset = 10 \text{ mm}$ transparent



Junction box to flat cable Technofil $3x \varnothing = 10 \text{ mm}$ transparent, with open pointed screws

Characteristics	
Eldas number	150704337
Base Unit	Piece
availability	Delivery in 4 weeks
EAN Code	7611718207945
group	170000
Packaging unit	50
country of origin	СН
Customs tariff number	8536.9080
Weight (g)	57 g
Color	gray
Technical data	
Вох Туре	Junction boxes
Fire load (KWh)	0,3 kWh
Dimensions length x width x height (mm)	62x38x31 mm
Dimensions length x width x height (inch)	2,44x1,5x1,22 inch





49908 - Junction box flat cable Technofil $3x \emptyset = 10 \text{ mm}$ transparent

Degree of protection	IP20, IP20D (with plug 06753)
Metal parts	Corrosion protected
Flat cable contacting type	Piercing contact (screw)
Number of poles	5 pole
Contacting type	Screw terminal
Connection conductor (mm²)	1,5 - 2,5 mm²
Connecting capacity (mm)	3,75 mm
Cable gland (mm)	3x10 mm
Rated current heavy current part (A)	17.5(1.5mm2) A
Rated voltage heavy current part (V)	500 V
Operating Temperature (°C)	-15 to 85 °C
Installation temperature min. (°C)	5 °C
Plastic parts	Halogen-free
Material slider/bottom part	Polyamide, black
Material housing	Polyamide, gray
Material hood	Polyamide, gray
Number Screwdriver Pointed screws Heavy current part	1
Operating torque of pointed screws for heavy current section (Nm)	0,7 Nm
Number Screwdriver Clamping screws Heavy current part	1
Tightening torque for clamping screw (Nm)	0,7 Nm





49908 - Junction box flat cable Technofil $3x \emptyset = 10 \text{ mm}$ transparent

Product accessories



35455/6201 - Marking card 6x12mm w. print. 10 x 1-10

with 500 labels per box





49908 - Junction box flat cable Technofil $3x \emptyset = 10 \text{ mm}$ transparent

Product systems



Flat cable system Technofil 5G2.5 mm²



Maximum flexibility for complex requirements. Discover our system with a variety of junction boxes to combine consumer lines according to your individual needs.