




Product data sheet

43234/F - Shielding terminal C30 25-32mm



made of A4 stainless steel, with stainless steel screw and spring for profile rails no. 4382IN and 4383IN





Characteristics	
Eldas number	158031047
Base Unit	Piece
availability	Delivery according to agreement
EAN Code	7611718226403
group	177000
Packaging unit	100
country of origin	CH
Customs tariff number	8536.9080
Weight (g)	50 g
Technical data	
Dimensions length x width x height (mm)	40x37 mm
Material	Stainless steel
Clampable diameter (mm)	25-32 mm



Product data sheet

43234/F - Shielding terminal C30 25-32mm

Product accessories

	<b>80170/16 - Bare earthing terminal 16mm2</b> with anchoring stud for mounting rail C30
	<b>80170/50 - Bare earthing terminal 50mm2</b> with anchoring stud for mounting rail C30
	<b>4382IN/3M - Profile rail C30 stainless steel V2A 3 m</b> Profile rail C30 with 29x15x2 mm made of stainless steel V2A, with a length of 3 m.
	<b>4383IN/3M - Profile rail C30 stainless steel V2A 3 m</b> Profile rail C30 with 32x18x3 mm made of stainless steel V2A, with a length of 3 m.



## Product data sheet

43234/F - Shielding terminal C30 25-32mm

### Product systems

---



#### Shielding terminals type C30 stainless steel A4 with screw



- With screw and with stainless steel spring
  - The profile rails serve as a busbar
  - Is suitable for installations where strong vibrations and large temperature differences may occur
  - With spring to prevent independent loosening of the screw, adjust the vulnerability of the screen.
  - Remove cable jacket, expose shield
  - Handle like quick installer
  - Do not use as a cable fastener!
-