





System overview

Floor channel BOK 8880 200x60mm on leveling device




Floor channel BOK 8880 200x60mm on leveling device.

Components




52260 - Floor duct BOK 8880/200x60 SK

made of sendzimir-galvanized steel sheet 1.5mm pressed into special aluminum profile Woertz on both sides with temporary protective edge inserted into groove and impact sound trapezoidal rubber as cover support including fastening straps and connecting material height 60mm / nominal cover width 200mm length: 2000mm




52261 - Angle connection BOK 8880/200x60 SK

made of sendzimir-galvanized sheet steel 1.5mm pressed into special aluminum profile Woertz on both sides with temporary protective edge inserted into groove and impact sound trapezoidal rubber as cover support including fastening straps and connecting material height 60mm / nominal cover width 200mm



52262 - T-joint BOK 8880/200x60 SK

made of sendzimir-galvanized sheet steel 1.5mm pressed into special aluminum profile Woertz on both sides with temporary protective edge inserted into groove and impact sound trapezoidal rubber as cover support including fastening straps and connecting material height 60mm / nominal cover width 200mm length: 1000mm



52263 - Cross joint BOK 8880/200x60 SK

made of sendzimir-galvanized sheet steel 1.5mm pressed into special aluminum profile Woertz on both sides with temporary protective edge inserted into groove and impact sound trapezoidal rubber as cover support including fastening straps and connecting material height 60mm / nominal cover width 200mm length: 1000mm



52407 - Connecting link straight BOK 8880



















made of sheet steel dimension: 130x10x2.5mm with 4 pieces hexagonal screws M4x8
for connecting the channel shells





System overview





















Floor channel BOK 8880 200x60mm on leveling device

	<p>52408 - Angle connecting link 90° BOK 8880</p> <p>made of sheet steel dimension: 67.5/67.5xx10x2.5mm with 4 pcs hexagonal bolts M4x8 for connecting the channel shells</p>	
	<p>52415 - U-clamp profile reinforced 1-3mm</p> <p>as edge protection profile for sheet thickness up to 3mm</p>	
	<p>52200 - Leveling bar straight BOK 8880/200</p> <p>made of steel dimension: 330x50x5mm</p>	
	<p>52502 - Leveling plate BOK 8880/200</p> <p>made of sendzimir galvanized sheet steel dimension: 330x330x4mm to angle- cross- and T-connection</p>	
	<p>52402 - Mounting bracket 60 BOK 8880/60</p> <p>made of sheet steel 2.5mm for floor trunking BOK 8880 height 60mm</p>	
	<p>52515 - Leveling foot M10 cpl H=53mm BOK 8880</p> <p>for finished floor heights: Channel height 50mm, 70-90mm Channel height 60mm, 80-100mm Channel height 80mm, 100-140mm</p>	
	<p>52516 - Leveling foot M10 cpl H=103mm BOK 8880</p> <p>for finished floor heights: Channel height 50mm, 80-140mm Channel height 60mm, 90-150mm Channel height 80mm, 110-170mm</p>	
	<p>52517 - Leveling foot M10 cpl H=153mm BOK 8880</p> <p>for finished floor heights: Channel height 50mm, 80-190mm Channel height 60mm, 90-200mm Channel height 80mm, 110-220mm</p>	
	<p>52518 - Leveling foot M10 cpl H=203mm BOK 8880</p> <p>for finished floor heights: Channel height 50mm, 180-240mm Channel height 60mm, 190-250mm Channel height 80mm, 210-270mm</p>	



System overview













Floor channel BOK 8880 200x60mm on leveling device

	<p>52519 - Leveling foot M10 cpl H=253mm BOK 8880</p> <p>for finished floor heights: Channel height 50mm, 230-290mm Channel height 60mm, 240-300mm Channel height 80mm, 260-320mm</p>	
	<p>52264 - End wall BOK 8880/200x60 SK</p> <p>made of sendzimir-galvanized steel sheet 1.5mm pressed into special aluminum profile Woertz with temporary protective edge inserted in groove and impact sound trapezoidal rubber as cover support including connecting material height 60mm / nominal cover width 200mm</p>	
	<p>52264/0 - End wall BOK 8880/200x60 SK 0</p> <p>made of sendzimir-galvanized steel sheet 1.5mm including connecting material height 60mm / lid nominal width 206mm</p>	
	<p>52277 - Temporary wooden cover BOK8880/200</p> <p>for insertion as a placeholder and protection for the floor channel Dimension: 1000x201x12mm</p>	
	<p>52265 - St lid BOK 8880/200 SK</p> <p>made of sendzimir galvanized steel sheet 4mm dimension: 1000x200mm</p>	
	<p>52269 - St lid BOK 8880/200 SK</p> <p>made of sendzimir galvanized steel sheet 4mm dimension: 500x200mm</p>	
	<p>52266 - St lid BOK 8880/200 SK KD</p> <p>made of sendzimir-galvanized steel sheet 4mm dimension: 500x200mm cable gland loosely enclosed</p>	
	<p>52267 - St lid BOK 8880/200 SK BL</p> <p>made of sendzimir-galvanized steel sheet 4mm dimension: 500x200mm with brush strips as cable outlet, for 3mm finished floor height</p>	
	<p>52268 - St lid BOK 8880/200 SK KMn</p> <p>made of sendzimir-galvanized steel sheet 4mm dimension: 500x200mm cable tray enclosed loose</p>	
	<p>51431 - St lid BOK 8880/200 SK</p> <p>made of steel sheet 4mm dimension: 500x200mm with opening for connection attachment</p>	



System overview























Floor channel BOK 8880 200x60mm on leveling device

	52265/0 - St lid BOK 8880/200 SK 0 made of sendzimir galvanized steel sheet 4mm dimension: 1000x206mm	
	52269/0 - St lid BOK 8880/200 SK 0 made of sendzimir galvanized steel sheet 4mm dimension: 500x206mm	
	52266/0 - St lid BOK 8880/200 SK 0 KD made of sendzimir galvanized steel sheet 4mm dimension: 500x206mm with cable gland	
	52267/0 - St lid BOK 8880/200 SK 0 BL made of sendzimir-galvanized steel sheet 4mm dimension: 500x206mm with brush strips as cable outlet, for 3mm finished floor height	
	52267/0SB - St lid visible BOK 8880/200 SK 0 BL made of sendzimir galvanized sheet steel 4mm dimension: 500x206mm with brush strip as cable outlet, top flush with lid for visible lid	
	52268/0 - St lid BOK 8880/200 SK 0 KMn made of sendzimir-galvanized steel sheet 4mm dimension: 500x206mm with cable trough enclosed loose	
	52272/3 - 0 aluminium 2mm galvanised sheet steel reinforced 3mm getox. Dimensions: 1000x199x7mm Edge height in 3mm	
	52272/12 - 0 for 12mm edge, to BOK 8880/200, Length: 1000mm	
	52272/22 - 0 for 22mm edge, to BOK 8880/200, Length: 1000mm	
	52273/3 - 0 made of aluminum 2mm toxtured with galvanized steel sheet insert 3mm. Dimension: 500x199x7mm edge height inside occupiable: 3mm	
	52273/12 - 0 for 12mm edge, to BOK 8880/200, Length: 500mm	



System overview



















Floor channel BOK 8880 200x60mm on leveling device

	52273/22 - 0 for 22mm edge, to BOK 8880/200,Length: 500mm	
	52274/3 - 0 aluminium 2mm galvanised sheet steel reinforced 3 mm getextDimensions: 500x200x7mm Edge height in 3 mm Loose cable trough	
	52274/12 - 0 of aluminiumdim 500x200edge 12mm cable trough separately enclosed	
	52274/22 - 0 of aluminiumdim 500x200edge 22mm cable trough separately enclosed	
	52278/0SB - Cr lid visible BOK 8880/200 SK 0 made of chrome steel V2A 4mm, brushed dimension: 990x206mm	
	52279/0SB - Cr lid visible BOK 8880/200 SK 0 BL made of chrome steel V2A 4mm, brushed Dimensions: 490x206mm With brush strip 54x30mm as a cable outlet Top flush for visible cover	
	51880 - Cable bushing with filler piece BOK made of polycarbonate crystal clearwith transparent fillerDimension: 86x60x9.5mm	
	51049 - Adjustable cable trough BOK 8880 fDsb made of polycarbonate crystal clear for cover visible for mounting with threaded bolt	
	51069 - Cable trough levelable BOK SK 0-21mm made of polycarbonate crystal clear for cover visible for mounting with threaded bolt	
	52420 - Brush strip cpl. BOK 8880 s=6 made of plastic, black dimension: 54x35mm bristles length: 25mm	
	52410/3 - Al protective edge 3 BOK 8880 made of aluminumDimension: 2000x18x3mm	



System overview


Floor channel BOK 8880 200x60mm on leveling device

	52410/12 - Al protective edge 12 BOK 8880 made of aluminum Dimension: 2000x27x3mm	
	52410/22 - Al protective edge 22 BOK 8880 made of aluminum Dimension: 2000x37x3mm	
	52412/3 - Cr protective edge 3 BOK 8880 made of chrome steel V2A dimension: 2000x18x3mm	
	52412/12 - Cr protective edge 12 BOK 8880 made of chrome steel V2A dimension: 2000x27x3mm	
	52412/22 - Cr protective edge 22 BOK 8880 made of chrome steel V2A dimension: 2000x37x3mm	
	55028 - Adapter plate BOK 8880/200x50/60 made of sendzimir-galvanized sheet steel 1.5mm for mounting the installation kits in the floor duct including fastening material	
	52348 - Insert set empty 4-8LM vertical BOK to BOK 8880/ from 60mm height for modules type Legrand Mosaic 45x45 made of galvanized sheet steel color RAL 7032 pebble gray	
	52344 - Insert Sts 3FLF horizontal SB BOK made of galvanized sheet steel 1.5mm with knurled screw for lateral fixing in the trunking shell Dimensions: 302x47(53)x40mm Color: RAL 7032 pebble gray equipped, wired and tested: 1 pcs. blind hole terminal 7x2.5mm ² 10127 3 pcs. socket T13 FLF white 55200 1x L1 / 1x L2 / 1x L3 1 pcs. Td cable 5x1.5mm ² / 1000mm. 1 pc. FK socket SK ecobus power 5x2.5 ² Pow 5P 49701P (16A)	
	51996 - Installation kit Scs 2FLF horizontal empty BOK Low current version made of galvanized steel sheet 1.5mm with strain relief stampings and knurled screw for lateral fixing in the trunking shell. Color: RAL 7032 pebble gray	



System overview

Floor channel BOK 8880 200x60mm on leveling device



52345 - Installation kit SCS 3FLF horizontal empty BOK

Low current version made of sendzimir galvanized sheet steel 1.5mm with strain relief stampings and knurled screw for lateral fixing in the trunking shell

Dimension: 400x95x41.4mm

Color: RAL 7032 pebble gray



55039 - Installation kit socket outlet T13 3FLF horizontal SB BOK

Installation kit socket T13 3FLF horizontal SB BOK made of galvanized sheet steel 1.5mm with knurled screw for lateral fixing in the trunking shell. Dimension: 302x47(53)x40mm Color: RAL 7032 pebble gray Equipped, wired and tested: 1 pcs. blind terminal 7x2.5mm² 10127 3 pcs. socket T13 FLF white 55200 1x L1 / 1x L2 / 1x L3 1 pc. Td-cable 5x1.5mm² / 1000mm 1 pc. FK junction box technofil 49909 (10A)




55041 - Installation kit socket T23 3FLF horizontal SB BOK

Installation kit socket T23 3FLF horizontal SB BOK made of galvanized sheet steel 1.5mm with knurled screw for lateral fixing in the trunking shell. Dimension: 302x47(53)x40mm Color: RAL 7032 pebble gray Equipped, wired and tested: 1 pcs. blind terminal 7x2.5mm² 10127 3 pcs. socket T23 FLF white 55210 1x L1 / 1x L2 / 1x L3 1 pc. Td-cable 5x2.5mm² / 1000mm 1 pc. FK socket SK ecobus power 5x2.5² Pow 5P 49701P (16A)



55031 - Installation kit Sts 3FLF horizontal empty BOK

made of galvanized sheet steel 1.5mm with knurled screw for lateral fixing in the trunking shell. Dimension: 302x47(53)x40mm Color: RAL 7032 pebble gray Equipped: 1 pcs. blind hole clamp 7x2.5mm² 10127



55032 - Installation kit Sts 4FLF horizontal empty BOK

made of galvanized sheet steel 1.5mm with knurled screw for lateral fixing in the trunking shell. Dimension: 376x47(53)x40mm Color: RAL 7032 pebble gray Equipped: 1 pcs. blind hole clamp 8x2.5mm² 10146



55033 - Installation kit Sts 6FLF horizontal empty BOK

made of galvanized sheet steel 1.5mm with knurled screw for lateral fixing in the trunking shell. Dimension: 525x47(53)x40mm Color: RAL 7032 pebble gray Equipped: 1 pcs. blind hole clamp 10x2.5mm² 10128



52091 - Mounting bracket 1 FLF 3/5 empty BOK

made of galvanized sheet steel color: RAL 7032 pebble gray



51432 - Connection attachment 2x5FLF vertical BOK




Top 200x219x80 for 10 FLF sockets standing
Color: at choice





System overview

Floor channel BOK 8880 200x60mm on leveling device

	<p>52421 - Brush strip cpl. BOK 8880 s=4 visible</p> <p>made of plastic, black dimension: 54x37mm bristles length: 30mm</p>	
	<p>55019 - Installation kit bticino 2x2-3gang empty BOK</p> <p>made of galvanized sheet steel color: RAL 7032 pebble gray</p>	