



Product data sheet

33200/4GN - Screw spring terminal 4mm² green



Screw spring clip with inscription 2x4 labels

| Characteristics                           |                                 |
|---|---------------------------------|
| Eldas number                              | 158136077                       |
| Base Unit                                 | Piece                           |
| availability                              | Delivery according to agreement |
| EAN Code                                  | 7611718250354                   |
| group                                     | 165000                          |
| Packaging unit                            | 50                              |
| country of origin                         | CH                              |
| Customs tariff number                     | 8536.9080                       |
| Weight (g)                                | 11,4 g                          |
| Color                                     | green                           |
| Technical data                            |                                 |
| Dimensions length x width x height (mm)   | 68.5x6x35 mm                    |
| Dimensions length x width x height (inch) | 2.70x0.24x1.38 inch             |
| Cross section (mm²)                       | 0,5 - 4 mm²                     |
| Nominal current (A)                       | 32 A                            |



Product data sheet

33200/4GN - Screw spring terminal 4mm² green

|   |                      |
|---|----------------------|
| Rated voltage (V)                       | 800 V                |
| Connection type                         | Coil spring terminal |
| Number of connection point              | 3                    |
| Number of floor                         | 1                    |
| Number of potentials                    | 1                    |
| Clamping screw M                        | M3                   |
| Insulating material                     | PA66                 |
| Nominal Cross-section (mm²)             | 4 mm²                |
| Stripping length mm (mm)                | 12 mm                |
| Head reception room width x height (mm) | 3.7x3.6 /3.2x4.6 mm  |
| Rating data according to UL 1059        |                      |
| Rated voltage US (V)                    | 600 V                |
| Nominal cross section (AWG)             | 12 AWG               |
| Cross-section (AWG)                     | 12 - 20 AWG          |
| Stripping length (inch)                 | 0,47 inch            |



## Product data sheet

33200/4GN - Screw spring terminal 4mm<sup>2</sup> green

### Product accessories




#### Bezeichnungskarte\_6x12mm - Designation cards 6x12mm

Various designation labels 6x12mm with different embossing.



#### Bezeichnungskarte\_6x9mm - Designation card 6x9mm

Various designation plates with different embossing.



#### Bezeichnungskarte\_6x3mm - Designation card 6x3mm

Various designation plates with different embossing.

#### 33210 - Separation end wall to screw spring clamp

null



#### 3418 - Stopper DIN35 height 30mm

Makrolon locking piece



#### 30370 - Stopper DIN35 height 23mm

Locking piece made of nickel-plated brass M3 screw



#### 81506/2 - Cross-connection 2-pole to terminals DIN32/35 4mm<sup>2</sup>

Insulated cross-connection 2-pole to terminals DIN32/35 4mm<sup>2</sup> including screws M3.  
Standard version. Dimension: 11.1x20.8 mm



#### 81506/3 - Cross-connection 3-pole to terminals DIN32/35 4mm<sup>2</sup>

Insulated cross-connection 3-pole to terminals DIN32/35 4mm<sup>2</sup> including screws M3.  
Standard version. Dimension: 17.2x20.8 mm



#### 81506/4 - Cross-connection 4-pole to terminals DIN32/35 4mm<sup>2</sup>

Insulated cross-connection 4-pole to terminals DIN32/35 4mm<sup>2</sup> including screws M3.  
Standard version. Dimension: 23.3x20.8 mm



#### 81506/5 - Cross-connection 5-pole to terminals DIN32/35 4mm<sup>2</sup>

Insulated cross-connection 5-pole to terminals DIN32/35 4mm<sup>2</sup> including screws M3.  
Standard version. Dimension: 29.4x20.8 mm



#### 81506/10 - Cross-connection 10-pole to terminals DIN32/35 4mm<sup>2</sup>


Insulated cross-connections 10-pole to terminals DIN32/35 4mm<sup>2</sup> including M3 screws.  
Standard version. Dimension: 59.9x20.8 mm



## Product data sheet

33200/4GN - Screw spring terminal 4mm<sup>2</sup> green

### Product systems



#### Screw-type plug-in spring terminals DIN 35

Various screw spring terminals.

