




Floor channel BOK 8880 300x80mm on leveling device



Floor channel BOK 8880 300x80mm on leveling device.

## Components



### 52380 - Floor duct BOK 8880/300x80 SK



made of sendzimir-galvanized steel sheet 1.5mm pressed into special aluminum profile Woertz on both sides with temporary protective edge inserted into groove and impact sound trapezoidal rubber as cover support including fastening straps and connecting material height 80mm / nominal cover width 300mm length: 2000mm



### 52381 - Angle connection BOK 8880/300x80 SK



made of sendzimir-galvanized sheet steel 1.5mm pressed into special aluminum profile Woertz on both sides with temporary protective edge inserted into groove and impact sound trapezoidal rubber as cover supportincluding fastening straps and connecting material height 80mm / nominal cover width 200mm



### 52382 - T-joint BOK 8880/300x80 SK



made of sendzimir-galvanized sheet steel 1.5mm pressed into special aluminum profile Woertz on both sides with temporary protective edge inserted into groove and impact sound trapezoidal rubber as cover supportincluding fastening straps and connecting material height 80mm / nominal cover width 300mm length: 1000mm



### 52383 - Cross connection BOK 8880/300x80 SK



made of sendzimir-galvanized sheet steel 1.5mm pressed into special aluminum profile Woertz on both sides with temporary protective edge inserted into groove and impact sound trapezoidal rubber as cover supportincluding fastening straps and connecting material height 80mm / nominal cover width 300mm length: 1000mm



### 52407 - Connecting link straight BOK 8880



made of sheet steel dimension: 130x10x2.5mm with 4 pieces hexagonal screws M4x8

for connecting the channel shells







	52408 - Angle connecting link 90° BOK 8880  made of sheet steel dimension: 67.5/67.5xx10x2.5mm with 4 pcs hexagonal bolts M4x8 for connecting the channel shells	
	52415 - U-clamp profile reinforced 1-3mm as edge protection profile for sheet thickness up to 3mm	
	52300 - Leveling bar straight BOK 8880/300 made of steel dimension: 430x50x5mm	
	52503 - Leveling plate BOK 8880/300  made of sendzimir galvanized sheet steel dimension: 430x430x4mm to angle- cross- and T-connection	
	52403 - Mounting bracket 80 BOK 8880/80 made of sheet steel 2.5mm for floor trunking BOK 8880 height 80mm	
	52515 - Leveling foot M10 cpl H=53mm BOK 8880  for finished floor heights: Channel height 50mm, 70-90mm Channel height 60mm, 80-100mm Channel height 80mm, 100-140mm	
	52516 - Leveling foot M10 cpl H=103mm BOK 8880  for finished floor heights: Channel height 50mm, 80-140mm Channel height 60mm, 90-150mm Channel height 80mm, 110-170mm	
<u></u>	52517 - Leveling foot M10 cpl H=153mm BOK 8880  for finished floor heights: Channel height 50mm, 80-190mm Channel height 60mm, 90-200mm Channel height 80mm, 110-220mm	
<b>‡</b>	52518 - Leveling foot M10 cpl H=203mm BOK 8880  for finished floor heights: Channel height 50mm, 180-240mm Channel height 60mm, 190-250mm Channel height 80mm, 210-270mm	





<b>†</b>	52519 - Leveling foot M10 cpl H=253mm BOK 8880	
	for finished floor heights: Channel height 50mm, 230-290mm	
	Channel height 60mm, 240-300mm	
	Channel height 80mm, 260-320mm	
	52384 - End wall BOK 8880/300x80 SK	回答: 24年 第4日 第4日 第4日 第4日 第4日 第4日 第4日 第4日 第4日 第4日
	made of sendzimir-galvanized steel sheet 1.5mm pressed into special aluminum	
	profile Woertz with temporary protective edge inserted in groove and impact	回数名器数据证
	sound trapezoidal rubber as cover supportincluding connecting material height 80mm / cover nominal width 300mm	
	Committee Width Socialin	ENDANCATION
	52384/0 - End wall BOK 8880/300x80 SK 0	
	made of sendzimir-galvanized steel sheet 1.5mm including connecting material	
	height 80mm / lid nominal width 306mm	Election.764
	52377 - Temporary wooden cover BOK 8880/300	
	for insertion as a placeholder and protection for the floor channel Dimension:	
	1000x301x12mm	回製炭製物線は
	52365 - St lid BOK 8880/300 SK	
	made of sendzimir galvanized steel sheet 4mm dimension: 1000x300mm	
	52369 - St lid BOK 8880/300 SK	
	made of sendzimir galvanized steel sheet 4mm dimension: 500x300mm	
	52366 - St lid BOK 8880/300 SK KD	
	made of sendzimir-galvanized steel sheet 4mm dimension: 500x300mm cable	
_	gland loosely enclosed	国际经验实验性
	52367 - St lid BOK 8880/300 SK BL	
	made of sendzimir-galvanized steel sheet 4mm dimension: 500x300mm with	
	brush strips as cable outlet, for 3mm finished floor height	<b>国的杂项流淌</b>
	52368 - St lid BOK 8880/300 SK KMn	
	made of sendzimir-galvanized steel sheet 4mm dimension: 500x300mm cable	
	tray enclosed loose	回行与经验的特
	52365/0 - St lid BOK 8880/300 SK 0	
	made of sendzimir galvanized steel sheet 4mm dimension: 1000x306mm	





52369/0 - St lid BOK 8880/300 SK 0 made of sendzimir galvanized steel sheet 4mm dimension 500x306mm	
52366/0 - St lid BOK 8880/300 SK 0 KD made of sendzimir galvanized steel sheet 4mm dimension: 500x306mm with cable gland	
52367/0 - St lid BOK 8880/300 SK 0 BL made of sendzimir-galvanized steel sheet 4mm dimension: 500x306mm with brush strips as cable outlet, for 3mm finished floor height	
52367/0SB - St lid visible BOK 8880/300 SK 0 BL made of sendzimir galvanized sheet steel 4mm dimension:500x306mm with brush strip as cable outlet, top flush with lid for visible lid	
52368/0 - St lid BOK 8880/300 SK 0 KMn made of sendzimir-galvanized steel sheet 4mm dimension: 500x306mm with cable trough enclosed loose	
<b>52372/3 - 0</b> for 3mm edge, to BOK 8880/300,Length: 1000mm	
<b>52372/12 - 0</b> for 12mm edge, to BOK 8880/300,Length: 1000mm	
<b>52372/22 - 0</b> for 22mm edge, to BOK 8880/300,Length: 1000mm	
<b>52373/3 - 0</b> for 3mm edge, to BOK 8880/300,Length: 500mm	
<b>52373/12 - 0</b> for 12mm edge, to BOK 8880/300,Length: 500mm	
<b>52373/22 - 0</b> for 22mm edge, to BOK 8880/300,Length: 500mm	





	<b>52374/3 - 0</b> of aluminiumdim 500x300edge 3mm cable trough separately enclosed	
$\wedge$	52374/12 - 0	
	of aluminiumdim 500x300edge 12mm cable trough separately enclosed	
	52374/22 - 0	
	of aluminiumdim 500x300edge 22mm cable trough separately enclosed	
	52378/0SB - Cr lid visible BOK 8880/300 SK 0	
	made of chrome steel V2A 4mm, brushed dimension: 990x306mm	
	52379/0SB - Cr lid visible BOK 8880/300 SK 0	
	made of chrome steel V2A 4mm, brushed Dimensions: 490x306mm With brush strip 54x30mm as a cable outlet top flush for visible cover	
	51880 - Cable bushing with filler piece BOK	
	made of polycarbonate crystal clearwith transparent fillerDimension: 86x60x9.5mm	
	51049 - Adjustable cable trough BOK 8880 fDsb	
	made of polycarbonate crystal clear for cover visible for mounting with threaded bolt	
•	51069 - Cable trough levelable BOK SK 0-21mm	
	made of polycarbonate crystal clear for cover visible for mounting with threaded bolt	
-	52420 - Brush strip cpl. BOK 8880 s=6	国大大学。 第二章
	made of plastic, black dimension: 54x35mm bristles length: 25mm	
9 9 8	52410/3 - Al protective edge 3 BOK 8880	国第58年2月日 月末日30日 日本 日本日本日本
	made of aluminumDimension: 2000x18x3mm	
1 0 N	52410/12 - Al protective edge 12 BOK 8880	
	made of aluminumDimension: 2000x27x3mm	





Floor channel BOK 8880 300x80mm on leveling device

1 0 8 8	52410/22 - Al protective edge 22 BOK 8880	回
	made of aluminumDimension: 2000x37x3mm	
-t_	52412/3 - Cr protective edge 3 BOK 8880	
8	made of chrome steel V2Adimension: 2000x18x3mm	
3-	52412/12 - Cr protective edge 12 BOK 8880	
8	made of chrome steel V2Adimension: 2000x27x3mm	
.a	52412/22 - Cr protective edge 22 BOK 8880	
\$ * 8	made of chrome steel V2Adimension: 2000x37x3mm	
	52348 - Insert set empty 4-8LM vertical BOK	
(1 mm/3 co)	to BOK 8880/ from 60mm height for modules type Legrand Mosaic 45x45 made of galvanized sheet steel color RAL 7032 pebble gray	
	52344 - Insert Sts 3FLF horizontal SB BOK	
( 10 of the	made of galvanized sheet steel 1.5mm with knurled screw for lateral fixing in the trunking shell Dimensions: 302x47(53)x40mm Color: RAL 7032 pebble gray	
	equipped, wired and tested: 1 pcs. blind hole terminal 7x2.5mm <sup>2</sup> 10127 3 pcs. socket T13 FLF white 55200 1x L1 / 1x L2 / 1x L3 1 pcs. Td cable	
	5x1.5mm <sup>2</sup> / 1000mm. 1 pc. FK socket SK ecobus power 5x2.5 <sup>2</sup> Pow 5P 49701P (16A)	
	55026 - Installation kit 2FLF 6/5 empty BOK 8880/x80	
	made of galvanized steel sheet 1.5mm with knurled screw for lateral fixing in the channel shell. Color: RAL 7032 pebble gray	
	51996 - Installation kit Scs 2FLF horizontal empty BOK	
	Low current versionmade of galvanized steel sheet 1.5mm with strain relief stampings and knurled screw for lateral fixing in the trunking shell. Color: RAL 7032 pebble gray	
	52345 - Installation kit Scs 3FLF horizontal empty BOK	
	Low current version made of sendzimir galvanized sheet steel 1.5mm with strain relief stampings and knurled screw for lateral fixing in the trunking	

shell

Dimension: 400x95x41.4mm Color: RAL 7032 pebble gray





Floor channel BOK 8880 300x80mm on leveling device



### 55039 - Installation kit socket outlet T13 3FLF horizontal SB BOK

Installation kit socket T13 3FLF horizontal SB BOK made of galvanized sheet steel 1.5mm with knurled screw for lateral fixing in the trunking shell. Dimension: 302x47(53)x40mm Color: RAL 7032 pebble gray Equipped, wired and tested: 1 pcs. blind terminal 7x2.5mm <sup>2</sup> 10127 3 pcs. socket T13 FLF white 55200 1x L1 / 1x L2 / 1x L3 1 pc. Td-cable 5x1.5mm <sup>2</sup> / 1000mm 1 pc. FK junction box technofil 49909 (10A)





### 55041 - Installation kit socket T23 3FLF horizontal SB BOK

Installation kit socket T23 3FLF horizontal SB BOK made of galvanized sheet steel 1.5mm with knurled screw for lateral fixing in the trunking shell. Dimension: 302x47(53)x40mm Color: RAL 7032 pebble gray Equipped, wired and tested: 1 pcs. blind terminal 7x2.5mm <sup>2</sup> 10127 3 pcs. socket T23 FLF white 55210 1x L1 / 1x L2 / 1x L3 1 pc. Td-cable 5x2.5mm <sup>2</sup> / 1000mm 1 pc. FK socket SK ecobus power 5x2.5<sup>2</sup> Pow 5P 49701P (16A)





### 55031 - Installation kit Sts 3FLF horizontal empty BOK

made of galvanized sheet steel 1.5mm with knurled screw for lateral fixing in the trunking shell. Dimension: 302x47(53)x40mm Color: RAL 7032 pebble gray Equipped: 1 pcs. blind hole clamp 7x2.5mm <sup>2</sup> 10127





## 55032 - Installation kit Sts 4FLF horizontal empty BOK

made of galvanized sheet steel 1.5mm with knurled screw for lateral fixing in the trunking shell. Dimension: 376x47(53)x40mm Color: RAL 7032 pebble gray Equipped: 1 pcs. blind hole clamp 8x2.5mm <sup>2</sup> 10146





### 55033 - Installation kit Sts 6FLF horizontal empty BOK

made of galvanized sheet steel 1.5mm with knurled screw for lateral fixing in the trunking shell. Dimension: 525x47(53)x40mm Color: RAL 7032 pebble gray Equipped: 1 pcs. blind hole clamp 10x2.5mm <sup>2</sup> 10128





### 52091 - Mounting bracket 1 FLF 3/5 empty BOK

made of galvanized sheet steel color: RAL 7032 pebble gray





### 52421 - Brush strip cpl. BOK 8880 s=4 visible

made of plastic, black dimension: 54x37mm bristles length: 30mm





### 55019 - Installation kit bticino 2x2-3gang empty BOK

made of galvanized sheet steel color: RAL 7032 pebble gray

