



Plug connections code 3 for mains voltage, 3-pole (LNPE)



3 pole connectors code 3 for mains voltage.

Components

 49343/1F/C3 - Pre-wired connection C3-F 3G1.5 1m HF Pre-wired connector, socket 3-poles code 3 with 1 m cable 3G1.5 mm ² with free end, conductor compressed, 16 A, 250 V, halogen free, behaviour to fire classification Cca	
49343/1F25/C3 - Pre-wired connection C3-F 3G2.5 1m HF Pre-wired connector, socket 3-poles code 3 with 1 m cable 3G2.5 mm ² with free end, conductor compressed, 20 A, 250 V, halogen free, behaviour to fire classification Cca	
49343/1M/C3 - Pre-wired connection C3-M 3G1.5 1m HF Pre-wired connector, plug 3-poles code 3 with 1 m cable 3G1.5 mm ² with free end, conductor compressed, 16 A, 250 V, halogen free, behaviour to fire classification Cca	
 49343/1M25/C3 - Pre-wired connection C3-M 3G2.5 1m HF Pre-wired connector, plug 3-poles code 3 with 1 m cable 3G2.5 mm ² with free end, conductor compressed, 20 A, 250 V, halogen free, behaviour to fire classification Cca	
49343/1MF/C3 - Pre-wired connection C3-M+F 3G1.5 1m HF Pre-wired connector, plug and socket 3-poles code 3 with 1 m cable 3G1.5 mm ², 16 A, 250 V, halogen free, behaviour to fire classification Cca	
49343/1MF25/C3 - Pre-wired connection C3-M+F 3G2.5 1m HF Pre-wired connector, plug and socket 3-poles code 3 with 1 m cable 3G2.5 mm ² , 20 A, 250 V, halogen free, behaviour to fire classification Cca	





— 4	49343/2F/C3 - Pre-wired connection C3-F 3G1.5 2m HF	
	Pre-wired connector, socket 3-poles code 3 with 2 m cable 3G1.5 mm ² with free end, conductor compressed, 16 A, 250 V, halogen free, behaviour to fire classification Cca	
	49343/2F25/C3 - Pre-wired connection C3-F 3G2.5 2m HF	
	Pre-wired connector, socket 3-poles code 3 with 2 m cable 3G2.5 mm ² with free end, conductor compressed, 20 A, 250 V, halogen free, behaviour to fire classification Cca	
	49343/2M/C3 - Pre-wired connection C3-M 3G1.5 2m HF	
	Pre-wired connector, plug 3-poles code 3 with 2 m cable 3G1.5 mm ² with free end, conductor compressed, 16 A, 250 V, halogen free, behaviour to fire classification Cca	
	49343/2M25/C3 - Pre-wired connection C3-M 3G2.5 2m HF	
	Pre-wired connector, plug 3-poles code 3 with 2 m cable 3G2.5 mm ² with free end, conductor compressed, 20 A, 250 V, halogen free, behaviour to fire classification Cca	
	49343/2MF/C3 - Pre-wired connection C3-M+F 3G1.5 2m HF	
	Pre-wired connector, plug and socket 3-poles code 3 with 2 m cable 3G1.5 mm ² , 16 A, 250 V, halogen free, behaviour to fire classification Cca	
	49343/2MF25/C3 - Pre-wired connection C3-M+F 3G2.5 2m HF	
	Pre-wired connector, plug and socket 3-poles code 3 with 2 m cable 3G2.5 mm ² , 20 A, 250 V, halogen free, behaviour to fire classification Cca	
	49343/3F/C3 - Pre-wired connection C3-F 3G1.5 3m HF	
—	Pre-wired connector, socket 3-poles code 3 with 3 m cable 3G1.5 mm ² with free end, conductor compressed, 16 A, 250 V, halogen free, behaviour to fire classification Cca	
	49343/3F25/C3 - Pre-wired connection C3-F 3G2.5 3m HF	
	Pre-wired connector, socket 3-poles code 3 with 3 m cable 3G2.5 mm ² with free end, conductor compressed, 20 A, 250 V, halogen free, behaviour to fire classification Cca	
	49343/3M/C3 - Pre-wired connection C3-M 3G1.5 3m HF	
	Pre-wired connector, plug 3-poles code 3 with 3 m cable 3G1.5 mm ² with free end, conductor compressed, 16 A, 250 V, halogen free, behaviour to fire classification Cca	





	49343/3M25/C3 - Pre-wired connection C3-M 3G2.5 3m HF	回逐渐高级。 更到45次分享等 200次次次第五
	Pre-wired connector, plug 3-poles code 3 with 3 m cable 3G2.5 mm ² with free end, conductor compressed, 20 A, 250 V, halogen free, behaviour to fire classification Cca	
	49343/3MF/C3 - Pre-wired connection C3-M+F 3G1.5 3m HF	
	Pre-wired connector, plug and socket 3-poles code 3 with 3 m cable 3G1.5 mm ² , 16 A, 250 V, halogen free, behaviour to fire classification Cca	
	49343/3MF25/C3 - Pre-wired connection C3-M+F 3G2.5 3m HF	
	Pre-wired connector, plug and socket 3-poles code 3 with 3 m cable 3G2.5 mm ² , 20 A, 250 V, halogen free, behaviour to fire classification Cca	
	49343/4F/C3 - Pre-wired connection C3-F 3G1.5 4m HF	
	Pre-wired connector, socket 3-poles code 3 with 4 m cable 3G1.5 mm ² with free end, conductor compressed, 16 A, 250 V, halogen free, behaviour to fire classification Cca	
	49343/4F25/C3 - Pre-wired connection C3-F 3G2.5 4m HF	
	Pre-wired connector, socket 3-poles code 3 with 4 m cable 3G2.5 mm ² with free end, conductor compressed, 20 A, 250 V, halogen free, behaviour to fire classification Cca	
	49343/4M/C3 - Pre-wired connection C3-M 3G1.5 4m HF	国家次路域3月 東西科技工程3年 東西科技工程3年
	Pre-wired connector, plug 3-poles code 3 with 4 m cable 3G1.5 mm ² with free end, conductor compressed, 16 A, 250 V, halogen free, behaviour to fire classification Cca	
	49343/4M25/C3 - Pre-wired connection C3-M 3G2.5 4m HF	
	Pre-wired connector, plug 3-poles code 3 with 4 m cable 3G2.5 mm ² with free end, conductor compressed, 20 A, 250 V, halogen free, behaviour to fire classification Cca	
	49343/4MF/C3 - Pre-wired connection C3-M+F 3G1.5 4m HF	国际编码。24国 第2国际公司第3 第2国际公司第3
	Pre-wired connector, plug and socket 3-poles code 3 with 4 m cable 3G1.5 mm ² , 16 A, 250 V, halogen free, behaviour to fire classification Cca	
	49343/4MF25/C3 - Pre-wired connection C3-M+F 3G2.5 4m HF	
	Pre-wired connector, plug and socket 3-poles code 3 with 4 m cable 3G2.5 mm ² , 20 A, 250 V, halogen free, behaviour to fire classification Cca	





	49343/5F/C3 - Pre-wired connection C3-F 3G1.5 5m HF	
	Pre-wired connector, socket 3-poles code 3 with 5 m cable 3G1.5 mm ² with free end, conductor compressed, 16 A, 250 V, halogen free, behaviour to fire classification Cca	
	49343/5F25/C3 - Pre-wired connection C3-F 3G2.5 5m HF	
	Pre-wired connector, socket 3-poles code 3 with 5 m cable 3G2.5 mm ² with free end, conductor compressed, 20 A, 250 V, halogen free, behaviour to fire classification Cca	
	49343/5M/C3 - Pre-wired connection C3-M 3G1.5 5m HF	
	Pre-wired connector, plug 3-poles code 3 with 5 m cable 3G1.5 mm ² with free end, conductor compressed, 16 A, 250 V, halogen free, behaviour to fire classification Cca	
	49343/5M25/C3 - Pre-wired connection C3-M 3G2.5 5m HF	
	Pre-wired connector, plug 3-poles code 3 with 5 m cable 3G2.5 mm ² with free end, conductor compressed, 20 A, 250 V, halogen free, behaviour to fire classification Cca	
	49343/5MF/C3 - Pre-wired connection C3-M+F 3G1.5 5m HF	
	Pre-wired connector, plug and socket 3-poles code 3 with 5 m cable 3G1.5 mm ² , 16 A, 250 V, halogen free, behaviour to fire classification Cca	
	49343/5MF25/C3 - Pre-wired connection C3-M+F 3G2.5 5m HF	
	Pre-wired connector, plug and socket 3-poles code 3 with 5 m cable 3G2.5 mm ² , 20 A, 250 V, halogen free, behaviour to fire classification Cca	
	49343/6F/C3 - Pre-wired connection C3-F 3G1.5 6m HF	
—	Pre-wired connector, socket 3-poles code 3 with 6 m cable 3G1.5 mm ² with free end, conductor compressed, 16 A, 250 V, halogen free, behaviour to fire classification Cca	
	49343/6F25/C3 - Pre-wired connection C3-F 3G2.5 6m HF	
	Pre-wired connector, socket 3-poles code 3 with 6 m cable 3G2.5 mm ² with free end, conductor compressed, 20 A, 250 V, halogen free, behaviour to fire classification Cca	
	49343/6M/C3 - Pre-wired connection C3-M 3G1.5 6m HF	
	Pre-wired connector, plug 3-poles code 3 with 6 m cable 3G1.5 mm ² with free end, conductor compressed, 16 A, 250 V, halogen free, behaviour to fire classification Cca	





	49343/6M25/C3 - Pre-wired connection C3-M 3G2.5 6m HF	
	Pre-wired connector, plug 3-poles code 3 with 6 m cable 3G2.5 mm ² with free end, conductor compressed, 20 A, 250 V, halogen free, behaviour to fire classification Cca	
	49343/6MF/C3 - Pre-wired connection C3-M+F 3G1.5 6m HF	
	Pre-wired connector, plug and socket 3-poles code 3 with 6 m cable 3G1.5 mm ² , 16 A, 250 V, halogen free, behaviour to fire classification Cca	
	49343/6MF25/C3 - Pre-wired connection C3-M+F 3G2.5 6m HF	
	Pre-wired connector, plug and socket 3-poles code 3 with 6 m cable 3G2.5 mm ² , 20 A, 250 V, halogen free, behaviour to fire classification Cca	
	49343/8F/C3 - Pre-wired connection C3-F 3G1.5 8m HF	
— —	Pre-wired connector, socket 3-poles code 3 with 8 m cable 3G1.5 mm ² with free end, conductor compressed, 16 A, 250 V, halogen free, behaviour to fire classification Cca	
	49343/8F25/C3 - Pre-wired connection C3-F 3G2.5 8m HF	
	Pre-wired connector, socket 3-poles code 3 with 8 m cable 3G2.5 mm ² with free end, conductor compressed, 20 A, 250 V, halogen free, behaviour to fire classification Cca	
	49343/8M25/C3 - Pre-wired connection C3-M 3G2.5 8m HF	
	Pre-wired connector, plug 3-poles code 3 with 8 m cable 3G2.5 mm ² with free end, conductor compressed, 20 A, 250 V, halogen free, behaviour to fire classification Cca	
	49343/8MF/C3 - Pre-wired connection C3-M+F 3G1.5 8m HF	
	Pre-wired connector, plug and socket 3-poles code 3 with 8 m cable 3G1.5 mm ² , 16 A, 250 V, halogen free, behaviour to fire classification Cca	
	49343/8MF25/C3 - Pre-wired connection C3-M+F 3G2.5 8m HF	
	Pre-wired connector, plug and socket 3-poles code 3 with 8 m cable 3G2.5 mm ² , 20 A, 250 V, halogen free, behaviour to fire classification Cca	
	49343/10F/C3 - Pre-wired connection C3-F 3G1.5 10m HF	
	Pre-wired connector, socket 3-poles code 3 with 10 m cable 3G1.5 mm ² with free end, conductor compressed, 16 A, 250 V, halogen free, behaviour to fire classification Cca	





49343/10F25/C3 - Pre-wired connection C3-F 3G2.5 10m HF Pre-wired connector, socket 3-poles code 3 with 10 m cable 3G2.5 mm ² with free end, conductor compressed, 20 A, 250 V, halogen free, behaviour to fire classification Cca	
 49343/10M/C3 - Pre-wired connection C3-M 3G1.5 10m HF Pre-wired connector, plug 3-poles code 3 with 10 m cable 3G1.5 mm ² with free end, conductor compressed, 16 A, 250 V, halogen free, behaviour to fire classification Cca	
 49343/10M25/C3 - Pre-wired connection C3-M 3G2.5 10m HF Pre-wired connector, plug 3-poles code 3 with 10 m cable 3G2.5 mm ² with free end, conductor compressed, 20 A, 250 V, halogen free, behaviour to fire classification Cca	
49343/10MF/C3 - Pre-wired connection C3-M+F 3G1.5 10m HF Pre-wired connector, plug and socket 3-poles code 3 with 10 m cable 3G1.5 mm 2, 16 A, 250 V, halogen free, behaviour to fire classification Cca	
49343/10MF25/C3 - Pre-wired connection C3-M+F 3G2.5 10m HF Pre-wired connector, plug and socket 3-poles code 3 with 10 m cable 3G2.5 mm 2, 20 A, 250 V, halogen free, behaviour to fire classification Cca	
3954 - Holder f. marking cable with 5 holders Cable label holder for 4 digits each, for cable 3x1.5mm2	
49750 - Locking to connectors For mechanical connection of socket to plug 3 and 5 poles	
49803 - Sealing element IP68 for 3-poles plug connection to extend the degree of protection to IP68 (waterproof) for all 3-pole connectors	