



Floor channel BOK 8880 300x80mm integrated leveling device



Floor channel BOK 8880 300x80mm with integrated leveling device.

Components



52345 - Installation kit Scs 3FLF horizontal empty BOK

Low current version made of sendzimir galvanized sheet steel 1.5mm with strain relief stampings and knurled screw for lateral fixing in the trunking shell

Dimension: 400x95x41.4mm Color: RAL 7032 pebble gray





55032 - Installation kit Sts 4FLF horizontal empty BOK

made of galvanized sheet steel 1.5mm with knurled screw for lateral fixing in the trunking shell. Dimension: 376x47(53)x40mm Color: RAL 7032 pebble gray Equipped: 1 pcs. blind hole clamp 8x2.5mm ² 10146





52381N - Angle connection BOK 8880/300x80 iN

with integrated levelingmade of sendzimir-galvanized sheet steel 1.5mmpressed into special aluminum profile Woertz on both sides with temporary protective edge inserted into groove and impact sound trapezoidal rubber as cover supportleveling hexagonal bolts M10x60 polyamideincluding connecting materialheight 80mm / nominal cover width 300mm





52382N - T-joint BOK 8880/300x80 iN

with integrated levelingmade of sendzimir-galvanized sheet steel 1.5mmpressed into special aluminum profile Woertz on both sides with temporary protective edge inserted into groove and impact sound trapezoidal rubber as cover supportleveling hexagonal bolts M10x60 polyamideincluding connecting materialheight 80mm / nominal cover width 300mm length: 1000mm





52383N - Cross connection BOK 8880/300x80 iN

with integrated levelingmade of sendzimir-galvanized sheet steel 1.5mmpressed into special aluminum profile Woertz on both sides with temporary protective edge inserted into groove and impact sound trapezoidal rubber as cover supportleveling hexagonal bolts M10x60 polyamideincluding connecting materialheight 80mm / nominal cover width 300mm length: 1000mm







	52384 - End wall BOK 8880/300x80 SK	
	made of sendzimir-galvanized steel sheet 1.5mm pressed into special aluminum profile Woertz with temporary protective edge inserted in groove and impact sound trapezoidal rubber as cover supportincluding connecting material height 80mm / cover nominal width 300mm	
~	52384/0 - End wall BOK 8880/300x80 SK 0	
	made of sendzimir-galvanized steel sheet 1.5mm including connecting material height 80mm / lid nominal width 306mm	
Ť	52410/22 - Al protective edge 22 BOK 8880	
26.	made of aluminumDimension: 2000x37x3mm	
-3	52410/3 - Al protective edge 3 BOK 8880	国家公路·思华国 理事(1972年) 2008 1983年(1984年) 3
98 72 72	made of aluminumDimension: 2000x18x3mm	
3	52410/12 - Al protective edge 12 BOK 8880	
22	made of aluminumDimension: 2000x27x3mm	
	52380N - Floor duct BOK 8880/300x80 iN	
	with integrated leveling made of sendzimir galvanized steel sheet 1.5mm pressed into special aluminum profile Woertz on both sides with temporary protective edge inserted into groove and impact sound trapezoidal rubber as cover support leveling hexagonal bolts M10x60 polyamide including connecting material height 80mm / nominal cover width 300mm length: 2000mm	
	52377 - Temporary wooden cover BOK 8880/300	
	for insertion as a placeholder and protection for the floor channel Dimension: 1000x301x12mm	
	52366 - St lid BOK 8880/300 SK KD	
	made of sendzimir-galvanized steel sheet 4mm dimension: 500x300mm cable gland loosely enclosed	
	52368 - St lid BOK 8880/300 SK KMn	回表表情。 第2日本2年 2年日本2年 2年 2年 2年 2年 2年 2年 2年 2年 2年 2年 2年 2年 2
	made of sendzimir-galvanized steel sheet 4mm dimension: 500x300mm cable tray enclosed loose	
	52372/3 - 0	
	for 3mm edge, to BOK 8880/300,Length: 1000mm	





	52369 - St lid BOK 8880/300 SK made of sendzimir galvanized steel sheet 4mm dimension: 500x300mm	
	52373/3 - 0 for 3mm edge, to BOK 8880/300,Length: 500mm	
	52372/22 - 0 for 22mm edge, to BOK 8880/300,Length: 1000mm	
	52374/3 - 0 of aluminiumdim 500x300edge 3mm cable trough separately enclosed	
	52373/12 - 0 for 12mm edge, to BOK 8880/300,Length: 500mm	
	52373/22 - 0 for 22mm edge, to BOK 8880/300,Length: 500mm	
	52374/12 - 0 of aluminiumdim 500x300edge 12mm cable trough separately enclosed	
	52374/22 - 0 of aluminiumdim 500x300edge 22mm cable trough separately enclosed	
	52372/12 - 0 for 12mm edge, to BOK 8880/300,Length: 1000mm	
2 12: 26: 36:	52412/3 - Cr protective edge 3 BOK 8880 made of chrome steel V2Adimension: 2000x18x3mm	
2 22 36	52412/12 - Cr protective edge 12 BOK 8880 made of chrome steel V2Adimension: 2000x27x3mm	
2 12: 26: 36:	52412/22 - Cr protective edge 22 BOK 8880 made of chrome steel V2Adimension: 2000x37x3mm	





	52367 - St lid BOK 8880/300 SK BL made of sendzimir-galvanized steel sheet 4mm dimension: 500x300mm with brush strips as cable outlet, for 3mm finished floor height	
	52365 - St lid BOK 8880/300 SK made of sendzimir galvanized steel sheet 4mm dimension: 1000x300mm	
	55026 - Installation kit 2FLF 6/5 empty BOK 8880/x80 made of galvanized steel sheet 1.5mm with knurled screw for lateral fixing in the channel shell. Color: RAL 7032 pebble gray	
	52304 - End piece to leveling bar BOK8880/300 Dimensions 260x50x4mm Leveling bar additionally used in caseof non-existent brace	
\$	52091 - Mounting bracket 1 FLF 3/5 empty BOK made of galvanized sheet steel color: RAL 7032 pebble gray	
(12 m) 3 m	52348 - Insert set empty 4-8LM vertical BOK to BOK 8880/ from 60mm height for modules type Legrand Mosaic 45x45 made of galvanized sheet steel color RAL 7032 pebble gray	
	52365/0 - St lid BOK 8880/300 SK 0 made of sendzimir galvanized steel sheet 4mm dimension: 1000x306mm	
	51996 - Installation kit Scs 2FLF horizontal empty BOK Low current versionmade of galvanized steel sheet 1.5mm with strain relief stampings and knurled screw for lateral fixing in the trunking shell. Color: RAL 7032 pebble gray	
1000	55041 - Installation kit socket T23 3FLF horizontal SB BOK Installation kit socket T23 3FLF horizontal SB BOK made of galvanized sheet steel 1.5mm with knurled screw for lateral fixing in the trunking shell. Dimension: 302x47(53)x40mm Color: RAL 7032 pebble gray Equipped, wired and tested: 1 pcs. blind terminal 7x2.5mm ² 10127 3 pcs. socket T23 FLF white 55210 1x L1 / 1x L2 / 1x L3 1 pc. Td-cable 5x2.5mm ² / 1000mm 1 pc. FK socket SK ecobus power 5x2.5² Pow 5P 49701P (16A)	





Floor channel BOK 8880 300x80mm integrated leveling device

	55039 - Installation kit socket outlet T13 3FLF horizontal SB BOK	
	Installation kit socket T13 3FLF horizontal SB BOK made of galvanized sheet steel 1.5mm with knurled screw for lateral fixing in the trunking shell. Dimension: 302x47(53)x40mm Color: RAL 7032 pebble gray Equipped, wired and tested: 1 pcs. blind terminal 7x2.5mm ² 10127 3 pcs. socket T13 FLF white 55200 1x L1 / 1x L2 / 1x L3 1 pc. Td-cable 5x1.5mm ² / 1000mm 1 pc. FK junction box technofil 49909 (10A)	
	51880 - Cable bushing with filler piece BOK	
	made of polycarbonate crystal clearwith transparent fillerDimension: 86x60x9.5mm	
	52367/0 - St lid BOK 8880/300 SK 0 BL	
	made of sendzimir-galvanized steel sheet 4mm dimension: 500x306mm with brush strips as cable outlet, for 3mm finished floor height	
	52368/0 - St lid BOK 8880/300 SK 0 KMn	
The state of the s	made of sendzimir-galvanized steel sheet 4mm dimension: 500x306mm with cable trough enclosed loose	
	52367/0SB - St lid visible BOK 8880/300 SK 0 BL	
	made of sendzimir galvanized sheet steel 4mm dimension:500x306mm with brush strip as cable outlet, top flush with lid for visible lid	
	52366/0 - St lid BOK 8880/300 SK 0 KD	(1) 2 2 2 4 (1) (1) (1) (1) (1) (1) (1) (1) (1) (1)
3	made of sendzimir galvanized steel sheet 4mm dimension: 500x306mm with cable gland	
	52378/0SB - Cr lid visible BOK 8880/300 SK 0	
	made of chrome steel V2A 4mm, brushed dimension: 990x306mm	
	52379/0SB - Cr lid visible BOK 8880/300 SK 0	
	made of chrome steel V2A 4mm, brushed Dimensions: 490x306mm With brush strip 54x30mm as a cable outlet top flush for visible cover	
	55019 - Installation kit bticino 2x2-3gang empty BOK	
A LIMIT SEN	made of galvanized sheet steel color: RAL 7032 pebble gray	
	52403 - Mounting bracket 80 BOK 8880/80	
	1 (1) 1 1 1 DOL(00001 11:00	

made of sheet steel 2.5mm for floor trunking BOK 8880 height 80mm





	55031 - Installation kit Sts 3FLF horizontal empty BOK	
	made of galvanized sheet steel 1.5mm with knurled screw for lateral fixing in the trunking shell. Dimension: 302x47(53)x40mm Color: RAL 7032 pebble gray Equipped: 1 pcs. blind hole clamp 7x2.5mm ² 10127	
	52344 - Insert Sts 3FLF horizontal SB BOK	
	made of galvanized sheet steel 1.5mm with knurled screw for lateral fixing in the trunking shell Dimensions: 302x47(53)x40mm Color: RAL 7032 pebble gray equipped, wired and tested: 1 pcs. blind hole terminal 7x2.5mm² 10127 3 pcs. socket T13 FLF white 55200 1x L1 / 1x L2 / 1x L3 1 pcs. Td cable 5x1.5mm² / 1000mm. 1 pc. FK socket SK ecobus power 5x2.5² Pow 5P 49701P (16A)	
	55033 - Installation kit Sts 6FLF horizontal empty BOK	
	made of galvanized sheet steel 1.5mm with knurled screw for lateral fixing in the trunking shell. Dimension: 525x47(53)x40mm Color: RAL 7032 pebble gray Equipped: 1 pcs. blind hole clamp 10x2.5mm ² 10128	
	51049 - Adjustable cable trough BOK 8880 fDsb	
	made of polycarbonate crystal clear for cover visible for mounting with threaded bolt	
	51069 - Cable trough levelable BOK SK 0-21mm	
	made of polycarbonate crystal clear for cover visible for mounting with threaded bolt	
A	52407 - Connecting link straight BOK 8880	
	made of sheet steel dimension: 130x10x2.5mm with 4 pieces hexagonal screws M4x8	
	for connecting the channel shells	
	52415 - U-clamp profile reinforced 1-3mm	
	as edge protection profile for sheet thickness up to 3mm	
^	52408 - Angle connecting link 90° BOK 8880	
	made of sheet steel dimension: 67.5/67.5xx10x2.5mm with 4 pcs hexagonal bolts M4x8	
	for connecting the channel shells	





	52304/100 - Leveling bar connection BOK 8880/300	
	made of sendzimir galvanized steel sheet 4mm dimensions: 260x100mm with 3 leveling hexagonal screws M10x60 polyamide with blind rivets for fastening to	
	channel shell for additional mounting in case of missing connection.	
	52369/0 - St lid BOK 8880/300 SK 0	
	made of sendzimir galvanized steel sheet 4mm dimension 500x306mm	
-	52420 - Brush strip cpl. BOK 8880 s=6	
	made of plastic, black dimension: 54x35mm bristles length: 25mm	
•	52421 - Brush strip cpl. BOK 8880 s=4 visible	回が対象が4回 7回が7点である。 12元間である。
	made of plastic, black dimension: 54x37mm bristles length: 30mm	
·		