



Product data sheet

48753/SI - Box FC E90 5G6 with fuse



Branching box E90 with fuse adapter IP66/68 for flat cable FE180 E90 5G6.0mm² with 3 cable glands M20x1.5 Ø6.0 - 15.0mm Project specific design on request (see Document/G00'299)

Characteristics	
Base Unit	Piece
availability	Delivery according to agreement
group	170000
country of origin	CH
Customs tariff number	8536.9080
Color	orange
Technical data	
Fire load (KWh)	2,16 kWh
Dimensions length x width x height (mm)	295x50x49 mm
Dimensions length x width x height (inch)	11,61x1,96x1.92 inch
Degree of protection	IP66/IP68 (2m,30min)
Metal parts	Metal parts:V4A / Contacting : Cu alloy
Flat cable contacting type	Piercing contact (screw)
Number of poles	5 pole
Contacting type	Screw terminal



Product data sheet

48753/SI - Box FC E90 5G6 with fuse


Connection conductor (mm²)	5x6,0 mm²
Thread cable gland	M20x1.5
Rated current heavy current part (A)	16 A
Rated voltage heavy current part (V)	250/400 V
Fuse	Three-phase (For ceramic fuse 5x20 mm)
Operating Temperature (°C)	-15 to 85 °C
Installation temperature min. (°C)	5 °C
Function maintenance	E30/E90 (DIN 4102-12)
Plastic parts	Halogen-free
Material slider/bottom part	Polyamide, black
Material housing	Polyamide
Material hood	Polyamide



Product data sheet

48753/SI - Box FC E90 5G6 with fuse

Product accessories

	<p>48354 - Retaining plate for junction box (48353/48653/48753)</p> <p>Retaining plate for junction box 48353-55/48653-55/48753-55</p>
--	---



Product data sheet

48753/SI - Box FC E90 5G6 with fuse

Product systems



FE180 E30/E90 5G6 mm²

Woertz fire safety system FE180 E30/E90 5G6 mm² for power supply of safety-relevant elements, such as emergency and escape route lighting, smoke extraction systems or fire department elevators.

