



System overview

FE180 E30/E90 3G4 mm²



Woertz fire safety system FE180 E30/E90 3G4 mm² for power supply of safety-relevant elements, such as emergency and escape route lighting, smoke extraction systems or fire department elevators.

Components



48450OR - Flat cable FE180/E90 3G4 orange

Flat cable Woertz FE180/E30/E90 3x4.00mm 2 FR/LS0H orange LNPE (rodent repellent) Fire protection cable with non-critical behavior (according to VKF guideline 14-15) for use in horizontal and vertical escape routes. Applicable in public buildings and facilities such as hospitals, hotels, offices, museums or other commercial buildings (KBOB). Also recommended for facilities with an increasing number of people in ever tighter spaces such as airports, train stations (above and below ground) or shopping malls (KBOB). Within the Woertz fire protection cabling systems also ideally suited for the high demands of infrastructure buildings such as tunnels, underpasses, parking garages or subway stations.



48453 - Junction box FK E90 3G4 M20 Ø 6-15 mm

Fire safety box IP66/IP68, 2-screw contacting for stripping-free feeding and branching, with screw connection for heavy current 3G4 mm², lengthwise outgoing, incl. 3 x cable glands M20x1.5, with a clamping range of Ø 6-8 mm, Ø 8-11 mm and Ø 11-15 mm respectively



48453/01 - Junction box FK E90 3G4 M20 Ø 6-8

Fire safety box IP66/IP68, 2-screw contacting for stripping-free feeding and branching, with screw connection for heavy current 3G4 mm², lengthwise outgoing, thread M20x1.5 incl. 1 x cable gland with Ø 6 - 8 mm



48453/02 - Junction box FK E90 3G4 M20 Ø 8-11

Fire safety box IP66/IP68, 2-screw contacting for stripping-free feeding and branching, with screw connection for heavy current 3G4 mm², lengthwise outgoing, thread M20x1.5 incl. 1 x cable gland with Ø 8 - 11 mm



48453/03 - Junction box FK E90 3G4 M20 Ø 11-15


Fire safety box IP66/IP68, 2-screw contacting for stripping-free feeding and branching, with screw connection for heavy current 3G4 mm², lengthwise outgoing, thread M20x1.5 incl. 1 x cable gland with Ø 11-15 mm





System overview

FE180 E30/E90 3G4 mm²

	<p>48453/SI - Box FC E90 3G4 with fuse</p> <p>Fire safety box with fuse adapter IP66/68 for flat cable FE180 E90 3G4mm²incl. 3 x cable gland M20x1.5, with a clamping range of Ø 6-8 mm, Ø 8-11 mm and Ø 11-15 mm respectively Project-specific design on request see document/G00'299</p>	
	<p>48960 - Junction box FK E90 3G2.5/3G4.0 IP68 with shrink tubing</p> <p>Feed/connection box E90, for feeding (round cable - flat cable) or for connection (flat cable - flat cable) for flat cable 3G2.5/4 mm². With heat shrink tubing IP66/68.</p>	
	<p>48961 - End caps FC E90 3G2.5/3G4.0/3G6.0</p> <p>End caps E90 IP66/68 for flat cable FE180 E90 3G2.5mm 2 /3G4.0mm 2 /3G6.0mm 2</p>	
	<p>48511/42 - End cap with mastic IP68 42/15 105mm</p> <p>Cable end piece shrink - end cap, diameter 42 mm, after shrinkage 15 mm, length 105 mm, black. Inside coated with adhesive and sealant.</p>	
	<p>49935 - Cutting shears up to 6 mm²</p> <p>Woertz flat cable shears up to 5x6 mm² (with higher force up to 5x16 mm²)</p>	
	<p>49370 - Fixing clamp 3G2.5/4 mm² E90</p> <p>Mounting distance: 800mm</p>	
	<p>49386 E90 - Riser clamp E90</p> <p>Max. Bride load: 50kg. For Woertz fire safety flat cable: Woertz FE180 3G2.5 and 4 mm², Woertz FE180 5G2.5, 4 6 mm². For Woertz flat cable: Woertz Technofil 5G2.5 1.5 mm², Woertz power 5G2.5 mm², Woertz Power IP 5G2.5 mm² 6 mm², Woertz combi 5G2.5 mm² 2x1.5 mm², Woertz Dali IP 5G2.5 mm² 2x1.5 mm², Woertz Dali 3/5G2.5 mm² 2x1.5 mm², Woertz 5G4 mm², Woertz 7G2.5 mm².</p>	
	<p>48254 - Retaining plate to box 48253/48453</p> <p>Retaining plate to connection box 48253/48453</p>	