














System overview

Three-stud installation clamps DIN 35



Various three-stud installation clamps.

Components

	<p>30431/2 - Three terminal block DIN35 4mm² PE-L gray</p> <p>Three-stud installation clamp, with stainless steel screws, 4x3-digit designation option, recessed for cross-connections</p>	
	<p>30432 - Three terminal block DIN35 4mm² PE-L gray</p> <p>Three-pole installation terminal without protective conductor, with stainless steel screws, 4x3-digit designation option, for cross-connections recessed 2-pole</p>	
	<p>30403 - Three-pin initiator terminal DIN35 2.5mm² (6 clamping points)</p> <p>Three-pole initiator terminal DIN35 2.5mm² for power supply with 6 terminal points</p>	
	<p>30430 - Three-pin terminal DIN35 4mm² PE-L-N gray/blue</p> <p>Three-stud installation terminal, with stainless steel screws, 4x3-digit designation option, with detachable neutral conductor isolator</p>	
	<p>30431/1 - Three-pin terminal DIN35 4mm² PE-L-N gray/blue</p> <p>Three-stud installation clamp, with stainless steel screws, 4x3-digit designation option, recessed for cross-connections</p>	
	<p>30400 - Three-pin initiator terminal DIN35 2.5mm² (4 clamping points)</p> <p>Three-pole initiator terminal DIN35 2.5mm² for power supply with 4 terminal points.</p>	