



Product data sheet

48655/01 - Junction box FK E90 5G4 mm² M25 Ø 12.5-16



Fire safety box IP66/IP68, 2-screw contacting for stripping-free feeding and branching, with screw connection for heavy current 5G4 mm², lengthwise outgoing, incl. 1 x cable glands M25x1.5, with a clamping range of Ø 12.5-16 mm.

Characteristics	
Base Unit	Piece
availability	Delivery according to agreement
EAN Code	7611718269974
group	170000
Packaging unit	1
country of origin	CH
Customs tariff number	8536.9080
Weight (g)	782,2 g
Color	orange
Technical data	
Fire load (KWh)	1,91 kWh
Dimensions length x width x height (mm)	185x65x70 mm
Dimensions length x width x height (inch)	7.28x2.56x2.76 inch
Degree of protection	IP66/IP68 (2m,30min)
Metal parts	Metal parts:V4A / Contacting : Cu alloy



Product data sheet

48655/01 - Junction box FK E90 5G4 mm² M25 Ø 12.5-16


Flat cable contacting type	Piercing contact (screw)
Number of poles	5 pole
Contacting type	Screw terminal
Connection conductor (mm ²)	5x2,5 mm ²
Thread cable gland	mit Kabelverschraubung M25x1.5 (IP68) D= 12.5 mm - 16.0 mm
Cable gland (mm)	12.5- 16 mm
Rated current heavy current part (A)	32(4mm ²) A
Rated voltage heavy current part (V)	690 V
Operating Temperature (°C)	-15 to 85 °C
Installation temperature min. (°C)	5 °C
Function maintenance	E30/E90 (DIN 4102-12)
Plastic parts	Halogen-free
Material slider/bottom part	Polyamide, orange
Material housing	Polyamide, orange
Material hood	Polyamide, orange



Product data sheet

48655/01 - Junction box FK E90 5G4 mm² M25 Ø 12.5-16

Product accessories



48254 - Retaining plate to box 48253/48453

Retaining plate to connection box 48253/48453



Product data sheet

48655/01 - Junction box FK E90 5G4 mm² M25 Ø 12.5-16

Product systems



FE180 E30/E90 5G4 mm²

Woertz fire safety system FE180 E30/E90 5G4 mm² for power supply of safety-relevant elements, such as emergency and escape route lighting, smoke extraction systems or fire department elevators.

