















System overview

Plug connections code 5 for light control DALI, 3 pole (1,2,3)



3 pole connectors code 5 for light control DALI.



















Components

	<p>49343/1F/C5 - Pre-wired connection C5-F 3x1.5 1m HF</p> <p>Pre-wired connector, socket 3-poles code 5 with 1 m cable 3x1.5 mm ² with free end, conductor compressed, 16 A, 250 V, halogen free, behaviour to fire classification Cca</p>	
	<p>49343/1M/C5 - Pre-wired connection C5-M 3x1.5 1m HF</p> <p>Pre-wired connector, plug 3-poles code 5 with 1 m cable 3x1.5 mm ² with free end, conductor compressed, 16 A, 250 V, halogen free, behaviour to fire classification Cca</p>	
	<p>49343/1MF/C5 - Pre-wired connection C5-M+F 3x1.5 1m HF</p> <p>Pre-wired connector, plug and socket 3-poles code 5 with 1 m cable 3x1.5 mm ², 16 A, 250 V, halogen free, behaviour to fire classification Cca</p>	
	<p>49343/2F/C5 - Pre-wired connection C5-F 3x1.5 2m HF</p> <p>Pre-wired connector, socket 3-poles code 5 with 2 m cable 3x1.5 mm ² with free end, conductor compressed, 16 A, 250 V, halogen free, behaviour to fire classification Cca</p>	
	<p>49343/2M/C5 - Pre-wired connection C5-M 3x1.5 2m HF</p> <p>Pre-wired connector, plug 3-poles code 5 with 2 m cable 3x1.5 mm ² with free end, conductor compressed, 16 A, 250 V, halogen free, behaviour to fire classification Cca</p>	
	<p>49343/2MF/C5 - Pre-wired connection C5-M+F 3x1.5 2m HF</p> <p>Pre-wired connector, plug and socket 3-poles code 5 with 2 m cable 3x1.5 mm ², 16 A, 250 V, halogen free, behaviour to fire classification Cca</p>	



System overview



















Plug connections code 5 for light control DALI, 3 pole (1,2,3)

	49343/3F/C5 - Pre-wired connection C5-F 3x1.5 3m HF Pre-wired connector, socket 3-poles code 5 with 3 m cable 3x1.5 mm ² with free end, conductor compressed, 16 A, 250 V, halogen free, behaviour to fire classification Cca	
	49343/3M/C5 - Pre-wired connection C5-M 3x1.5 3m HF Pre-wired connector, plug 3-poles code 5 with 3 m cable 3x1.5 mm ² with free end, conductor compressed, 16 A, 250 V, halogen free, behaviour to fire classification Cca	
	49343/3MF/C5 - Pre-wired connection C5-M+F 3x1.5 3m HF Pre-wired connector, plug and socket 3-poles code 5 with 3 m cable 3x1.5 mm ² , 16 A, 250 V, halogen free, behaviour to fire classification Cca	
	49343/4F/C5 - Pre-wired connection C5-F 3x1.5 4m HF Pre-wired connector, socket 3-poles code 5 with 4 m cable 3x1.5 mm ² with free end, conductor compressed, 16 A, 250 V, halogen free, behaviour to fire classification Cca	
	49343/4M/C5 - Pre-wired connection C5-M 3x1.5 4m HF Pre-wired connector, plug 3-poles code 5 with 4 m cable 3x1.5 mm ² with free end, conductor compressed, 16 A, 250 V, halogen free, behaviour to fire classification Cca	
	49343/4MF/C5 - Pre-wired connection C5-M+F 3x1.5 4m HF Pre-wired connector, plug and socket 3-poles code 5 with 4 m cable 3x1.5 mm ² , 16 A, 250 V, halogen free, behaviour to fire classification Cca	
	49343/5F/C5 - Pre-wired connection C5-F 3x1.5 5m HF Pre-wired connector, socket 3-poles code 5 with 5 m cable 3x1.5 mm ² with free end, conductor compressed, 16 A, 250 V, halogen free, behaviour to fire classification Cca	
	49343/5M/C5 - Pre-wired connection C5-M 3x1.5 5m HF Pre-wired connector, plug 3-poles code 5 with 5 m cable 3x1.5 mm ² with free end, conductor compressed, 16 A, 250 V, halogen free, behaviour to fire classification Cca	
	49343/5MF/C5 - Pre-wired connection C5-M+F 3x1.5 5m HF Pre-wired connector, plug and socket 3-poles code 5 with 5 m cable 3x1.5 mm ² , 16 A, 250 V, halogen free, behaviour to fire classification Cca	



System overview






Plug connections code 5 for light control DALI, 3 pole (1,2,3)

	<p>49343/6F/C5 - Pre-wired connection C5-F 3x1.5 6m HF</p> <p>Pre-wired connector, socket 3-poles code 5 with 6 m cable 3x1.5 mm² with free end, conductor compressed, 16 A, 250 V, halogen free, behaviour to fire classification Cca</p>	
	<p>49343/6M/C5 - Pre-wired connection C5-M 3x1.5 6m HF</p> <p>Pre-wired connector, plug 3-poles code 5 with 6 m cable 3x1.5 mm² with free end, conductor compressed, 16 A, 250 V, halogen free, behaviour to fire classification Cca</p>	
	<p>49343/6MF/C5 - Pre-wired connection C5-M+F 3x1.5 6m HF</p> <p>Pre-wired connector, plug and socket 3-poles code 5 with 6 m cable 3x1.5 mm², 16 A, 250 V, halogen free, behaviour to fire classification Cca</p>	
	<p>49343/8F/C5 - Pre-wired connection C5-F 3x1.5 8m HF</p> <p>Pre-wired connector, socket 3-poles code 5 with 8 m cable 3x1.5 mm² with free end, conductor compressed, 16 A, 250 V, halogen free, behaviour to fire classification Cca</p>	
	<p>49343/8M/C5 - Pre-wired connection C5-M 3x1.5 8m HF</p> <p>Pre-wired connector, plug 3-poles code 5 with 8 m cable 3x1.5 mm² with free end, conductor compressed, 16 A, 250 V, halogen free, behaviour to fire classification Cca</p>	
	<p>49343/8MF/C5 - Pre-wired connection C5-M+F 3x1.5 8m HF</p> <p>Pre-wired connector, plug and socket 3-poles code 5 with 8 m cable 3x1.5 mm², 16 A, 250 V, halogen free, behaviour to fire classification Cca</p>	
	<p>49343/10F/C5 - Pre-wired connection C5-F 3x1.5 10m HF</p> <p>Pre-wired connector, socket 3-poles code 5 with 10 m cable 3x1.5 mm² with free end, conductor compressed, 16 A, 250 V, halogen free, behaviour to fire classification Cca</p>	
	<p>49343/10M/C5 - Pre-wired connection C5-M 3x1.5 10m HF</p> <p>Pre-wired connector, plug 3-poles code 5 with 10 m cable 3x1.5 mm² with free end, conductor compressed, 16 A, 250 V, halogen free, behaviour to fire classification Cca</p>	
	<p>49343/10MF/C5 - Pre-wired connection C5-M+F 3x1.5 10m HF</p> <p>Pre-wired connector, plug and socket 3-poles code 5 with 10 m cable 3x1.5 mm², 16 A, 250 V, halogen free, behaviour to fire classification Cca</p>	



System overview

Plug connections code 5 for light control DALI, 3 pole (1,2,3)

	<p>3954 - Holder f. marking cable with 5 holders</p> <p>Cable label holder for 4 digits each, for cable 3x1.5mm2</p>	
	<p>49750 - Locking to connectors</p> <p>For mechanical connection of socket to plug 3 and 5 poles</p>	
	<p>49803 - Sealing element IP68 for 3-poles plug connection</p> <p>to extend the degree of protection to IP68 (waterproof) for all 3-pole connectors</p>	