




35340/3GR - Tension clamp terminal DIN35 2.5mm² gray



Tension clamp terminal DIN35 2.5mm² 88x5x31mm blue with 4 connections marking possibility on the side and in the middle with stripes, recessed for cross connection

Characteristics	
Eldas number	158450137
Base Unit	Piece
availability	available from stock
EAN Code	7611718221361
group	165000
Packaging unit	25
country of origin	СН
Customs tariff number	8536.9080
Weight (g)	12 g
Color	gray
Technical data	
Dimensions length x width x height (mm)	88x5x31 mm
Dimensions length x width x height (inch)	3.47x0.20x1.22 inch
Cross section (mm ²)	0,2 - 2,5 mm²
Nominal current (A)	20 A





35340/3GR - Tension clamp terminal DIN35 2.5mm² gray

Rated voltage (V)	600 V
Connection type	Spring clamp
DIN rail type	DIN-35
Smallest connectable section (mm ²)	0,5 mm²
Number of connection point	4
Number of floor	1
Number of potentials	1
Clamping screw M	M4
Central thread M	3
Insulating material	PA66
Nominal Cross-section (mm²)	2,5 mm²
Stripping length mm (mm)	10 mm
Rating data according to UL 1059	
Rated voltage US (V)	300 V
Nominal cross section (AWG)	14 AWG
Cross-section (AWG)	14 - 26 AWG
Smallest connectable section (AWG)	18 AWG
Stripping length (inch)	0,39 inch
Tightening torque (Ib-inch)	13,3 lb-inch





35340/3GR - Tension clamp terminal DIN35 2.5mm² gray

Product accessories

80247 - Test plug Ø 2.3mm red, socket 4mm connecting cable incl.
80248 - Test plug Ø 2.3mm black, socket 4mm connecting cable incl.
Bezeichnungskarte_5x12mm - Designation card 5x12mm Various designation plates
Bezeichnungskarte_5x9mm - Designation card 5x9mm Various designation plates with different embossing.
35455/09BS - Marking strip 9x240mm with 25strips per box
35455/59T - Marking adaptor for label 5x9mm null
35341/3 - Partition and end barrier 88x36mm grey, to spring clamp terminals with 3 and 4 clamps
35445 - End retainer for Spring clamp terminal DIN35 of polyamide 66, greydimensions: 8x45.2x23.5mm to spring clamp terminals 1.5 to 16mm 2
35425/05 - Center jumper cover grey Cross-connection rake insulated, gray, to tension spring terminals 5mm
35425/05BR - Bridge to cross-junction rack grey Bridge insulated, suitable for 3542505 to connect 2 connecting rakes. 33.2x6x10.4 mm
35435/302 - Cable entrance to 0.2mm2 conductors funnel-shaped, to spring clamp terminals 1.5 and 2.5mm 2Stripes of 10 pieces, separable
35435/305 - Cable entrance to 0.5mm2 conductors funnel-shaped, to spring clamp terminals 1.5 and 2.5mm 2Stripes of 10 pieces, separable





35340/3GR - Tension clamp terminal DIN35 2.5mm² gray

35435/310 - Cable entrance to 1mm2 conductors

funnel-shaped, to spring clamp terminals 1.5 and 2.5mm 2Stripes of 10 pieces, separable





35340/3GR - Tension clamp terminal DIN35 2.5mm² gray

Product systems



Tension clamp terminals with four connections DIN 35

Various tension spring terminals with four connections.

