



Product data sheet

80291/3M - Combination rail DIN35/C30 of aluminum 3 m



Combination rail Extrudal-050 DIN35/C30 with 35x15x1 mm made of aluminum alloy, with a 85 mm² copper cross section, 3 m length.

Characteristics	
Eldas number	168000537
Base Unit	Meter
availability	Delivery in 4 weeks
EAN Code	7611718247804
group	171000
Packaging unit	3
country of origin	CH
Customs tariff number	7604.2900
Weight (g)	370 g
Technical data	
Dimensions length x width x height (mm)	215x82x120 mm
Dimensions length x width x height (inch)	8.46x3.25x4.72 inch
Rated voltage (V)	650 V
DIN rail type	DIN-35
Number of connection point	2



Product data sheet

80291/3M - Combination rail DIN35/C30 of aluminum 3 m

Number of floor	1
Number of potentials	1
Nominal Cross-section (mm²)	500 mm²
Ladder mounting space Width (mm)	30 mm
Ladder mounting space Height (mm)	62 mm



Product data sheet

80291/3M - Combination rail DIN35/C30 of aluminum 3 m


Product accessories



Product data sheet

80291/3M - Combination rail DIN35/C30 of aluminum 3 m

Product systems



Profile rails DIN15, DIN32, DIN35

Various mounting rails and combination rails.



Sliding blocks made of galvanized steel type C30

available in three versions:

- with screw, with spring
- without screw, with spring
- without screw, without spring
- Fits profile rails no. 4382, 4383 and 80291, type C30



Profile rails DIN35

DIN rail DIN35, universal carrier made of a sheet metal profile in electrical engineering for fastening electrical equipment in distribution boxes, control cabinets, junction boxes, etc. Different components (e.g. relays, impulse switches, timers, circuit breakers, terminal blocks) can be slid onto a carrier rail from the side or plugged in and locked from the front. This standardized method facilitates the assembly of control cabinets and switch boxes, thus reducing labor costs. The different types of rails are in the standard EN 60715.

