




System overview

DAK22 levelable 271x271 square



Raised floor system DAK22 271x271 square, with levelable covering height

Components



52955N - Bushings niv 271 DAK22 AI KM

Hanging plate for cutout 283x283 made of chrome steel 1.5mm with infinitely adjustable frame 278x278x30mm

- made of aluminum 3mm
- with cover support rubber 2mm

Lid 271x271x25mm made of aluminum 3mm

- Occupiable inside 22mm
- including 2 cable trays

Height adjustment: 0-22mm




52060 - Installation kit 2x3FLF horizontal empty BAK22

hook-in, to BAK with protective edge 12mm and 22mm made of galvanized sheet steel 1.5mm including 2 mounting plates

color: RAL 7032 pebble gray

equipped with: 1 pc. Terminal strip 7x2.5mm²

minimum floor height: BAK12=74mm; BAK22=84mm



52050 - Installation kit 2x5FLF vertical SB BAK22

hook-in, to BAK with protective edge 12mm and 22mm including 2 mounting plates

Color: RAL 7032 pebble gray

equipped, wired and tested: 1 pcs. Terminal strip 9x2.5mm²

5 pcs. socket FLF 3/5 T13 white 55200

Minimum floor height: BAK12=89mm; BAK22=99mm



52040 - Installation kit 2x5FLF vertical empty BAK22

hook-in, to BAK with protective edge 12mm and 22mm made of galvanized sheet steel 1.5mm including 2 mounting plates

color: RAL 7032 pebble gray

equipped with: 1 pc. Terminal strip 9x2.5mm²

minimum floor height: BAK12=89mm; BAK22=99mm






System overview

DAK22 levelable 271x271 square



52073 - Installation kit 2x8 module-LM empty BAK22 / DAK22

for modules type Legrand Mosaic
hangable, to BAK with protective edge 12mm and 22mm
including 2 mounting plates
color: RAL 7032 pebble gray
equipped with: 1 pc. Terminal strip 9x2.5mm²
minimum floor height: BAK12=89mm; BAK22=99mm




52058 - Installation kit 2x8 module-BT empty BAK22 / DAK22

for modules type bticino
mountable, to BAK and DAK with protective edge 22mm
including 2 holding plates and 2 mounting plates
color: RAL 7032 pebble gray
equipped with: 1 pc. Terminal strip 9x2.5mm²
minimum floor height: BAK12=89mm; BAK22=99mm



52940 - Protective housing FLF standing DAK22

suitable for installation kit 52040 and 52050,
as a lower cover of the installation kit,
can be mounted with an installation kit from above,
made of galvanized sheet steel 1mm color: RAL 7032 pebble gray



51567 - Al cover visible BAK22 KM

made of aluminum 3mm, Sichseite colorless anodized,
glued to wood raw chipboard V100 22mm.
Dimension: 271x271x25mm



52960 - Protective housing FLF horizontal DAK22

suitable for installation kit 52030 and 52060,
as a lower cover of the installation kit,
can be mounted with an installation kit from above,
made of galvanized sheet steel 1mm color: RAL 7032 pebble gray



52030 - Installation kit 2x3FLF horizontal SB BAK22

hook-in, to BAK with protective edge 12mm and 22mm
made of galvanized sheet steel 1.5mm
including 2 mounting plates
color: RAL 7032 pebble gray
equipped, wired and tested: 1 pc. Terminal block 7x2.5mm²
3 pcs. socket FLF 3/5 T13 white 55200
minimum floor height: BAK12=74mm; BAK22=84mm

