



Product data sheet

49595 - Raptor USB interface - KNX



KNX system component - Raptor USB interface - compatible to ETS3 - KNX bus coupler integrated - IP20

Characteristics	
Eldas number	405830007
Base Unit	Piece
availability	Delivery according to agreement
EAN Code	7611718249112
group	376000
Packaging unit	1
country of origin	CH
Customs tariff number	8536.5000
Weight (g)	190 g
Color	black
Technical data	
Dimensions length x width x height (mm)	114x74x55 mm
Dimensions length x width x height (inch)	4.49x2.91x2.17 inch
Degree of protection	IP20
Flat cable contacting type	Piercing contact (knife)



Product data sheet

49595 - Raptor USB interface - KNX

Material	PA 6.6
Configuration mode	S-mode
Type of connection	USB 2.0 Type B
Type of mounting	Flat cable Woertz combi 5G2.5 2x1.5 mm2
Transmission media	KNX TP1
Operating Temperature (°C)	-5 - 45 °C
Installation temperature min. (°C)	10 °C
Contact to flat cable	KNX
KNX bus voltage (type)	29 VDC SELV Typ



Product data sheet

49595 - Raptor USB interface - KNX

Product accessories



Product data sheet


49595 - Raptor USB interface - KNX

Product systems



KNX flat cable power supply / interface / programming console

Various KNX flat cables Power supply / interface / programming console



Flat cable system Combi 5G2.5 2x1.5 mm² (KNX)

This flexible system is the basis for decentralized building automation and combines power current and bus data line in a single cable application.

The areas of application are office and public buildings, industrial buildings, hotels or even modular buildings with a high degree of prefabrication for quick installation.

