



35310/6GR - Tension clamp terminal DIN35 6mm<sup>2</sup> gray



Tension clamp with 2 connections Marking option on the side and in the middle with strip, recessed for cross connection

Characteristics	
Eldas number	158430337
Base Unit	Piece
availability	available from stock
EAN Code	7611718217463
group	165000
Packaging unit	50
country of origin	СН
Customs tariff number	8536.9080
Weight (g)	15 g
Color	gray
Technical data	
Dimensions length x width x height (mm)	65.5x8x35 mm
Dimensions length x width x height (inch)	2.58x0.32x1.38 inch
Cross section (mm <sup>2</sup> )	0,5 - 6 mm²
Nominal current (A)	50 A





### 35310/6GR - Tension clamp terminal DIN35 6mm<sup>2</sup> gray

Rated voltage (V)	600 V
Connection type	Spring clamp
DIN rail type	DIN-35
Number of connection point	2
Number of floor	1
Number of potentials	1
Insulating material	PA66
Nominal Cross-section (mm²)	6 mm²
Stripping length mm (mm)	12 mm
Rating data according to UL 1059	
Rated voltage US (V)	300 V
Nominal cross section (AWG)	10 AWG
Cross-section (AWG)	10 - 20 AWG
Stripping length (inch)	0,47 inch





35310/6GR - Tension clamp terminal DIN35 6mm<sup>2</sup> gray

#### Product accessories

80247 - Test plug Ø 2.3mm red, socket 4mm connecting cable incl.
80248 - Test plug Ø 2.3mm black, socket 4mm connecting cable incl.
Bezeichnungskarte_8x9mm - Designation card 8x9mm Various designation plates with different embossing.
Bezeichnungskarte_8x12mm - Designation card 8x12mm Various designation plates with different embossing.
<b>35455/09BS - Marking strip 9x240mm</b> with 25strips per box
<b>35455/69T - Marking adaptor for label 6x9mm</b> to spring clamp terminals
<b>35311/4 - Partition and end barrier 64.5x39mm</b> grey, to spring clamp terminals with 2 clamps
<b>35445</b> - End retainer for Spring clamp terminal DIN35 of polyamide 66, greydimensions: 8x45.2x23.5mm to spring clamp terminals 1.5 to 16mm 2
<b>35425/08 - Cross-junction rack 10pole black</b> insulated, to spring clamp terminals 8mm
<b>35425/06BR - Bridge to cross-junction rack black</b> Bridge insulated, suitable for 3542506 and 3542508 to connect 2 connecting rakes. 33.2x6x10.4 mm





35310/6GR - Tension clamp terminal DIN35 6mm<sup>2</sup> gray

### **Product systems**



Tension clamp terminals with two connections DIN 35

Various tension spring terminals with two connections.

