



Product data sheet

49721/C - Branching box FC combi BUS C3



Characteristics	
Eldas number	150707237
Base Unit	Piece
availability	Delivery according to agreement
EAN Code	7611718248528
group	170000
Packaging unit	50
country of origin	CH
Customs tariff number	8536.9080
Weight (g)	18,1 g
Color	black
Coding plug connection	Code 3
Technical data	
Box Type	Junction boxes
Fire load (KWh)	0,12 kWh
Dimensions length x width x height (mm)	44x39,5x28 mm



Product data sheet

49721/C - Branching box FC combi BUS C3

Dimensions length x width x height (inch)	1,73x1,56x1,1 inch
Degree of protection	IP20, IP40 (Connected)
Metal parts	Corrosion protected
Flat cable contacting type	Piercing contact (screw)
Number of poles	2 pole
Rated current bus section (A)	3 A
Rated voltage bus part (V)	50 V
Operating Temperature (°C)	-15 to 85 °C
Installation temperature min. (°C)	5 °C
Plastic parts	Halogen-free
Material gate valve/bottom part bus	Polyamide, Purple
Material housing bus	Polyamide, black
Material hood bus	Polycarbonate, transparent
Number Screwdriver Pointed Screws Bus Part	3
Service torque Pointed screws Bus part (Nm)	1 Nm



Product data sheet

49721/C - Branching box FC combi BUS C3

Product accessories



Stecker_BUS - Plug connections / connection cables for BUS (Code Woertz, Code


Plug connections / connection cables for BUS (Code Woertz, Code KNX, Code 3)



Product data sheet

49721/C - Branching box FC combi BUS C3

Product systems



Flat cable system Combi 5G2.5 2x1.5 mm²

Intelligent building control in a flexible system. Power current and bus data line combined for maximum efficiency. For office and public buildings, industrial buildings, hotels and modern modular buildings. Experience the future of building automation with our innovative solution.

