




33200/4RO - Screw spring terminal 4mm² red



Screw spring clip with inscription 2x4 labels

Characteristics	
Eldas number	158136027
Base Unit	Piece
availability	Delivery according to agreement
EAN Code	7611718250378
group	165000
Packaging unit	50
country of origin	СН
Weight (g)	11,4 g
Color	red
Technical data	
Dimensions length x width x height (mm)	68.5x6x35 mm
Dimensions length x width x height (inch)	2.70x0.24x1.38 inch
Cross section (mm ²)	0,5 - 4 mm²
Nominal current (A)	32 A
Rated voltage (V)	800 V





33200/4RO - Screw spring terminal 4mm² red

Connection type	Coil spring terminal
Number of connection point	3
Number of floor	1
Number of potentials	1
Clamping screw M	M3
Insulating material	PA66
Nominal Cross-section (mm ²)	4 mm²
Stripping length mm (mm)	12 mm
Head reception room width x height (mm)	3.7x3.6 /3.2x4.6 mm
Rating data according to UL 1059	
Rated voltage US (V)	600 V
Nominal cross section (AWG)	12 AWG
Cross-section (AWG)	12 - 20 AWG
Stripping length (inch)	0,47 inch





33200/4RO - Screw spring terminal 4mm² red

Product accessories

	Bezeichnungskarte_6x12mm - Designation cards 6x12mm
	Various designation labels 6x12mm with different embossing.
	Bezeichnungskarte_6x9mm - Designation card 6x9mm
	Various designation plates with different embossing.
5	Bezeichnungskarte_6x3mm - Designation card 6x3mm
	Various designation plates with different embossing.
	33210 - Separation end wall to screw spring clamp
	null
	3418 - Stopper DIN35 height 30mm
	Makrolon locking piece
	30370 - Stopper DIN35 height 23mm
	Locking piece made of nickel-plated brass M3 screw
Ħ	81506/2 - Cross-connection 2-pole to terminals DIN32/35 4mm ²
	Insulated cross-connection 2-pole to terminals DIN32/35 4mm ² including screws M3. Standard version. Dimension: 11.1x20.8 mm
ŤŤŤ	81506/3 - Cross-connection 3-pole to terminals DIN32/35 4mm ²
	Insulated cross-connection 3-pole to terminals DIN32/35 4mm ² including screws M3. Standard version. Dimension: 17.2x20.8 mm
	81506/4 - Cross-connection 4-pole to terminals DIN32/35 4mm ²
	Insulated cross-connection 4-pole to terminals DIN32/35 4mm ² including screws M3. Standard version. Dimension: 23.3x20.8 mm
	81506/5 - Cross-connection 5-pole to terminals DIN32/35 4mm ²
	Insulated cross-connection 5-pole to terminals DIN32/35 4mm ² including screws M3. Standard version. Dimension: 29.4x20.8 mm
	81506/10 - Cross-connection 10-pole to terminals DIN32/35 4mm ²
	Insulated cross-connections 10-pole to terminals DIN32/35 4mm ² including M3 screws. Standard version. Dimension: 59.9x20.8 mm





33200/4RO - Screw spring terminal 4mm² red

Product systems



Screw-type plug-in spring terminals DIN 35

Various screw spring terminals.

