



49615/1x5G10/15 - Junction box Pre-assembled for flat cable 49615 1.5M HF-K 5G10



Junction box pre-assembled 5-pole 5G16mm²/5G25mm² including mounting and 1 threaded socket M40x1.5 for 1 outlet. With cable gland 49635 and pre-assembled round cable 5G10mm² 1.5 m.

Characteristics	
Base Unit	Piece
availability	Delivery according to agreement
EAN Code	7611718282669
group	0170000
Packaging unit	1
country of origin	СН
Customs tariff number	85369080
Color	black
Technical data	
Вох Туре	Junction boxes
Fire load (KWh)	3,3 kWh
Dimensions length x width x height (mm)	1700x85x91 mm
Degree of protection	IP65
Metal parts	Corrosion protected
Flat cable contacting type	Piercing contact (screw)





49615/1x5G10/15 - Junction box Pre-assembled for flat cable 49615 1.5M HF-K 5G10

Number of poles	5 pole
Contacting type	Screw terminal
Connection conductor (mm²)	5x16 mm²
Thread cable gland	with cable gland M25x1.5 D= 13.0 mm - 18.0 mm and M40x1.5 for flat cable
Rated current heavy current part (A)	76(16mm2) / 80(with flat cable 5x25mm2) A
Rated voltage heavy current part (V)	690 V
Operating Temperature (°C)	-15 to 85 °C
Installation temperature min. (°C)	5 °C
Plastic parts	Halogen-free
Material slider/bottom part	Polyamide, black
Material housing	Polyamide, black
Material hood	Polyamide, black





49615/1x5G10/15 - Junction box Pre-assembled for flat cable 49615 1.5M HF-K 5G10

Product accessories





49615/1x5G10/15 - Junction box Pre-assembled for flat cable 49615 1.5M HF-K 5G10

Product systems



Flat cable system Power 5G25 mm² (IP65)

Ideal for construction temporary buildings, offices, tunnels, halls, trade fairs and e-mobility. Robust, weatherproof and powerful - perfect for temporary or permanent power supply.









Flat cable system Power 5G25 mm² (IP65)





Pre-assembled E-Mobility Installation



Our junction and branch boxes provide safe protection for your electrical installations. The installation is simple and flexible thanks to preassembled round cables and various cable glands.



- Our boxes are weatherproof thanks to IP65 protection class and offer a high load capacity up to 63A and cross sections up to 35 mm².
- Perfect for garage applications with our special accessories. Rely on our reliable products for a safe electrical installation!
 With our Woertz junction and branch boxes you can rely on a durable and reliable solution for your electrical installations. Protect your connections with our RCD protection and benefit from the easy installation and flexible application options.



Flat cable system Power 5G16 mm² (IP65)

Robust, weatherproof and powerful - a flexible power supply solution for construction temporary buildings, offices, tunnels, ships, halls, trade fairs and e-mobility.



Flat cable system Power 5G16 mm² (IP65)









49615/1x5G10/15 - Junction box Pre-assembled for flat cable 49615 1.5M HF-K 5G10



Flat cable system Power 5G16 mm² (IP65)

