



Product data sheet

48253/03 - Junction box FK E90 3G2.5 M20 Ø 11-15 mm



Fire safety box IP66/IP68, 2-screw contacting for stripping-free feeding and branching, with screw connection for heavy current 3G2.5 mm², lengthwise outgoing, incl. 1 x cable gland M20x1.5, with a clamping range of Ø 11-15 mm

Characteristics	
Base Unit	Piece
availability	Delivery according to agreement
EAN Code	7611718269844
group	170000
Packaging unit	1
country of origin	CH
Customs tariff number	8536.9080
Weight (g)	391,21 g
Color	orange
Technical data	
Fire load (KWh)	1,15 kWh
Dimensions length x width x height (mm)	137x50x49 mm
Dimensions length x width x height (inch)	5.39x1.97x1.93 inch
Degree of protection	IP66/IP68 (2m,30min)
Metal parts	Metal parts:V4A / Contacting : Cu alloy



Product data sheet

48253/03 - Junction box FK E90 3G2.5 M20 Ø 11-15 mm


Flat cable contacting type	Piercing contact (screw)
Number of poles	3 pole
Contacting type	Screw terminal
Connection conductor (mm²)	3x2.5 mm²
Thread cable gland	mit Kabelverschraubung M20x1.5 (IP68) D= 11.0 mm - 15.0 mm
Cable gland (mm)	11.0 - 15.0 mm
Rated current heavy current part (A)	24(2.5mm²) A
Rated voltage heavy current part (V)	690 V
Operating Temperature (°C)	-15 to 85 °C
Installation temperature min. (°C)	5 °C
Function maintenance	E30/E90 (DIN 4102-12)
Plastic parts	Halogen-free
Material slider/bottom part	Polyamide, orange
Material housing	Polyamide, orange
Material hood	Polyamide, orange



Product data sheet

48253/03 - Junction box FK E90 3G2.5 M20 Ø 11-15 mm

Product accessories



48254 - Retaining plate to box 48253/48453

Retaining plate to connection box 48253/48453



Product data sheet

48253/03 - Junction box FK E90 3G2.5 M20 Ø 11-15 mm

Product systems



FE180 E30/E90 3G2.5 mm²



Woertz Fire Safety System FE180 E30/E90 3G2.5 mm² for power supply of safety-relevant elements, such as emergency and escape route lighting, smoke extraction systems or fire department elevators.