




Floor channel BOK 8880 400x60mm integrated leveling device



Floor channel BOK 8880 400x60mm with integrated leveling device.

### Components



### 52345 - Installation kit Scs 3FLF horizontal empty BOK

Low current version made of sendzimir galvanized sheet steel 1.5mm with strain relief stampings and knurled screw for lateral fixing in the trunking shell

Dimension: 400x95x41.4mm Color: RAL 7032 pebble gray





#### 55032 - Installation kit Sts 4FLF horizontal empty BOK

made of galvanized sheet steel 1.5mm with knurled screw for lateral fixing in the trunking shell. Dimension: 376x47(53)x40mm Color: RAL 7032 pebble gray

Equipped: 1 pcs. blind hole clamp 8x2.5mm <sup>2</sup> 10146





#### 52463N - Cross connection BOK 8880/400x60 iN

Cross joint BOK 8880/400x60 with integrated levelingmade of sendzimirgalvanized sheet steel 1.5mm pressed on both sides in special aluminum profile Woertz with temporary protective edge inserted in groove and impact sound trapezoidal rubber as cover support

leveling hexagonal bolts M10x60 polyamide including connecting material

High 60mm / cover nominal width 400mm

Length: 1000mm





#### 52473/12 - 0

made of aluminum 3mm dimension: 500x399x16mm edge height inside 13mm





### 52461N - Angle connection BOK 8880/400x60 iN

with integrated levelingmade of sendzimir-galvanized sheet steel 1.5mmpressed into special aluminum profile Woertz on both sides with temporary protective edge inserted in groove and impact sound trapezoidal rubber as cover supportleveling hexagonal bolts M10x60 polyamideincluding connecting materialheight 60mm / nominal cover width 400mm







Floor channel BOK 8880 400x60mm integrated leveling device

	52462N - T-joint BOK 8880/400x60 iN	
	with integrated levelingmade of sendzimir-galvanized sheet steel 1.5mmpressed into special aluminum profile Woertz on both sides with temporary protective edge inserted in groove and impact sound trapezoidal rubber as cover supportleveling hexagonal bolts M10x60 polyamideincluding connecting materialheight 60mm / nominal cover width 400mm length: 1000mm	
<u> </u>	52404 - End piece to leveling bar BOK8880/400	
	Dimensions 360x50x4mm Leveling bar additionally used in caseof non-existent brace	
	52464/0 - End wall BOK 8880/400x60 SK 0	国统格级4国 要是被关键等 学生现象的数
	made of sendzimir-galvanized steel sheet 1.5mm including connecting material height 60mm / lid nominal width 406mm	
<u> </u>	52464 - End wall BOK 8880/400x60 SK	
	made of sendzimir-galvanized steel sheet 1.5mm pressed into special aluminum profile Woertz with temporary protective edge inserted into groove and impact sound trapezoidal rubber as cover supportincluding connecting materialheight 60mm / nominal cover width 400mm	
	52467 - St lid BOK 8880/400 SK BL	
	made of sendzimir-galvanized steel sheet 4mm dimension: 500x400mm with brush strips as cable outlet, for 3mm finished floor height	
	52465 - St lid BOK 8880/400 SK	
	made of sendzimir galvanized steel sheet 4mm dimension: 1000x400mm	
	52469 - St lid BOK 8880/400 SK	
	made of sendzimir galvanized steel sheet 4mm dimension: 500x400mm	
	52466 - St lid BOK 8880/400 SK KD	
	made of sendzimir-galvanized steel sheet 4mm dimension: 500x400mm cable gland enclosed loose	
$\rightarrow$	52472/3 - 0	
	made of aluminum 2mm with galvanized steel sheet insert 2mm getoxt.dimension: 1000x399x7mm edge height inside occupiable: 3mm	
	52468 - St lid BOK 8880/400 SK KMn	

made of sendzimir-galvanized steel sheet 4mm dimension: 500x400mm cable

tray enclosed loose





	52477 - Temporary wooden cover BOK 8880/400	
	to be inserted as a placeholder and protection for the floor channel Dimension: 1000x401x12mm	
	52473/3 - 0	
	made of aluminum 2mm toxtured with galvanized steel sheet insert 2mm. Dimension: 500x399x7mm edge height inside occupiable: 3mm	
Ţ.,	52410/22 - Al protective edge 22 BOK 8880	回标:#4.24回 7.343 7
) N	made of aluminumDimension: 2000x37x3mm	
	52472/12 - 0	回系(#45-84回 552-1354 (#45 552-1354 (#45
	for 12mm edge, to BOK 8880/400,Length: 1000mm	
	52472/22 - 0	
	made of aluminum 3mm dimension: 1000x399x16mm edge height inside 22mm	
	52474/3 - 0	
	of aluminiumdim 500x400edge 3mm cable trough separately enclosed	
-1	52410/3 - Al protective edge 3 BOK 8880	国公共46公共国 开展1990年第二
) N	made of aluminumDimension: 2000x18x3mm	
<u> </u>	52410/12 - Al protective edge 12 BOK 8880	
8 8	made of aluminumDimension: 2000x27x3mm	
· <u>·</u>	52412/3 - Cr protective edge 3 BOK 8880	
** **	made of chrome steel V2Adimension: 2000x18x3mm	
-3	52412/12 - Cr protective edge 12 BOK 8880	
25	made of chrome steel V2Adimension: 2000x27x3mm	
Ť.	52412/22 - Cr protective edge 22 BOK 8880	
× × × × × × × × × × × × × × × × × × ×	made of chrome steel V2Adimension: 2000x37x3mm	
	52473/22 - 0	
	made of aluminum 3mm dimension: 500x399x19mm edge height inside 22mm	
	· · · · · · · · · · · · · · · · · · ·	





	51880 - Cable bushing with filler piece BOK	
	made of polycarbonate crystal clearwith transparent fillerDimension: 86x60x9.5mm	
	52460N - Floor duct BOK 8880/400x60 iN	
	with integrated leveling made of sendzimir galvanized steel sheet 1.5mm pressed into special aluminum profile Woertz on both sides with temporary protective edge inserted into groove and impact sound trapezoidal rubber as cover support leveling hexagonal bolts M10x60 polyamide including connecting material height 60mm / nominal cover width 400mm length: 2000mm	
<u> </u>	52091 - Mounting bracket 1 FLF 3/5 empty BOK	
	made of galvanized sheet steel color: RAL 7032 pebble gray	
	52348 - Insert set empty 4-8LM vertical BOK	
Taraka sa	to BOK 8880/ from 60mm height for modules type Legrand Mosaic 45x45 made of galvanized sheet steel color RAL 7032 pebble gray	
	52469/0 - St lid BOK 8880/400 SK 0	
	made of sendzimir galvanized steel sheet 4mm dimension: 500x406mm	
	51996 - Installation kit Scs 2FLF horizontal empty BOK	
	Low current versionmade of galvanized steel sheet 1.5mm with strain relief stampings and knurled screw for lateral fixing in the trunking shell. Color: RAL 7032 pebble gray	
	55039 - Installation kit socket outlet T13 3FLF horizontal SB BOK	
10000	Installation kit socket T13 3FLF horizontal SB BOK made of galvanized sheet steel 1.5mm with knurled screw for lateral fixing in the trunking shell. Dimension: 302x47(53)x40mm Color: RAL 7032 pebble gray Equipped, wired and tested: 1 pcs. blind terminal 7x2.5mm <sup>2</sup> 10127 3 pcs. socket T13 FLF white 55200 1x L1 / 1x L2 / 1x L3 1 pc. Td-cable 5x1.5mm <sup>2</sup> / 1000mm 1 pc. FK junction box technofil 49909 (10A)	
	52465/0 - St lid BOK 8880/400 SK 0	
	made of sendzimir galvanized steel sheet 4mm dimension: 1000x406	
	52467/0 - St lid BOK 8880/400 SK 0 BL	
	made of sendzimir-galvanized steel sheet 4mm dimension: 500x406mm with brush strips as cable outlet, for 3mm finished floor height	





	52466/0 - St lid BOK 8880/400 SK 0 KD	
dir.	made of sendzimir galvanized steel sheet 4mm dimension: 500x406mm with cable gland	
	52467/0SB - St lid visible BOK 8880/400 SK 0 BL	
	made of sendzimir galvanized steel sheet 4mm dimension:500x406mm with brush strip as cable outlet, top flush for visible lid	
	52468/0 - St lid BOK 8880/400 SK 0 KMn	
The state of the s	made of sendzimir-galvanized steel sheet 4mm dimension 500x406mm with cable trough enclosed loose	
	52479/0SB - Cr lid visible BOK 8880/400 SK 0 BL	
	made of chrome steel V2A 4mm, brushed Dimensions: 490x406mm With brush strip 54x30mm as a cable outlet top flush for visible cover	
	52474/22 - Al lid with rim BOK 22 8880/400 KMn	
	made of aluminum 3mm dimension: 500x399x26mm edge height inside occupiable: 23mm cable trough loosely enclosed	
$\sim$	52474/12 - Al lid with rim BOK 12 8880/400 KMn	国第25条之间 525月12日 687年2月23年
	made of aluminum 3mm dimension: 500x399x16mm edge height inside 13mm cable tray enclosed loose	
	52478/0SB - Cr lid visible BOK 8880/400 SK 0	
	made of chrome steel V2A 4mm, brushed dimension: 990x406mm	
	55019 - Installation kit bticino 2x2-3gang empty BOK	
Table 3.5	made of galvanized sheet steel color: RAL 7032 pebble gray	
A	52402 - Mounting bracket 60 BOK 8880/60	
	made of sheet steel 2.5mm for floor trunking BOK 8880 height 60mm	
1000	55041 - Installation kit socket T23 3FLF horizontal SB BOK	
	Installation kit socket T23 3FLF horizontal SB BOK made of galvanized sheet steel 1.5mm with knurled screw for lateral fixing in the trunking shell. Dimension: 302x47(53)x40mm Color: RAL 7032 pebble gray Equipped, wired and tested: 1 pcs. blind terminal 7x2.5mm <sup>2</sup> 10127 3 pcs. socket T23 FLF white 55210 1x L1 / 1x L2 / 1x L3 1 pc. Td-cable 5x2.5mm <sup>2</sup> / 1000mm 1 pc. FK socket SK ecobus power 5x2.5 <sup>2</sup> Pow 5P 49701P (16A)	





Floor channel BOK 8880 400x60mm integrated leveling device

	52404/100 - Leveling bar connection BOK 8880/400	
	made of sendzimir galvanized steel sheet 4mm dimensions: 360x100mm with 3 leveling hexagonal screws M10x60 polyamide with blind rivets for fastening to channel shell for additional mounting in case of missing connection.	
	55031 - Installation kit Sts 3FLF horizontal empty BOK	
	made of galvanized sheet steel 1.5mm with knurled screw for lateral fixing in the trunking shell. Dimension: 302x47(53)x40mm Color: RAL 7032 pebble gray Equipped: 1 pcs. blind hole clamp 7x2.5mm <sup>2</sup> 10127	
	52344 - Insert Sts 3FLF horizontal SB BOK	
	made of galvanized sheet steel 1.5mm with knurled screw for lateral fixing in the trunking shell Dimensions: 302x47(53)x40mm Color: RAL 7032 pebble gray	
	equipped, wired and tested: 1 pcs. blind hole terminal 7x2.5mm <sup>2</sup> 10127 3 pcs. socket T13 FLF white 55200 1x L1 / 1x L2 / 1x L3 1 pcs. Td cable 5x1.5mm <sup>2</sup> / 1000mm. 1 pc. FK socket SK ecobus power 5x2.5 <sup>2</sup> Pow 5P 49701P (16A)	
	55033 - Installation kit Sts 6FLF horizontal empty BOK	
	made of galvanized sheet steel 1.5mm with knurled screw for lateral fixing in the trunking shell. Dimension: 525x47(53)x40mm Color: RAL 7032 pebble gray Equipped: 1 pcs. blind hole clamp 10x2.5mm <sup>2</sup> 10128	
	51049 - Adjustable cable trough BOK 8880 fDsb	
die.	made of polycarbonate crystal clear for cover visible for mounting with threaded bolt	
	51069 - Cable trough levelable BOK SK 0-21mm	
	made of polycarbonate crystal clear for cover visible for mounting with threaded bolt	
	52407 - Connecting link straight BOK 8880	
	made of sheet steel dimension: 130x10x2.5mm with 4 pieces hexagonal screws M4x8 for connecting the channel shells	
	52408 - Angle connecting link 90° BOK 8880	
	made of sheet steel dimension: 67.5/67.5xx10x2.5mm with 4 pcs hexagonal bolts M4x8	
	for a constant to the selected all a	

for connecting the channel shells





	52415 - U-clamp profile reinforced 1-3mm as edge protection profile for sheet thickness up to 3mm	
•	<b>52420 - Brush strip cpl. BOK 8880 s=6</b> made of plastic, black dimension: 54x35mm bristles length: 25mm	
•	52421 - Brush strip cpl. BOK 8880 s=4 visible made of plastic, black dimension: 54x37mm bristles length: 30mm	