



Product data sheet

30430 - Three-pin terminal DIN35 4mm² PE-L-N gray/blue



Three-stud installation terminal, with stainless steel screws, 4x3-digit designation option, with detachable neutral conductor isolator

Characteristics

Eldas number	158101937
Base Unit	Piece
availability	Delivery according to agreement
EAN Code	7611718204708
group	165000
Packaging unit	25
country of origin	CH
Customs tariff number	8536.9080
Weight (g)	30 g
Color	gray

Technical data

Dimensions length x width x height (mm)	89x6x47.5 mm
Dimensions length x width x height (inch)	3.50x0.24x1.87 inch
Cross section (mm ²)	0,5 - 4 mm ²
Nominal current (A)	34 A



Product data sheet

30430 - Three-pin terminal DIN35 4mm² PE-L-N gray/blue

Rated voltage (V)	400 V
Connection type	Screw terminal
DIN rail type	DIN-35
Number of connection point	4
Number of floor	3
Number of potentials	3
Clamping screw M	M3
Insulating material	PA66
Nominal Cross-section (mm ²)	4 mm ²
Stripping length mm (mm)	8,5 mm
Head reception room width x height (mm)	3.1x3.4 mm
Rating data according to UL 1059	
Rated voltage US (V)	300 V
Nominal cross section (AWG)	12 AWG
Cross-section (AWG)	12 - 20 AWG
Stripping length (inch)	0,34 inch



Product data sheet

30430 - Three-pin terminal DIN35 4mm² PE-L-N gray/blue

Product accessories



81536/2 - Cross-connection 2-pole to three-pole terminals DIN35 4mm²

Insulated cross-connection 2-pole to three-pole terminals DIN35 4mm² including screws M2.5. dimension: 11.1x11.4 mm



81536/3 - Cross-connection 3-pole to three-pole terminals DIN35 4mm²

Insulated cross-connection 3-pole to three-pole terminals DIN35 4mm² including screws M2.5. dimension: 17.2x11.4 mm



81536/4 - Cross-connection 4-pole to three-pin terminals DIN35 4mm²

Insulated cross-connection 4-pole to three-pole terminals DIN35 4mm² including screws M2.5. dimension: 23.3x11.4 mm



81536/5 - Cross-connection 5-pole to three-pin terminals DIN35 4mm²

Insulated cross-connection 5-pole to three-pin terminals DIN35 4mm² including screws M2.5. Dimension: 29.4x11.4 mm



81536/10 - Cross-connection 10-pole to three-pin terminals DIN35 4mm²

Insulated cross-connection 10-pole to three-pin terminals DIN35 4mm² including screws M2.5. dimension: 59.9x11.4 mm



81535 - Cross connection bolt single M2.5 insulated (4.1 mm)

Cross connection bolt complete with spacer sleeve. 4.1 mm



30441 - Link to cross-connections

to terminals 4mm 2



80247 - Test plug Ø 2.3mm red, socket 4mm

connecting cable incl.



80248 - Test plug Ø 2.3mm black, socket 4mm

connecting cable incl.



Bezeichnungskarte_6x9mm - Designation card 6x9mm

Various designation plates with different embossing.



Bezeichnungskarte_6x3mm - Designation card 6x3mm

Various designation plates with different embossing.



Product data sheet

30430 - Three-pin terminal DIN35 4mm² PE-L-N gray/blue



30439 - End barrier and rail holder DIN35

End wall suitable for 30430



3418 - Stopper DIN35 height 30mm

Makrolon locking piece



3859 - Busbar Cu 10x2mm length 1000mm

to neutral disconnecting terminals and terminals for busbars



3856 - Busbar Cu 10x3mm length 1000mm

to neutral disconnecting terminals and terminals for busbars



Product data sheet

30430 - Three-pin terminal DIN35 4mm² PE-L-N gray/blue

Product systems



Three-stud installation clamps DIN 35

Various three-stud installation clamps.

