



Product data sheet

43231/F - Shielding terminal C30 12-16mm



made of stainless steel A4, with screw and spring made of stainless steel for profile rails no. 4382IN and 4383IN

Characteristics	
Eldas number	158031017
Base Unit	Piece
availability	Delivery according to agreement
EAN Code	7611718218767
group	177000
Packaging unit	100
country of origin	СН
Customs tariff number	8536.9080
Weight (g)	25 g
Technical data	
Dimensions length x width x height (mm)	40 x 19.5 x 56(max)/37(min) mm
Material	Stainless steel
Clampable diameter (mm)	12-16 mm





Product data sheet

43231/F - Shielding terminal C30 12-16mm

Product accessories

070	80170/50 - Bare earthing terminal 50mm2 with anchoring stud for mounting rail C30
	80170/16 - Bare earthing terminal 16mm2 with anchoring stud for mounting rail C30
	4382IN/3M - Profile rail C30 stainless steel V2A 3 m Profile rail C30 with 29x15x2 mm made of stainless steel V2A, with a length of 3 m.
	4383IN/3M - Profile rail C30 stainless steel V2A 3 m Profile rail C30 with 32x18x3 mm made of stainless steel V2A, with a length of 3 m.





Product data sheet

43231/F - Shielding terminal C30 12-16mm

Product systems



Shielding terminals type C30 stainless steel A4 with screw



- With screw and with stainless steel spring
- The profile rails serve as a busbar
- Is suitable for installations where strong vibrations and large temperature differences may occur
- With spring to prevent independent loosening of the screw, adjust the vulnerability of the screen.
 - Remove cable jacket, expose shield
 - Handle like quick installer
 - Do not use as a cable fastener!