



Product data sheet

43712 - Shielding terminal C30 8.5-12.5mm



made of aluminum alloy, hardened

Characteristics	
Eldas number	158600117
Base Unit	Piece
availability	Delivery in 4 weeks
EAN Code	7611718229848
group	177000
Packaging unit	50
country of origin	CH
Customs tariff number	8536.9080
Weight (g)	65 g
Technical data	
Dimensions length x width x height (mm)	32x22x56 mm
Material	PA 6.6
Clampable diameter (mm)	8.5-12.5 mm
Rated voltage (V)	600 V
Smallest connectable section (mm²)	0,5 mm²



Product data sheet

43712 - Shielding terminal C30 8.5-12.5mm



Clamping screw M	5
Stripping length mm (mm)	13 mm
Ladder mounting space Height (mm)	6,2 mm
Ladder mounting space Width (mm)	6.7 mm
Rating data according to UL 1059	
Smallest connectable section (AWG)	18 AWG
Stripping length (inch)	0,51 inch



Product data sheet

43712 - Shielding terminal C30 8.5-12.5mm

Product accessories

	80170/16 - Bare earthing terminal 16mm2 with anchoring stud for mounting rail C30
	80170/50 - Bare earthing terminal 50mm2 with anchoring stud for mounting rail C30



Product data sheet

43712 - Shielding terminal C30 8.5-12.5mm

Product systems



Shielding terminals type C30 made of hardened aluminum alloy



- With pin and with spring
 - Profile rails No. 4382,4383 and 80291, type C30 serves as busbar
 - Remove cable sheath, expose shield
 - Handle like quick installer
 - With steel spring that creates contact without damaging shield
 - Do not use as a cable fastener!
-