



52468 - St lid BOK 8880/400 SK KMn



made of sendzimir-galvanized steel sheet 4mm dimension: 500x400mm cable tray enclosed loose

Characteristics	
Base Unit	Piece
availability	Delivery according to agreement
group	282000
Packaging unit	1
country of origin	СН
Customs tariff number	7308.9000
Weight (g)	6220 g
Technical data	
Material	PA 6.6
Rated voltage (V)	800 V
Nominal mass	400
Smallest connectable section (mm²)	0,5 mm²
Stripping length mm (mm)	12 mm
Rating data according to UL 1059	
Rated voltage US (V)	600 V





52468 - St lid BOK 8880/400 SK KMn

Smallest connectable section (AWG)	22 AWG
Stripping length (inch)	0,47 inch





52468 - St lid BOK 8880/400 SK KMn

Product accessories





52468 - St lid BOK 8880/400 SK KMn

Product systems

Floor channel BOK 8880 400x50mm on leveling device Floor channel BOK 8880 400x50mm on leveling device.	
Floor channel BOK 8880 400x60mm on leveling device Floor channel BOK 8880 400x60mm on leveling device.	
Floor channel BOK 8880 400x80mm on leveling device Floor channel BOK 8880 400x80mm on leveling device.	
Floor channel BOK 8880 400x50mm integrated leveling device Floor channel BOK 8880 400x50mm with integrated leveling device.	
Floor channel BOK 8880 400x60mm integrated leveling device Floor channel BOK 8880 400x60mm with integrated leveling device.	
Floor channel BOK 8880 400x80mm integrated leveling device Floor channel BOK 8880 400x80mm with integrated leveling device.	