



49345/4F25/C1 - Pre-wired connection C1-F 5G2.5 4m HF



Pre-wired connector, socket 5-poles code 1 with 4 m cable 5G2.5 mm ² with free end, conductor compressed, 20 A, 250/400 V, halogen free, behaviour to fire classification Cca

Characteristics	
Eldas number	157500657
Base Unit	Piece
availability	Delivery according to agreement
EAN Code	7611718280153
group	170000
Packaging unit	1
country of origin	СН
Customs tariff number	8544.4229
Weight (g)	731 g
Color	purple
Connector type	Connection cable socket
Coding plug connection	Code 1
Technical data	
Dimensions length x width x height (mm)	4000 x 52.3 x 13.7 mm
Dimensions length x width x height (inch)	157 x 2.06 x 0.54 inch





49345/4F25/C1 - Pre-wired connection C1-F 5G2.5 4m HF

Degree of protection	IP20, IP40 (Connected),IP68 (with sealing cover)
Number of poles	5 pole
Material	Polyamide
Construction (mm²)	5x2.5 mm²
Rated current heavy current part (A)	20 A
Rated voltage heavy current part (V)	250/400 V
Cable length (m)	4 m
Halogen free	Yes
Cable type	Halogen free cables
International designation	N05Z1Z1-F
Reaction to fire classification	Cca s1 d0 a1
Cross section (mm²)	2.5 mm²
Copper conductor	Fine stranded KL5 EN60228
cores insulation	Flame retardant polyolefin
Cores colors	brown,blue,green/yellow,black,gray
Sheat insulation	Polyolefin flame retardant
Sheath color	Black
Minimum bending radius	6xD
Operating Temperature (°C)	-15 till 70 °C
Installation temperature min. (°C)	5 °C
Test current heavy current part (kV)	4 kV





49345/4F25/C1 - Pre-wired connection C1-F 5G2.5 4m HF

Halogen free acc. to	IEC/EN60754-1/2
Flame retardant according to	IEC/EN60332-1-2
Minimal smoke emision acc. to	IEC/EN 61034-2





49345/4F25/C1 - Pre-wired connection C1-F 5G2.5 4m HF

Product accessories





49345/4F25/C1 - Pre-wired connection C1-F 5G2.5 4m HF

Product systems



Plug connections code 1 for mains voltage, 3-pole (LNPE)

3 pole connectors code 1 for mains voltage.

