



3427E - Terminal block DIN35 16mm² 55x11x55mm green-yellow insulated



Terminal block DIN35 16mm² 55x11x55mm green-yellow insulated with best possible contacting, stainless steel screws, 4-digit marking possibility on both sides, recessed for cross-connections

Characteristics	
Eldas number	158120567
Base Unit	Piece
availability	Delivery according to agreement
EAN Code	7611718205538
group	165000
Packaging unit	20
country of origin	СН
Customs tariff number	8536.9080
Weight (g)	46 g
Color	green/yellow
Technical data	
Dimensions length x width x height (mm)	55x11x55 mm
Dimensions length x width x height (inch)	2.17x0.43x2.17 inch
Cross section (mm²)	1,5 - 16 mm²
Nominal current (A)	76 A





3427E - Terminal block DIN35 16mm² 55x11x55mm green-yellow insulated

Rated voltage (V)	1000 V
Connection type	Screw terminal
DIN rail type	DIN-35
Smallest connectable section (mm²)	1,5 mm²
Number of connection point	2
Number of floor	1
Number of potentials	1
Clamping screw M	M5 (M = 2.5Nm)
Central thread M	M4 (M = 1.5Nm)
Insulating material	PA66
Nominal Cross-section (mm²)	16 mm²
Stripping length mm (mm)	13 mm
conductors of the same cross-section per clamping point EN60947 (mm²)	1x16 , 2x10 , 2x6 mm²
Head reception room width x height (mm)	7.3x8.6 mm
Rating data according to UL 1059	
Rated voltage US (V)	600 V
Nominal cross section (AWG)	6 AWG
Cross-section (AWG)	4 - 14 AWG
Smallest connectable section (AWG)	16 AWG
Stripping length (inch)	0,51 inch
Tightening torque (Ib-inch)	22,13 lb-inch





3427E - Terminal block DIN35 16mm² 55x11x55mm green-yellow insulated

Product accessories

Ħ	81501/2 - Cross-connection 2-pole to DIN35 16mm² terminal blocks Insulated cross-connection 2-pole to terminal blocks DIN35 16mm² including screws M4. Dimension: 20x29.8 mm
	81501/3 - Cross-connection 3-pole to DIN35 16mm² terminal blocks Insulated cross-connection 3-pole to terminal blocks DIN35 16mm² including screws M4. Dimension: 31x29.8 mm
	81501/4 - Cross-connection 4-pole to DIN35 16mm² terminal blocks Insulated cross-connection 4-pole to terminal blocks DIN35 16mm² including screws M4. Dimension: 42x29.8 mm
	81501/5 - Cross-connection 5-pole to DIN35 16mm² terminal blocks Insulated cross-connection 5-pole to terminal blocks DIN35 16mm² including screws M4. Dimension: 53x29.8 mm
	81501/10 - Cross-connection 10-pole to DIN35 16mm² terminal blocks Insulated cross-connection 10-pole to terminal blocks DIN35 16mm² including screws M4. Dimension: 108x29.8 mm
	81501 - Separate connecting pin M4 insulated Cross connection bolt complete with spacer sleeve
	81414L - Link to cross-connections to terminals 16mm 2
	Bezeichnungskarte_6x12mm - Designation cards 6x12mm Various designation labels 6x12mm with different embossing.
	Bezeichnungskarte_6x9mm - Designation card 6x9mm Various designation plates with different embossing.
	Bezeichnungskarte_6x3mm - Designation card 6x3mm Various designation plates with different embossing.
	80071R - Test plug Ø M4 red, socket 4mm plug and adaptor in one piece





3427E - Terminal block DIN35 16mm² 55x11x55mm green-yellow insulated

	3518 - End barrier DIN35 grey to 3427
	End wall suitable for 3427
	3508 - Partition DIN35 grey to 3427
	Partition wall suitable for 3427
	3418 - Stopper DIN35 height 30mm
	Makrolon locking piece
	30370 - Stopper DIN35 height 23mm
	Locking piece made of nickel-plated brass M3 screw
	30199 - Stopper DIN35 height 50mm
	Aluminum alloy locking piece
Woertz @ 38855	3868/4 - Cover for 4 terminals yellow
	with black printing, to series 3427,345216
A Partie	3868/5 - Cover for 5 terminals yellow
	with black printing, to series 3427,345216
- Market	3868/6 - Cover for 6 terminals yellow
	with black printing, to series 3427,345216
	3868/7 - Cover for 7 terminals yellow
	with black printing, to series 3427,345216
Service Control of the Control of th	3868/8 - Cover for 8 terminals yellow
	with black printing, to series 3427,345216
	81441 - Sealing eyelet Ø 4.2mm
	Sealing eyes





3427E - Terminal block DIN35 16mm² 55x11x55mm green-yellow insulated

Product systems



Terminal blocks for high demands DIN35



