



3880BL - Double level terminal block DIN32 4mm² blue



Double level clamp DIN32 4mm² blue with stainless steel screws, recessed for cross connections, 2x3-digit marking option on both sides

Characteristics	
Eldas number	158202257
Base Unit	Piece
availability	Delivery in 4 weeks
EAN Code	7611718201394
group	165000
Packaging unit	50
country of origin	СН
Customs tariff number	8536.9080
Weight (g)	16,7 g
Color	blue
Technical data	
Dimensions length x width x height (mm)	62x6x48 mm
Dimensions length x width x height (inch)	2.44x0.24x1.89 inch
Cross section (mm ²)	0,5 - 4 mm²
Nominal current (A)	20 A





3880BL - Double level terminal block DIN32 4mm² blue

Rated voltage (V)	500 V
Connection type	Screw terminal
DIN rail type	DIN-32
Number of connection point	4
Number of floor	2
Number of potentials	2
Clamping screw M	МЗ
Insulating material	PA66
Nominal Cross-section (mm ²)	4 mm²
Stripping length mm (mm)	10 mm
Head reception room width x height (mm)	3.2x5 mm
Rating data according to UL 1059	
Rated voltage US (V)	300 V
Nominal cross section (AWG)	12 AWG
Cross-section (AWG)	12 - 20 AWG
Stripping length (inch)	0,39 inch





3880BL - Double level terminal block DIN32 4mm² blue

Product accessories

	80222/6 - Test adaptor to terminal series 3450 2 spiral springs with hole for strands up to 0.75mm 2
	Bezeichnungskarte_6x9mm - Designation card 6x9mm Various designation plates with different embossing.
	Bezeichnungskarte_6x3mm - Designation card 6x3mm Various designation plates with different embossing.
Ħ	81526/2 - Cross-connection 2pole to terminal 2.5mm2/4mm2 Cross connections complete with M3 screws. 11.1x17.8 mm
ĦĦ	81526/3 - Cross-connection 3-pole to terminals DIN15/32/35 2.5mm²/4mm² Insulated cross-connection 3-pole to terminals DIN15/32/35 2.5mm²/4mm² including screws M3. Dimension: 17.2x17.8 mm
	81526/4 - Cross-connection 4-pole to terminals DIN15/32/35 2.5mm²/4mm² Insulated cross-connection 4-pole to terminals DIN15/32/35 2.5mm²/4mm² including screws M3. Dimension: 23.3x17.8 mm
	81526/5 - Cross-connection 5-pole to terminals DIN15/32/35 2.5mm²/4mm² Insulated cross-connection 5-pole to terminals DIN15/32/35 2.5mm²/4mm² including screws M3. Dimension: 29.4x17.8 mm
	81526/10 - Cross-connection 10-pole to terminals DIN15/32/35 2.5mm²/4mm² Insulated cross-connection 10-pole to terminals DIN15/32/35 2.5mm²/4mm² including screws M3. Dimension: 59.9x17.8 mm
Ī	81526 - Cross connection bolt single M3, insulated (9.1 mm) Cross connection bolt complete with spacer sleeve. 9.1 mm
	30441 - Link to cross-connections to terminals 4mm 2
- D	3894/4 - Cover for 4 terminals yellow with black printing, to series 3430





3880BL - Double level terminal block DIN32 4mm² blue

- A	3894/5 - Cover for 5 terminals yellow with black printing, to series 3430
- D	3894/6 - Cover for 6 terminals yellow with black printing, to series 3430
- D	3894/7 - Cover for 7 terminals yellow with black printing, to series 3430
- D	3894/8 - Cover for 8 terminals yellow with black printing, to series 3430
Ļ	81440 - Sealing eyelet Ø 3.2mm Sealing eyes
ANT	3512 - Sealing screw M3x25 of polyamide Sealing screw spring-loaded test probes, several numbers of poles can be lined up
annan	30421 - Cover strip for double level and terminal blocks 9.5mm, length 280mm Cover strip for double level and terminal blocks DIN32/35 9.5mm, length 280mm





3880BL - Double level terminal block DIN32 4mm² blue

Product systems

Double deck clamps DIN32

Various double deck clamps DIN32.

