



Product data sheet

9052 - Supply / Junction box FC multibus / Technofil 3xØ8.5 mm



Supply box at the cable end and Flat cable connection for flat cable multibus

Characteristics	
Eldas number	150706037
Base Unit	Piece
availability	available from stock
EAN Code	7611718208836
group	170000
Packaging unit	50
country of origin	CH
Customs tariff number	8536.9080
Weight (g)	46,7 g
Color	gray
Technical data	
Box Type	Feeding sockets
Fire load (KWh)	0,11 kWh
Dimensions length x width x height (mm)	70x40x18 mm
Dimensions length x width x height (inch)	2,75x1,57x0,71 inch



Product data sheet

9052 - Supply / Junction box FC multibus / Technofil 3xØ8.5 mm

Degree of protection	IP20
Metal parts	Corrosion protected
Flat cable contacting type	Piercing contact (screw)
Number of poles	4 pole
Connection conductor (mm²)	1,5 mm²
Connecting capacity (mm)	3,3 mm
Rated current heavy current part (A)	16 A
Rated voltage heavy current part (V)	500 V
Operating Temperature (°C)	-15 to 85 °C
Installation temperature min. (°C)	5 °C
Plastic parts	Halogen-free
Material slider/bottom part	Polyamide, gray
Material housing	Polyamide, gray
Material hood	Polyamide, gray
Number Screwdriver Clamping screws Heavy current part	1
Tightening torque for clamping screw (Nm)	0,7 Nm



Product data sheet

9052 - Supply / Junction box FC multibus / Technofil 3xØ8.5 mm

Product accessories



49665 - PVC round cable 4x0.75 mm² SW

Round cable PVC flexible 4x0.75 mm²



Product data sheet

9052 - Supply / Junction box FC multibus / Technofil 3xØ8.5 mm

Product systems



Flat cable system Multibus 4x1.5 mm²

Smart solutions for building control. Ideal for extra-low voltage, heating, ventilation, air conditioning and Belimo MP-Bus. Meets SMI LoVo requirements. Optimize your building technology!

