



Product data sheet

3400A - Combination rail DIN35/DIN15 of aluminum 2 m



Combination rail Extrudal-050 DIN35/DIN15, with 35x7.5x3.3 mm, made of aluminum alloy, with a 35 mm² copper cross-section, 2 m length

Characteristics	
Eldas number	168000327
Base Unit	Meter
availability	Delivery in 4 weeks
EAN Code	7611718247781
group	165000
Packaging unit	2
country of origin	CH
Customs tariff number	7216.9900
Weight (g)	263 g
Technical data	
Dimensions length x width x height (mm)	110x51x81 mm
Dimensions length x width x height (inch)	4.33x2.01x3.19 inch
Rated voltage (V)	300 V
DIN rail type	DIN-35
Number of connection point	2



Product data sheet

3400A - Combination rail DIN35/DIN15 of aluminum 2 m

Number of floor	1
Number of potentials	1
Nominal Cross-section (mm²)	150 mm²
Ladder mounting space Width (mm)	16 mm
Ladder mounting space Height (mm)	36 mm



Product data sheet

3400A - Combination rail DIN35/DIN15 of aluminum 2 m

Product accessories



Product data sheet


3400A - Combination rail DIN35/DIN15 of aluminum 2 m

Product systems



Profile rail DIN15

DIN rail DIN15, universal carrier made of a sheet metal profile in electrical engineering for fastening electrical equipment in distribution boxes, control cabinets, junction boxes, etc. Different components (for example relays, impulse switches, timers, circuit breakers, terminal blocks) can be slid onto a carrier rail from the side or plugged on and locked from the front. This standardized method facilitates the assembly of control cabinets and switch boxes, thus reducing labor costs. The different types of rails are in the standard EN 60715.



Profile rails DIN15, DIN32, DIN35

Various mounting rails and combination rails.



Profile rails DIN35

DIN rail DIN35, universal carrier made of a sheet metal profile in electrical engineering for fastening electrical equipment in distribution boxes, control cabinets, junction boxes, etc. Different components (e.g. relays, impulse switches, timers, circuit breakers, terminal blocks) can be slid onto a carrier rail from the side or plugged in and locked from the front. This standardized method facilitates the assembly of control cabinets and switch boxes, thus reducing labor costs. The different types of rails are in the standard EN 60715.

